

**\* ENGINE SYSTEMS UNIFORM INSPECTION GUIDELINES \***  
**Article Text**

This file passed thru Volkswagen Technical Site - <http://volkswagen.msk.ru>

**ARTICLE BEGINNING**

**GENERAL INFORMATION**

**Engine Performance and Maintenance - January 2002 Motorist Assurance Program Standards For Automotive Repair**

**All Makes and Models**

**INTRODUCTION TO MOTORIST ASSURANCE PROGRAM (MAP)**

**OVERVIEW**

The Motorist Assurance Program is the consumer outreach effort of the Automotive Maintenance and Repair Association, Inc. (AMRA). Participation in the Motorist Assurance Program is drawn from retailers, suppliers, independent repair facilities, vehicle manufacturers and industry associations.

Our organization's mission is to strengthen the relationship between the consumer and the auto repair industry. We produce materials that give motorists the information and encouragement to take greater responsibility for their vehicles-through proper, manufacturer-recommended, maintenance. We encourage participating service and repair shops (including franchisees and dealers) to adopt (1) a Pledge of Assurance to their Customers and (2) the Motorist Assurance Program Standards of Service. All participating service providers have agreed to subscribe to this Pledge and to adhere to the promulgated Standards of Service demonstrating to their customers that they are serious about customer satisfaction.

These Standards of Service require that an inspection of the vehicle's (problem) system be made and the results communicated to the customer according to industry standards. Given that the industry did not have such standards, the Motorist Assurance Program successfully promulgated industry inspection communication standards in 1994-95 for the following systems: Exhaust, Brakes, ABS, Steering and Suspension, Engine Maintenance and Performance, HVAC, and Electrical Systems. Further, revisions to all of these inspection communication standards are continually republished. In addition to these, standards for Drive Train and Transmissions have recently been promulgated. Participating shops utilize these Uniform Inspection & Communication Standards as part of the inspection process and for communicating their findings to their customers.

The Motorist Assurance Program continues to work cooperatively and proactively with government agencies and consumer groups toward solutions that both benefit the customer and are mutually acceptable to both regulators and industry. We maintain the belief that industry must retain control over how we conduct our business, and we must be viewed as part of the solution and not part of the problem. Meetings with state and other government officials (and their representatives), concerned with auto repair and/or consumer protection, are conducted. Feedback from these sessions is brought back to the association, and the program adjusted as needed.

To assure auto repair customers recourse if they were not satisfied with a repair transaction, the Motorist Assurance Program offers mediation and arbitration through MAP/BBB-CARE and other non-profit organizations. MAP conducted pilot programs in twelve states before announcing the program nationally in October, 1998. During the pilots, participating repair shops demonstrated their adherence to the Pledge and Standards and agreed to follow the UICS in communicating the results of their inspection to their customers. To put some "teeth" in the program, an accreditation requirement for shops was initiated. The requirements are stringent, and a self-policing method has been incorporated which includes the "mystery shopping" of

outlets.

We welcome you to join us as we continue our outreach... with your support, both the automotive repair industry and your customers will reap the benefits. Please visit MAP at our Internet site [www.motorist.org](http://www.motorist.org) or contact us at:

7101 Wisconsin Avenue  
Bethesda, MD 20814

Phone: (301) 634-4955  
Fax: (202) 318-3078  
E-mail: [map@motorist.org](mailto:map@motorist.org)

January 2002

## OVERVIEW OF SERVICE REQUIREMENTS AND SUGGESTIONS

It is MAP policy that all exhaust, brake, steering, suspension, wheel alignment, drive-line, engine performance and maintenance, and heating, ventilation and air conditioning, and electrical services be offered and performed under the standards and procedures specified in these sections.

Before any service is performed on a vehicle, an inspection of the appropriate system must be performed. The results of this inspection must be explained to the customer and documented on an inspection form. The condition of the vehicle and its components will indicate what services/part replacements may be "Required" or "Suggested." In addition, suggestions may be made to satisfy the requests expressed by the customer.

When a component is suggested or required to be repaired or replaced, the decision to repair or replace must be made in the customer's best interest, and at his or her choice given the options available.

This section lists the various parts and the conditions that indicate a required or suggested service or part replacement. Although this list is extensive, it is not fully inclusive. In addition to this list, a technician may make a suggestion. However, any suggestions must be based on substantial and informed experience, or the vehicle manufacturer's recommended service interval and must be documented.

Some conditions indicate that service or part replacement is required because the part in question is no longer providing the function for which it is intended, does not meet a vehicle manufacturer's design specification or is missing.

- \* Example: An exhaust pipe has corroded severely and has a hole in it through which exhaust gases are leaking. Replacement of the exhaust pipe in this case is required due to functional failure.
- \* Example: A brake rotor has been worn to the point where it measures less than the vehicle manufacturer's discard specifications. Replacement of the rotor is required because it does not meet design specifications.

Some conditions indicate that a service or part replacement is suggested because the part is close to the end of its useful life or addresses a customer's need, convenience or request. If a customer's vehicle has one of these conditions, the procedure may be only to suggest service.

- \* Example: An exhaust pipe is rusted, corroded or weak, but no leaks are present. In this case, the exhaust pipe has not failed. However, there is evidence that the pipe may need



Condition	Code	Procedure
Adjustable valve lash is out of specification ...	B	Require repair.
Combustion efficiency is reduced due to carbon deposits in the combustion chamber ...	2	Suggest repair.
Combustion efficiency is reduced due to carbon deposits on the intake valve .....	2	Suggest repair.
Internal component failure (any component) .....	A	(1) Require repair or replacement of cylinder head assembly.

(1) - It is Required that all other failure-related components be inspected for cause and condition. Additional components or assemblies may be Suggested for repair or replacement, such as a water pump on a short block (reason code 4, technician's recommendation based on substantial and informed experience).

**Example:**

If there is a failed head gasket with an external coolant leak, in addition to Requiring replacement of the head gasket, inspection of the following for cause and condition is Required: Block, Cooling System, Cylinder Head. It may be Suggested that additional inspections be performed, such as the other head gasket on a V-type engine.

AA

**LONG BLOCK ASSEMBLIES**

**NOTE:** A Long Block Assembly is a short block assembly together with a cylinder head assembly and all those components fitted within the rocker or cam cover, and timing cover (the whole presented as an assembly). A rebuilt or new oil pump, or kit shall be supplied or fitted as appropriate.

**LONG BLOCK ASSEMBLY INSPECTION**

AA

Condition	Code	Procedure
Combustion efficiency is reduced due to carbon deposits in the combustion chamber ...	2	Suggest repair.
Internal component failure (any component) .....	A	(1) Require repair or replacement of the long block assembly.

(1) - It is Required that all other failure-related components be inspected for cause and condition. Additional components or assemblies may be Suggested for repair or replacement such as a water pump on a short block (reason code 4, technician's recommendation based on substantial and informed experience).

**Example:**

If there is a failed head gasket with an external coolant

leak, in addition to Requiring replacement of the head gasket, inspection of the following for cause and condition is Required: Block, Cooling System, Cylinder Head. It may be Suggested that additional inspections be performed, such as the other head gasket on a V-type engine.

AA

SHORT BLOCK ASSEMBLIES

NOTE: A Short Block Assembly is a cylinder block and all those components contained within the limits of the block deck or decks, the pan rail, the block rear face and the timing cover (where fitted), including the crankshaft.

SHORT BLOCK ASSEMBLY INSPECTION

AA

Condition	Code	Procedure
Combustion efficiency is reduced due to carbon deposits in the combustion chamber	... 2	..... Suggest repair.
Internal component failure (any component)	..... A	..... (1) Require repair or replacement of the short block assembly.

(1) - It is Required that all other failure-related components be inspected for cause and condition. Additional components or assemblies may be Suggested for repair or replacement, such as a water pump on a short block (reason code 4, technician's recommendation based on substantial and informed experience).

Example:

If there is a failed head gasket with an external coolant leak, in addition to Requiring replacement of the head gasket, inspection of the following for cause and condition is Required: Block, Cooling System, Cylinder Head. It may be Suggested that additional inspections be performed, such as the other head gasket on a V-type engine.

AA

ENGINE COMPONENTS

ACCELERATOR PEDAL POSITION SENSORS

ACCELERATOR PEDAL POSITION SENSOR INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing	..... C	..... Require replacement of hardware.
Attaching hardware threads damaged	..... A	... Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing)	..... A	... Require repair or replacement of hardware.
Connector broken	..... A	.. Require repair or replacement.

Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Inoperative .....	B	.....	(2) Require repair or replacement. Further inspection required.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

(2) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

ACCESSORY BELTS

ACCESSORY BELT INSPECTION

AA

Condition	Code		Procedure
Alignment incorrect .....	B	.....	(1) Further inspection required.
Cracked .....	1	.....	Suggest replacement.
Frayed .....	1	.....	Suggest replacement.
Missing .....	C	.....	Require replacement.
Noisy .....	2	.....	(2) Further inspection required.
Plies separated .....	A	.....	Require replacement.
Tension out of specification .....	B	.....	Require adjustment or replacement.
Worn beyond adjustment range .....	B	.....	Require replacement.
Worn so it contacts bottom of pulley .....	A	.....	Require replacement.

(1) - Determine cause of incorrect alignment and require repair.

(2) - Determine cause of noise and suggest repair.

AA

ACCESSORY PULLEYS

ACCESSORY PULLEY INSPECTION

AA

Condition	Code	Procedure
Alignment incorrect .....	B ..	Require repair or replacement.
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Bent .....	A .....	Require replacement.
Cracked .....	A .....	Require replacement.
Loose .....	A ..	Require repair or replacement.
Missing .....	C .....	Require replacement.
Pulley damaged, affecting belt life .....	A .....	Require replacement.

AA

ACTUATORS

See SENSORS AND ACTUATORS.

AIR CONDITIONING CYCLING SWITCHES

AIR CONDITIONING CYCLING SWITCH INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware threads damaged .....	A ...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A ...	Require repair or replacement of hardware.
Connector broken .....	A ..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	C .....	Require replacement.
Contaminated .....	A .....	(2) Require repair or replacement.
Inoperative .....	B .....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A ..	Require repair or replacement.
Missing .....	C .....	Require replacement.
Resistance out of specification .....	B ..	Require repair or replacement.
Restricted, affecting performance .....	A ..	Require repair or replacement.
Terminal broken .....	A ..	Require repair or replacement.

Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

AIR CONDITIONING PRESSURE SENSORS

AIR CONDITIONING PRESSURE SENSOR INSPECTION

AA

Condition	Code		Procedure
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware threads damaged .....	A	...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	...	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Contaminated .....	A	.....	(2) Require repair or replacement.
Inoperative .....	B	.....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.

Restricted, affecting performance .....	A	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

AIR DUCTS AND TUBES

AIR DUCT AND TUBE INSPECTION

AA

Condition	Code		Procedure
Attaching hardware broken .....	A	...	Require repair or replacement of hardware.
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware not functioning .....	A	...	Require repair or replacement of hardware.
Leaking .....	A	..	Require repair or replacement.
Missing .....	C	.....	Require replacement.
Restricted, affecting performance .....	A	..	Require repair or replacement.

AA

AIR FILTER ELEMENTS

AIR FILTER ELEMENT INSPECTION

AA

Condition	Code		Procedure
Leaking .....	A	.....	Require replacement.
Paper filter element			

oil-soaked .....	A	.....	(1) Require replacement.
Maintenance intervals ...	3	...	Suggest replacement to comply with vehicle's OEM recommended service intervals.
Melted .....	A	.....	Required replacement.
Missing .....	C	.....	Require replacement.
Restricted, affecting performance .....	A	.....	Require replacement.
Water-contaminated .....	A	.....	(1) Require replacement.

(1) - Further inspection required to determine cause.

AA

AIR FILTER GASKETS

See AIR FILTER HOUSINGS AND GASKETS.

AIR FILTER HOUSINGS AND GASKETS

AIR FILTER HOUSING AND GASKET INSPECTION

AA

Condition	Code		Procedure
Attaching hardware broken .....	A	...	Require repair or replacement of hardware.
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware not functioning .....	A	...	Require repair or replacement of hardware.
Leaking .....	A	..	Require repair or replacement.
Missing .....	C	.....	Require replacement.

AA

AIR FUEL RATIO SENSORS

AIR FUEL RATIO SENSOR INSPECTION

AA

Condition	Code		Procedure
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware threads damaged .....	A	...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	...	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Contaminated .....	A	.....	(2) Require repair or replacement.
Inoperative .....	B	.....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.

Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.
Restricted, affecting performance .....	A	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

AIR INJECTION CONTROL SOLENOIDS

AIR INJECTION CONTROL SOLENOID INSPECTION

AA

Condition	Code		Procedure
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware threads damaged .....	A	..	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	..	Require repair or replacement of hardware.
Connector broken .....	A	.	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	.	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Inoperative .....	B	.....	(2) Require repair or replacement. Further inspection required.
Leaking .....	A	.	Require repair or replacement.

Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	.	Require repair or replacement.
Restricted, affecting performance .....	A	.	Require repair or replacement.
Terminal broken .....	A	.	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	.	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	.	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	.	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	.	Require repair or replacement.
Terminal loose, not affecting performance ..	1	.	Suggest repair or replacement.
Threads damaged .....	A	.	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	.	Require repair or replacement.
Wire lead corroded .....	A	.	Require repair or replacement.
Wire lead open .....	A	.	Require repair or replacement.
Wire lead shorted .....	A	.	Require repair or replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

(2) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

AIR PLENUMS

AIR PLENUM INSPECTION

AA

Condition	Code		Procedure
Integrated air or fuel control components inoperative .....	A	.....	(1) Require repair or replacement.
Internal air or fuel components damaged, affecting performance ..	A	...	Require repair or replacement of component.
Internal air or fuel components damaged, not affecting performance ..	..	.....	No service suggested or required.
Internal air or fuel components missing .....	C	.....	Require replacement of component.
Leaking .....	A	..	Require repair or replacement.
Restricted .....	A	..	Require repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	..	Require repair or replacement.

(1) - Inoperative includes intermittent operation or out of OEM specification.

AA

AIR PUMP BELTS

AIR PUMP BELT INSPECTION

AA

Condition	Code	Procedure
Alignment incorrect .....	B .....	(1) Further inspection required.
Cracked .....	1 .....	Suggest replacement.
Frayed .....	1 .....	Suggest replacement.
Maintenance intervals ...	3 ...	Suggest replacement to comply with vehicle OEM recommended service intervals.
Missing .....	C .....	Require replacement.
Noisy .....	2 .....	(2) Further inspection required.
Plies separated .....	A .....	Require replacement.
Tension out of specification .....	B .....	Require adjustment or replacement.
Worn beyond adjustment range .....	B .....	Require replacement.
Worn so it contacts bottom of pulley .....	A .....	Require replacement.

- (1) - Determine cause of incorrect alignment and require repair.
- (2) - Determine cause of noise and suggest repair.

AA

AIR PUMPS (ELECTRIC-DRIVEN)

AIR PUMP (ELECTRIC-DRIVEN) INSPECTION

AA

Condition	Code	Procedure
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Connector broken .....	A ..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	C .....	Require replacement.
Inoperative .....	A .....	(2) Require replacement.
Leaking .....	A .....	Require replacement.
Missing .....	C .....	Require replacement.
Noisy .....	2 .....	Suggest replacement.
Terminal broken .....	A ..	Require repair or replacement.
Terminal burned, affecting performance .....	A .....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A ..	Require repair or replacement.



Condition	Code	Procedure
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Conductor exposed .....	A .....	Require replacement.
Connector broken .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	C .....	Require replacement.
Inoperative .....	A .....	(2) Require replacement.
Insulation overheated ...	A .....	Require replacement.
Terminal broken .....	A ..	Require repair or replacement.
Terminal burned, affecting performance .....	A .....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A ..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B ..	Require repair or replacement.
Terminal loose, not affecting performance ..	1 ..	Suggest repair or replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

(2) - Inoperative includes intermittent operation or out of OEM specification.

AA

BAROMETRIC PRESSURE SENSORS

BAROMETRIC PRESSURE SENSOR INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware threads damaged .....	A ...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A ...	Require repair or replacement of hardware.
Connector broken .....	A ...	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	C .....	Require replacement.
Contaminated .....	A .....	(2) Require repair or replacement.
Inoperative .....	B .....	(3) Require repair or

				replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.	
Missing .....	C	.....	Require replacement.	
Resistance out of specification .....	B	..	Require repair or replacement.	
Restricted, affecting performance .....	A	..	Require repair or replacement.	
Terminal broken .....	A	..	Require repair or replacement.	
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.	
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.	
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.	
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.	
Terminal loose, affecting performance .....	B	..	Require repair or replacement.	
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.	
Threads damaged .....	A	..	Require repair or replacement.	
Threads stripped (threads missing) .....	A	.....	Require replacement.	
Wire lead conductors exposed .....	B	..	Require repair or replacement.	
Wire lead corroded .....	A	..	Require repair or replacement.	
Wire lead open .....	A	..	Require repair or replacement.	
Wire lead shorted .....	A	..	Require repair or replacement.	

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

BATTERIES

Proper operation of any electrical system or component can be affected by battery condition. The battery(ies) must meet or exceed minimum specification for vehicle as equipped and test to that specific battery's CCA.

Definition of Terms

- \* Battery Performance Testing  
Testing that determines whether or not a battery meets both vehicle OEM and battery manufacturer's specifications.
- \* Cold Cranking Amp (CCA) Rating  
The number of amperes a new, fully charged battery at 0° F (-17.8° C) can deliver for 30 seconds and maintain at least a voltage of 1.2 volts per cell (7.2 volts for a 12-volt battery).
- \* Cranking Amps (CA)  
The number of amperes a new, fully charged battery, typically at 32° F (0° C) can deliver for 30 seconds and maintain at least a voltage of 1.2 volts per cell (7.2 volts for a

12-volt battery).

- \* OEM Cranking Amps  
The minimum CCA required by the original vehicle manufacturer for a specific vehicle.

BATTERY INSPECTION

AA

Condition	Code	Procedure
Battery frozen .....	..	(1) Further inspection required.
Case leaking .....	A	Require replacement.
Casing swollen .....	A	(2) Further inspection required.
Circuit open internally .	A	Require replacement.
Electrolyte contamination .....	A	(2) Further inspection required.
Electrolyte discoloration .....	A	(2) Further inspection required.
Fails to accept and hold charge .....	A	(3) Require replacement.
Fluid level low .....	B	(4) Further inspection required.
Out of performance specification for battery .....	B	(5) Require replacement.
Out of specification for application .....	B	(5) Require replacement.
Post (top or side) burned, affecting performance ..	A	(6) Require repair or replacement.
Post (top or side) burned, not affecting performance .....	2	(6) Suggest repair or replacement.
Post (top or side) corroded, affecting performance .....	A	Require repair.
Post (top or side) corroded, not affecting performance .....	2	Suggest repair.
Post (top or side) loose .....	A	Require replacement.
Post (top or side) melted, affecting performance .....	A	(6) Require repair or replacement.
Post (top or side) melted, not affecting performance .....	2	(6) Suggest repair or replacement.
Specific gravity low ....	B	(7) Further inspection required.
State of charge low .....	A	(7) Further inspection required.
Top dirty .....	2	Suggest cleaning battery.
Top wet .....	A	(8) Require cleaning battery. Further inspection required.
Vent cap loose .....	A	Require repair or replacement of vent cap.
Vent cap missing .....	C	Require replacement of vent

cap.

- (1) - DO NOT attempt to charge a frozen battery. Allow battery to warm thoroughly and then performance-test. If battery fails performance test, require replacement.
- (2) - No service suggested or required unless the battery fails performance test, in which case, require replacement.
- (3) - This phrase refers to a battery that fails to either accept and/or retain a charge using appropriate times listed in the Battery Charging Guide of the BCI Service Manual, battery charger operating manual, or battery manufacturer's specifications.
- (4) - Determine cause of low fluid level. Refill to proper level(s) with water (distilled water preferred). Recharge battery and performance-test.
- (5) - The battery may meet battery manufacturer's specifications but test below the minimum specification defined by the vehicle's OEM for that vehicle.
- (6) - Determine cause and correct prior to repair or replacement of part.
- (7) - Recharge and test to manufacturer's specifications. If battery fails performance test, require replacement.
- (8) - Check fluid level and adjust to manufacturer's specification. Suggest checking charging system for proper operation.

AA

#### BATTERY CABLES, WIRES AND CONNECTORS

##### BATTERY CABLE, WIRE AND CONNECTOR INSPECTION

AA

Condition	Code	Procedure
Application incorrect ...	B ..	Require repair or replacement.
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Connector broken .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	C .....	Require replacement.
Insulation damaged, conductors exposed .....	A .....	(2) Require repair or replacement.
Insulation damaged, conductors not exposed .	1 .....	Suggest replacement.
Open .....	A ..	Require repair or replacement.
Protective shield (conduit) melted .....	2 .....	(1) Suggest repair or replacement.
Protective shield (conduit) missing .....	2 ..	Suggest repair or replacement.
Resistance (voltage drop) out of specification ...	A ..	Require repair or replacement.
Routed incorrectly .....	B .....	Require repair.
Secured incorrectly .....	B .....	Require repair.

Shorted .....	A	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Voltage drop out of specification .....	A	..	Require repair or replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

(2) - Exposed conductor at replacement (aftermarket) terminal end does not require repair or replacement.

AA

BATTERY CONNECTORS

See BATTERY CABLES, WIRES AND CONNECTORS.

BATTERY TRAYS AND HOLD DOWN HARDWARE

BATTERY TRAY AND HOLD DOWN HARDWARE INSPECTION

AA

Condition	Code		Procedure
Battery improperly secured .....	2	.....	Suggest repair.
Bent, affecting performance .....	A	..	Require repair or replacement.
Bent, not affecting performance .....	..	.....	No service suggested or required.
Broken, affecting performance .....	A	..	Require repair or replacement.
Broken, not affecting performance .....	..	.....	No service suggested or required.
Corroded, affecting performance .....	A	..	Require repair or replacement.
Corroded, not affecting performance .....	2	..	Suggest repair or replacement.
Cracked, affecting performance .....	A	..	Require repair or replacement.
Cracked, not affecting performance .....	1	..	Suggest repair or replacement.
Missing .....	C	.....	Require replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Water drain clogged .....	A	.....	Require repair.

AA

BATTERY WIRES

See BATTERY CABLES, WIRES AND CONNECTORS.

BELT-DRIVEN AIR PUMPS

BELT-DRIVEN AIR PUMP INSPECTION

Condition	Code	Procedure
Attaching hardware broken .....	A	... Require repair or replacement of hardware.
Attaching hardware missing .....	C	..... Require replacement of hardware.
Attaching hardware not functioning .....	A	... Require repair or replacement of hardware.
Inoperative .....	A	..... (1) Require replacement.
Leaking .....	A	..... Require replacement.
Missing .....	C	..... Require replacement.
Noisy .....	2	..... Suggest replacement.
Pulley alignment incorrect .....	B	.. Require repair or replacement.
Pulley bent .....	A	..... Require replacement.
Pulley cracked .....	A	..... Require replacement.
Pulley loose .....	A	.. Require repair or replacement.
Pulley missing .....	C	..... Require replacement.
Threads damaged .....	A	.. Require repair or replacement.
Threads stripped (threads missing) .....	A	.. Require repair or replacement.

(1) - Inoperative includes intermittent operation or out of OEM specification.

BELT IDLER ASSEMBLIES (ACCESSORY AND CAM BELTS)

BELT IDLER ASSEMBLY (ACCESSORY AND CAM BELT) INSPECTION

Condition	Code	Procedure
Alignment incorrect .....	B	.. Require repair or replacement.
Attaching hardware broken .....	A	... Require repair or replacement of hardware.
Attaching hardware missing .....	C	..... Require replacement of hardware.
Attaching hardware not functioning .....	A	... Require repair or replacement of hardware.
Bearings worn .....	1	..... Suggest replacement.
Cracked .....	2	..... Suggest replacement.
Missing .....	C	..... Require replacement.
Noisy .....	2	..... Suggest replacement.
Seized .....	A	.. Require repair or replacement.

BELT TENSIONERS (ACCESSORY AND CAM BELTS)

BELT TENSIONER (ACCESSORY AND CAM BELT) INSPECTION

Condition	Code	Procedure
Alignment incorrect .....	B	.. Require repair or replacement.

Attaching hardware broken .....	A ..	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Bearings worn .....	1 .....	Suggest replacement.
Belt tension incorrect ..	B ...	Require adjustment or repair.
Cracked .....	2 .....	Suggest replacement.
Missing .....	C .....	Require replacement.
Noisy .....	2 .....	Suggest replacement.
Pulley damaged, affecting belt life .....	A .....	Require replacement.
Seized .....	A ..	Require repair or replacement.

AA

BOOST CONTROL MECHANISMS

See WASTE GATES AND BOOST CONTROL MECHANISMS.

CAMSHAFT POSITION SENSORS

CAMSHAFT POSITION SENSOR INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware threads damaged .....	A ...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A ...	Require repair or replacement of hardware.
Connector broken .....	A ..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	C .....	Require replacement.
Contaminated .....	A .....	(2) Require repair or replacement.
Inoperative .....	B .....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A ..	Require repair or replacement.
Missing .....	C .....	Require replacement.
Terminal broken .....	A ..	Require repair or replacement.
Terminal burned, affecting performance .....	A .....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A ..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B ..	Require repair or replacement.



CASTING CORE PLUGS AND EXPANSION PLUGS

CASTING CORE PLUG AND EXPANSION PLUG INSPECTION

Condition	Code	Procedure
Leaking .....	A .....	Require replacement.
Material type incorrect .....	2 .....	Suggest replacement.

CHARGE AIR COOLERS "INTERCOOLERS" (CAC)

CHARGE AIR COOLER "INTERCOOLER" (CAC) INSPECTION

Condition	Code	Procedure
Air-to-air intercooler leaking, affecting boost performance .....	A ..	Require repair or replacement.
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Leaking coolant .....	A ..	Require repair or replacement.
Missing .....	C .....	Require replacement.
Restricted, affecting performance .....	A ..	Require repair or replacement.

CHECK VALVES

See ASPIRATOR, CHECK AND DECEL VALVES.

CHOKES

See CARBURETORS AND CHOKES.

CLUTCH PEDAL POSITION SWITCHES

CLUTCH PEDAL POSITION SWITCH INSPECTION

Condition	Code	Procedure
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware threads damaged .....	A ...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A ...	Require repair or replacement of hardware.
Connector broken .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	C .....	Require replacement.
Inoperative .....	B .....	(2) Require repair or

				replacement. Further inspection required.
Missing .....	C	.....		Require replacement.
Resistance out of specification .....	B	..		Require repair or replacement.
Terminal broken .....	A	..		Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1)	Require repair or replacement.
Terminal burned, not affecting performance ..	2	..		Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..		Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..		Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..		Require repair or replacement.
Terminal loose, not affecting performance ..	1	..		Suggest repair or replacement.
Threads damaged .....	A	..		Require repair or replacement.
Threads stripped (threads missing) .....	A	.....		Require replacement.
Wire lead conductors exposed .....	B	..		Require repair or replacement.
Wire lead corroded .....	A	..		Require repair or replacement.
Wire lead open .....	A	..		Require repair or replacement.
Wire lead shorted .....	A	..		Require repair or replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

(2) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

COLD START INJECTORS

See FUEL AND COLD START INJECTORS.

CONNECTORS

See WIRING HARNESSSES AND CONNECTORS.

COOLANT

COOLANT INSPECTION

AA

Condition		Code		Procedure
Acidity (pH) incorrect ..	1	.....		Suggest correction or replacement.
Contaminated .....	B	.....	(1)	Require replacement or recycling. Further inspection required.
Level low .....	B	...	(2)	Require filling to proper level.
Maintenance intervals ...	3	.....	(3)	Suggest replacement.
Mixture incorrect .....	B	.....		Require correction or replacement.
Type incorrect .....	B	.....		Require replacement.

(1) - Determine source of contamination and require correction prior to coolant replacement.

(2) - Determine source of incorrect level and suggest repair.

(3) - The system should be drained and/or flushed and refilled with correct coolant according to OEM recommended service interval and procedures.

AA

COOLANT RECOVERY TANKS

COOLANT RECOVERY TANK INSPECTION

AA

Condition	Code	Procedure
Attaching hardware broken .....	A ..	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ..	Require repair or replacement of hardware.
Leaking .....	A .	Require repair or replacement.
Missing (if original equipment) .....	C .....	Require replacement.

AA

COOLING FAN MOTOR MODULES

See COOLING FAN MOTOR RELAYS AND MODULES.

COOLING FAN MOTOR RELAYS AND MODULES

COOLING FAN MOTOR RELAY AND MODULE INSPECTION

AA

Condition	Code	Procedure
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Connector broken .....	A ..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	C .....	Require replacement.
Housing cracked .....	2 ..	Suggest repair or replacement.
Malfunctioning .....	A .....	(2) Require repair or replacement.
Missing .....	C .....	Require replacement.
Terminal broken .....	A ..	Require repair or replacement.
Terminal burned, affecting performance .....	A .....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A ..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2 ..	Suggest repair or replacement.

Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.  
(2) - Includes inoperative, intermittent operation, failure to perform all functions, or out of OEM specification.

AA

COOLING FAN MOTOR RESISTORS

COOLING FAN MOTOR RESISTOR INSPECTION

AA

Condition	Code		Procedure
Application incorrect ...	B	.....	Require replacement.
Attaching hardware broken .....	A	...	Require repair or replacement of hardware.
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware not functioning .....	A	...	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Missing .....	C	.....	Require replacement.
Open .....	A	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.
Shorted .....	A	.....	Require replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ...	2	.	Suggest repair or replacement.
Terminal corroded, affecting performance ...	A	.	Require repair or replacement.
Terminal corroded, not affecting performance ...	2	.	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	.	Require repair or replacement.
Terminal loose, not affecting performance ...	1	.	Suggest repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.

AA

COOLING FAN MOTOR SENSORS AND SWITCHES

COOLING FAN MOTOR SENSOR AND SWITCH INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C	Require replacement of hardware.
Attaching hardware threads damaged .....	A	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	Require repair or replacement of hardware.
Connector broken .....	A	Require repair or replacement.
Connector melted .....	A	(1) Require repair or replacement.
Connector missing .....	C	Require replacement.
Contaminated .....	A	(2) Require repair or replacement.
Inoperative .....	B	(3) Require repair or replacement. Further inspection required.
Leaking .....	A	Require repair or replacement.
Missing .....	C	Require replacement.
Resistance out of specification .....	B	Require repair or replacement.
Terminal broken .....	A	Require repair or replacement.
Terminal burned, affecting performance .....	A	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	Require repair or replacement.
Terminal loose, not affecting performance ..	1	Suggest repair or replacement.
Threads damaged .....	A	Require repair or replacement.
Threads stripped (threads missing) .....	A	Require replacement.
Wire lead conductors exposed .....	B	Require repair or replacement.
Wire lead corroded .....	A	Require repair or replacement.
Wire lead open .....	A	Require repair or replacement.
Wire lead shorted .....	A	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

COOLING FAN MOTOR SWITCHES

See COOLING FAN MOTOR SENSORS AND SWITCHES.

COOLING FAN MOTORS

COOLING FAN MOTOR INSPECTION

AA

Condition	Code	Procedure
Attaching hardware broken .....	A ..	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ..	Require repair or replacement of hardware.
Connector broken .....	A .	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A .	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	C .....	Require replacement.
Hydraulic fan motor leaking .....	A .	Require repair or replacement.
Inoperative .....	A .....	(2) Require replacement.
Missing .....	C .....	Require replacement.
Noisy .....	2 .....	Suggest replacement.
Rotation incorrect for application .....	B .	Require repair or replacement.
Terminal broken .....	A .	Require repair or replacement.
Terminal burned, affecting performance .....	A .....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2 .	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A .	Require repair or replacement.
Terminal corroded, not affecting performance ..	2 .	Suggest repair or replacement.
Terminal loose, affecting performance .....	B .	Require repair or replacement.
Terminal loose, not affecting performance ..	1 .	Suggest repair or replacement.
Vibration .....	1 .....	Suggest replacement.
Wire lead conductors exposed .....	B .	Require repair or replacement.
Wire lead corroded .....	A .	Require repair or replacement.
Wire lead open .....	A .	Require repair or replacement.
Wire lead shorted .....	A .	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Check fan motor/controls. Inoperative includes intermittent operation or out of OEM specification.

AA

CRANKSHAFT POSITION SENSORS

CRANKSHAFT POSITION SENSOR INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C .....	Require replacement of hardware.

Attaching hardware threads damaged .....	A	...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	...	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Contaminated .....	A	..	Require repair or replacement.
Inoperative .....	B	..	Require repair or replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

(2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.

(3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

DECEL VALVES

See ASPIRATOR, CHECK AND DECEL VALVES.

DEFLECTORS

See SHROUDS, BAFFLES AND DEFLECTORS.

DIP STICKS AND TUBES

DIP STICK AND TUBE INSPECTION

Condition	Code	Procedure
Application incorrect ...	B	Require replacement.
Bent .....	2	Suggest repair or replacement.
Broken, affecting performance (for example, fuel mixture) .....	A	Require repair or replacement.
Broken, not affecting performance .....	2	Suggest repair or replacement.
Leaking, affecting performance (for example, fuel mixture) .....	A	Require repair or replacement.
Leaking, not affecting performance .....	2	Suggest repair or replacement.
Missing	C	Require replacement.

DIP STICK TUBES

See DIP STICKS AND TUBES.

DISTRIBUTOR ADVANCES AND RETARDERS (MECHANICAL AND VACUUM)

DISTRIBUTOR ADVANCE AND RETARDER (MECHANICAL AND VACUUM) INSPECTION

Condition	Code	Procedure
Attaching hardware broken .....	A	Require repair or replacement of hardware.
Attaching hardware missing .....	C	Require replacement of hardware.
Attaching hardware not functioning .....	A	Require repair or replacement of hardware.
Binding .....	A	Require repair or replacement.
Inoperative .....	A	(1) Require repair or replacement.
Leaking .....	A	Require replacement.
Out of specification ....	B	Require repair or replacement.

(1) - Inoperative includes intermittent operation.

DISTRIBUTOR BOOTS AND SHIELDS

DISTRIBUTOR BOOT AND SHIELD INSPECTION

Condition	Code	Procedure
Attaching hardware broken .....	A	Require repair or replacement of hardware.
Attaching hardware missing .....	C	Require replacement of hardware.
Attaching hardware not functioning .....	A	Require repair or replacement of hardware.
Deteriorated .....	A	Require replacement.
Leaking .....	A	Require replacement.
Missing .....	A	Require replacement.

Torn ..... A ..... Require replacement.  
 AA

DISTRIBUTOR CAPS

DISTRIBUTOR CAP INSPECTION

AAA

Condition	Code	Procedure
Application incorrect ...	B	Require replacement.
Arcing .....	A	Require replacement.
Attaching hardware broken .....	A	Require repair or replacement of hardware.
Attaching hardware missing .....	C	Require replacement of hardware.
Attaching hardware not functioning .....	A	Require repair or replacement of hardware.
Burned .....	A	Require replacement.
Carbon button missing ...	A	Require replacement.
Carbon button worn, affecting performance ..	A	Require replacement.
Carbon button worn, not affecting performance ..	1	Suggest replacement.
Carbon-tracked .....	A	Require replacement.
Cracked .....	A	Require replacement.
Loose .....	2	Suggest repair or replacement.
Terminal broken .....	A	Require repair or replacement.
Terminal burned, affecting performance .....	A	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	Suggest repair or replacement.
Terminal eroded, affecting performance .....	A	Require repair or replacement.
Terminal eroded, not affecting performance ..	..	No service suggested or required.
Terminal loose, affecting performance .....	B	Require repair or replacement.
Terminal loose, not affecting performance ..	1	Suggest repair or replacement.

(1) - Determine cause and correct prior to repair or  
 replacement of part.

AAA

DISTRIBUTOR RETARDERS (MECHANICAL AND VACUUM)

See

DISTRIBUTOR ADVANCES AND RETARDERS (MECHANICAL AND VACUUM).

DISTRIBUTOR ROTORS

DISTRIBUTOR ROTOR INSPECTION

AAA

Condition	Code	Procedure
-----------	------	-----------

Application incorrect ...	B	.....	Require replacement.
Attaching hardware broken .....	A	...	Require repair or replacement of hardware.
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware not functioning .....	A	...	Require repair or replacement of hardware.
Carbon-tracked .....	A	.....	Require replacement.
Contact burned .....	A	.....	Require replacement.
Corroded .....	1	.....	Suggest replacement.
Eroded .....	1	.....	Suggest replacement.
Loose .....	A	..	Require repair or replacement.
Out of specification ....	B	.....	Require replacement.
AA			

DISTRIBUTOR SHIELDS

See DISTRIBUTOR BOOTS AND SHIELDS.

DISTRIBUTORS

DISTRIBUTOR INSPECTION

AA

Condition	Code		Procedure
Attaching hardware broken .....	A	...	Require repair or replacement of hardware.
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware not functioning .....	A	...	Require repair or replacement of hardware.
Bushings worn, affecting performance .....	A	..	Require repair or replacement.
Bushings worn, not affecting performance ..	1	..	Suggest repair or replacement.
Cam lobes worn, affecting performance .....	A	..	Require repair or replacement.
Cam lobes worn, not affecting performance ..	1	..	Suggest repair or replacement.
Gear broken .....	A	..	Require repair or replacement.
Gear worn, affecting performance .....	A	.....	Require replacement.
Gear worn, not affecting performance .....	..	.....	No service suggested or required.
Integrated pickup triggering device loose .....	A	..	Require repair or replacement.
Integrated pickup triggering device magnetism incorrect ....	A	..	Require repair or replacement.
Leaking oil internally ..	A	..	Require repair or replacement.
Noisy .....	2	..	Suggest repair or replacement.
Pickup triggering device (reluctor) broken .....	A	..	Require repair or replacement.
Pickup triggering device (reluctor) loose .....	A	..	Require repair or replacement.
Pickup triggering device			

(reluctor) weak	.....	A	..	Require repair or replacement.
Reluctor (pickup triggering device)				
broken	.....	A	..	Require repair or replacement.
Reluctor (pickup triggering device)				
loose	.....	A	..	Require repair or replacement.
Reluctor (pickup triggering device)				
weak	.....	A	..	Require repair or replacement.
Shaft bent	.....	A	.....	Require replacement.
Thrust washer broken	....	A	..	Require repair or replacement.
Thrust washer missing	...	C	..	Require repair or replacement.
Thrust washer worn, affecting performance	..	A	..	Require repair or replacement.
Thrust washer worn, not affecting performance	..	1	..	Suggest repair or replacement.

AA

EARLY FUEL EVAPORATION VALVES (HEAT RISER ASSEMBLIES)

EARLY FUEL EVAPORATION VALVE (HEAT RISER ASSEMBLY) INSPECTION

AA

Condition		Code		Procedure
Broken	.....	A	.	Require replacement of affected parts.
Diaphragm inoperative	...	A	.....	(1) Further inspection required.
Leaking	.....	A	..	Require repair or replacement.
Noisy	.....	2	..	Suggest repair or replacement.
Seized	.....	A	.	Require replacement of affected parts.
Spring broken	.....	B	.....	Require replacement of spring(s).
Spring inoperative	.....	A	.....	(2) Require replacement of spring(s).

(1) - Inoperative includes intermittent operation or out of OEM specification. If the inoperative diaphragm is separate from the heat riser, then require replacement of the inoperative diaphragm. If the inoperative diaphragm is part of the heat riser, then replace the heat riser.

(2) - Inoperative includes intermittent operation or out of OEM specification.

AA

EGR COOLERS

See EGR PLATES AND COOLERS.

EGR EXHAUST MANIFOLD PASSAGES

See EGR INTAKE AND EXHAUST MANIFOLD PASSAGES.

EGR INTAKE AND EXHAUST MANIFOLD PASSAGES

EGR INTAKE AND EXHAUST MANIFOLD PASSAGE INSPECTION

AA

Condition		Code		Procedure
Leaking	.....	A	..	Require repair or replacement.
Restricted, affecting				

performance ..... A .. Require repair or replacement.  
 AA

EGR PLATES AND COOLERS

EGR PLATE AND COOLER INSPECTION  
 AA

Condition	Code	Procedure
Leaking .....	A ..	Require repair or replacement.
Missing .....	C .....	Require replacement.
Restricted, affecting performance .....	A ..	Require repair or replacement.

AAA

ELECTRONIC SPARK CONTROL MODULES

ELECTRONIC SPARK CONTROL MODULE INSPECTION  
 AA

Condition	Code	Procedure
Application incorrect ...	B .....	Require replacement.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware threads damaged .....	A ...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A ...	Require repair or replacement of hardware.
Connector broken .....	A ..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	A .....	Require repair.
Contaminated .....	A .....	(2) Require repair or replacement.
Leaking .....	A ..	Require repair or replacement.
Malfunctioning .....	A .....	(3) Require repair or replacement.
Missing .....	C .....	Require replacement.
Terminal broken .....	A ..	Require repair or replacement.
Terminal burned, affecting performance .....	A .....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A ..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B ..	Require repair or replacement.
Terminal loose, not affecting performance ..	1 ..	Suggest repair or replacement.
Threads damaged .....	A ..	Require repair or replacement.
Threads stripped (threads missing) .....	A .....	Require replacement.
Wire lead conductors exposed .....	B ..	Require repair or replacement.
Wire lead corroded .....	A ..	Require repair or replacement.

Wire lead open ..... A .. Require repair or replacement.  
 Wire lead shorted ..... A .. Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement of source.
- (3) - Includes inoperative, intermittent operation, failure to perform all functions, or out of OEM specification.

AA

ELECTRONIC TRANSMISSION CONTROL DEVICES

ELECTRONIC TRANSMISSION CONTROL DEVICE INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware threads damaged .....	A ...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A ...	Require repair or replacement of hardware.
Connector broken .....	A ..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	C .....	Require replacement.
Contaminated .....	A .....	(2) Require repair or replacement.
Leaking .....	A ..	Require repair or replacement.
Malfunctioning .....	A .....	(3) Require repair or replacement.
Missing .....	C .....	Require replacement.
Resistance out of specification .....	B ..	Require repair or replacement.
Restricted, affecting performance .....	A ..	Require repair or replacement.
Terminal broken .....	A ..	Require repair or replacement.
Terminal burned, affecting performance .....	A .....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A ..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B ..	Require repair or replacement.
Terminal loose, not affecting performance ..	1 ..	Suggest repair or replacement.
Threads damaged .....	A ..	Require repair or replacement.
Threads stripped (threads missing) .....	A .....	Require replacement.
Wire lead conductors exposed .....	B ..	Require repair or replacement.
Wire lead corroded .....	A ..	Require repair or replacement.

Wire lead open ..... A .. Require repair or replacement.  
 Wire lead shorted ..... A .. Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Includes inoperative, intermittent operation, failure to perform all functions, or out of OEM specification.

AA

ELECTRONIC TRANSMISSION FEEDBACK DEVICES

ELECTRONIC TRANSMISSION FEEDBACK DEVICE INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware threads damaged .....	A ...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A ..	Require repair or replacement of hardware.
Connector broken .....	A ..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	C .....	Require replacement.
Contaminated .....	A .....	(2) Require repair or replacement.
Inoperative .....	B .....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A ..	Require repair or replacement.
Missing .....	C .....	Require replacement.
Resistance out of specification .....	B ..	Require repair or replacement.
Restricted, affecting performance .....	A ..	Require repair or replacement.
Terminal broken .....	A ..	Require repair or replacement.
Terminal burned, affecting performance .....	A .....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A ..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B ..	Require repair or replacement.
Terminal loose, not affecting performance ..	1 ..	Suggest repair or replacement.
Threads damaged .....	A ..	Require repair or replacement.
Threads stripped (threads missing) .....	A .....	Require replacement.
Wire lead conductors exposed .....	B ..	Require repair or replacement.

Wire lead corroded ..... A .. Require repair or replacement.  
 Wire lead open ..... A .. Require repair or replacement.  
 Wire lead shorted ..... A .. Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

ENGINE COOLANT TEMPERATURE SENSORS

ENGINE COOLANT TEMPERATURE SENSOR INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware threads damaged .....	A ...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A ...	Require repair or replacement of hardware.
Connector broken .....	A ..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	C .....	Require replacement.
Contaminated .....	A .....	(2) Require repair or replacement.
Inoperative .....	B .....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A ..	Require repair or replacement.
Missing .....	C .....	Require replacement.
Resistance out of specification .....	B ..	Require repair or replacement.
Restricted, affecting performance .....	A ..	Require repair or replacement.
Terminal broken .....	A ..	Require repair or replacement.
Terminal burned, affecting performance .....	A .....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A ..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B ..	Require repair or replacement.
Terminal loose, not affecting performance ..	1 ..	Suggest repair or replacement.
Threads damaged .....	A ..	Require repair or replacement.
Threads stripped (threads missing) .....	A .....	Require replacement.

Wire lead conductors

exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

ENGINE COOLING SYSTEMS

NOTE: Overheating, poor engine performance, and insufficient cabin heat can be affected by, but are not limited to, all of the components in the engine cooling system.

ENGINE COVERS (OIL PAN, VALVE COVER, TIMING COVER)

ENGINE COVER (OIL PAN, VALVE COVER, TIMING COVER) INSPECTION

AA

Condition	Code	Procedure
Attaching hardware incorrect .....	B	..... Require replacement.
Attaching hardware loose .....	A	.. Require repair or replacement.
Attaching hardware missing .....	C	..... Require replacement.
Baffle loose .....	2	.. Suggest repair or replacement.
Baffle missing .....	C	..... Require replacement.
Bent, affecting performance .....	A	.. Require repair or replacement.
Bent, not affecting performance .....	..	..... No service suggested or required.
Cracked (not leaking) ...	2	.. Suggest repair or replacement.
Leaking externally .....	A	.. Require repair or replacement.
Leaking internally, causing fluid contamination .....	A	.. Require repair or replacement.
Missing .....	C	..... Require replacement.
Restricted passage .....	A	.. Require repair or replacement.
Threads damaged .....	A	.. Require repair or replacement.

AA

ENGINE OIL

ENGINE OIL INSPECTION

AA

Condition	Code	Procedure
Contaminated .....	A	.. (1) Require replacement of oil and filter.
Level high .....	B	... Determine source of incorrect level and require repair.
Level low .....	B	... Determine source of incorrect level and require repair.
Maintenance intervals ...	3	... Suggest replacement to comply





Condition	Code	Procedure
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Maintenance interval ....	3 ...	Suggest replacement to comply with OEM recommended service interval.
Missing .....	C .....	Require replacement.
Restricted, affecting performance .....	A .....	Require replacement.
Restricted, not affecting performance .....	1 .....	Suggest replacement.
Water-contaminated .....	A .....	Require replacement.

EVAPORATIVE EMISSION (EVAP) CANISTER PURGE DEVICES

EVAPORATIVE EMISSION (EVAP) CANISTER PURGE DEVICE INSPECTION

Condition	Code	Procedure
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware threads damaged .....	A ...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A ...	Require repair or replacement of hardware.
Connector broken .....	A ..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	C .....	Require replacement.
Contaminated .....	A .....	(2) Require repair or replacement.
Inoperative .....	B .....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A ..	Require repair or replacement.
Missing .....	C .....	Require replacement.
Resistance out of specification .....	B ..	Require repair or replacement.
Restricted, affecting performance .....	A ..	Require repair or replacement.
Terminal broken .....	A ..	Require repair or replacement.
Terminal burned, affecting performance .....	A .....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A ..	Require repair or replacement.
Terminal corroded, not		

affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

EVAPORATIVE EMISSION (EVAP) CANISTERS

EVAPORATIVE EMISSION (EVAP) CANISTER INSPECTION

AA

Condition	Code	Procedure
Inoperative .....	A	..... (1) Require repair or replacement.
Leaking .....	A	..... Require replacement.
Missing .....	C	..... Require replacement.
Saturated .....	A	..... Require replacement.

- (1) - Inoperative includes intermittent operation or out of OEM specification.

AA

EVAPORATIVE EMISSION (EVAP) FEEDBACK DEVICES

EVAPORATIVE EMISSION (EVAP) FEEDBACK DEVICE INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C	..... Require replacement of hardware.
Attaching hardware threads damaged .....	A	... Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	... Require repair or replacement of hardware.
Connector broken .....	A	.. Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	.. Require repair or replacement.
Connector melted .....	A	..... (1) Require repair or replacement.
Connector missing .....	C	..... Require replacement.
Contaminated .....	A	..... (2) Require repair or replacement.

Inoperative .....	B	.....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.
Restricted, affecting performance .....	A	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

EXHAUST GAS RECIRCULATION DEVICES

EXHAUST GAS RECIRCULATION DEVICE INSPECTION

AA

Condition	Code		Procedure
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware threads damaged .....	A	...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	...	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.

Contaminated .....	A	.....	(2) Require repair or replacement.
Inoperative .....	B	.....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.
Restricted, affecting performance .....	A	..	Require repair or replacement.
Restricted, not affecting performance .....	1	..	Suggest repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

EXHAUST GAS RECIRCULATION FEEDBACK DEVICES

EXHAUST GAS RECIRCULATION FEEDBACK DEVICE INSPECTION

AA

Condition	Code		Procedure
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware threads damaged .....	A	...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	...	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack			

type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Contaminated .....	A	.....	(2) Require repair or replacement.
Inoperative .....	B	.....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.
Restricted, affecting performance .....	A	..	Require repair or replacement.
Restricted, not affecting performance .....	1	..	Suggest repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

EXPANSION PLUGS

See CASTING CORE PLUGS AND EXPANSION PLUGS.

FAN CONTROL SENSORS

FAN CONTROL SENSOR INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C	..... Require replacement of hardware.
Attaching hardware		

threads damaged .....	A	...	Require repair or replacement of hardware.
Attaching hardware			
threads stripped (threads missing) .....	A	...	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Contaminated .....	A	.....	(2) Require repair or replacement.
Inoperative .....	B	.....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.
Restricted, affecting performance .....	A	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors			
exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

FUEL

FUEL INSPECTION

AA

Condition	Code	Procedure
Contaminated .....	B	..... (1) Require repair or replacement.

Fuel incorrect ..... B ..... (2) Require flushing of system.

(1) - Determine of source of contamination. Require repair or replacement.

(2) - If a fuel other than specification fuel is present in the system, the required service is to flush and fill with the correct fuel.

AA

### FUEL ACCUMULATORS AND DAMPERS

#### FUEL ACCUMULATOR AND DAMPER INSPECTION

AA

Condition	Code	Procedure
Attaching hardware broken .....	A	... Require repair or replacement of hardware.
Attaching hardware missing .....	C	..... Require replacement of hardware.
Attaching hardware not functioning .....	A	... Require repair or replacement of hardware.
Connections leaking .....	A	.. Require repair or replacement.
Inoperative .....	A	..... (1) Require replacement.
Leaking .....	A	..... Require replacement.

(1) - Inoperative includes intermittent operation or out of OEM specification.

AA

### FUEL AND COLD START INJECTORS

NOTE: You are not required to replace injectors in sets. However, you may suggest replacement of all injectors for preventive maintenance.

#### FUEL AND COLD START INJECTOR INSPECTION

AA

Condition	Code	Procedure
Application incorrect ...	B	..... Require replacement.
Attaching hardware broken .....	A	... Require repair or replacement of hardware.
Attaching hardware missing .....	C	..... Require replacement of hardware.
Attaching hardware not functioning .....	A	... Require repair or replacement of hardware.
Connector broken .....	A	.. Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	.. Require repair or replacement.
Connector melted .....	A	..... (1) Require repair or replacement.
Connector missing .....	C	..... Require replacement.
Flow restricted .....	B	.. Require repair or replacement.
Inoperative .....	B	..... (2) Require repair or replacement. Further inspection required.
Leaking .....	A	.. Require repair or replacement.

Resistance out of specification .....	B	.....	Require replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

(2) - Inoperative includes intermittent operation, out of OEM specification. Some components may be serviceable.

AA

FUEL DAMPERS

See FUEL ACCUMULATORS AND DAMPERS.

FUEL DELIVERY CHECK VALVES

FUEL DELIVERY CHECK VALVE INSPECTION

AA

Condition	Code	Procedure
Inoperative .....	A	..... (1) Require replacement.
Leaking externally .....	A	.. Require repair or replacement.
Missing .....	C	..... Require replacement.
Pressure leaking (bleeds down) .....	A	.. Require repair or replacement.

(1) - Inoperative includes intermittent operation or out of OEM specification.

AA

FUEL DISTRIBUTORS (BOSCH CIS)

FUEL DISTRIBUTOR (BOSCH CIS) INSPECTION

AA

Condition	Code	Procedure
Inoperative .....	A	..... (1) Require repair or replacement. Further inspection required.
Leaking .....	A	.. Require repair or replacement.
Out of specification ....	B	.. Require repair or replacement.
Restricted, affecting performance .....	A	..... (2) Require repair or replacement. Further inspection required.

(1) - Inoperative includes intermittent operation.

(2) - Some components may be serviceable; check for accepted

cleaning procedure.

AA

FUEL FILLER NECKS AND RESTRICTORS

FUEL FILLER NECK AND RESTRICTOR INSPECTION

AA

Condition	Code	Procedure
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Leaking .....	A ..	Require repair or replacement.
Missing .....	C .....	Require replacement.
Restricted .....	2 ..	Suggest repair or replacement.

AA

FUEL FILTERS

FUEL FILTER INSPECTION

AA

Condition	Code	Procedure
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Leaking .....	A ..	Require repair or replacement.
Maintenance interval ....	3 ...	Suggest replacement to comply with OEM recommended service interval.
Missing .....	C .....	Require replacement.
Restricted, affecting performance .....	A .....	Require replacement.
Restricted, not affecting performance .....	1 .....	Suggest replacement.
Water-contaminated .....	2 .....	Suggest replacement.

AA

FUEL INJECTORS

FUEL INJECTOR INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware threads damaged .....	A ..	Require repair or replacement of hardware.
Attaching hardware threads stripped		

(threads missing) .....	A	..	Require repair or replacement of hardware.
Connector broken .....	A	.	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	.	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Contaminated .....	A	.....	(2) Require repair or replacement.
Inoperative .....	B	.....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A	.	Require repair or replacement.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	.	Require repair or replacement.
Restricted, affecting performance .....	A	.	Require repair or replacement.
Restricted, not affecting performance .....	2	.	Suggest repair or replacement.
Terminal broken .....	A	.	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	.	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	.	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	.	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	.	Require repair or replacement.
Terminal loose, not affecting performance ..	1	.	Suggest repair or replacement.
Threads damaged .....	A	.	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	.	Require repair or replacement.
Wire lead corroded .....	A	.	Require repair or replacement.
Wire lead open .....	A	.	Require repair or replacement.
Wire lead shorted .....	A	.	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

FUEL LEVEL SENDERS

FUEL LEVEL SENDER INSPECTION

AA

Condition	Code	Procedure
-----------	------	-----------

Attaching hardware broken .....	A	...	Require repair or replacement of hardware.
---------------------------------	---	-----	--

Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware not functioning .....	A	...	Require repair or replacement of hardware.
Inoperative .....	A	.....	(1) Require repair or replacement.
Leaking .....	A	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(2) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

(1) - Inoperative includes intermittent operation or out of OEM specification.

(2) - Determine cause and correct prior to repair or replacement of part.

AA

FUEL PRESSURE REGULATORS

FUEL PRESSURE REGULATOR INSPECTION

AA

Condition	Code		Procedure
Contaminated .....	2	.....	(1) Suggest repair or replacement. Further inspection required.
Inoperative .....	B	.....	(2) Require repair or replacement.
Leaking (internally or externally) .....	A	..	Require repair or replacement.
Pressure out of specification .....	B	..	Require repair or replacement.
Vapor bypass restricted .	A	..	Require repair or replacement.

(1) - Some components may be serviceable; check for accepted cleaning procedure. Determine source of contamination. Require repair or replacement.

(2) - Inoperative includes intermittent operation or out of OEM specification.

AA

FUEL PUMPS (IN-TANK AND EXTERNAL, ELECTRICAL OR MECHANICAL)

FUEL PUMP (IN-TANK AND EXTERNAL, ELECTRICAL OR MECHANICAL) INSPECTION

AA

Condition	Code		Procedure
-----------	------	--	-----------

Attaching hardware broken .....	A	...	Require repair or replacement of hardware.
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware not functioning .....	A	...	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Contaminated .....	A	.....	(2) Require replacement.
Inoperative .....	A	.....	(3) Require repair or replacement.
Leaking externally (includes pulsator) ....	A	..	Require repair or replacement.
Leaking internally (includes pulsator) ....	A	..	Require repair or replacement.
Noisy .....	2	..	Suggest repair or replacement.
Out of specification ....	B	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

(2) - Determine source of contamination. Require repair or replacement.

(3) - Inoperative includes intermittent operation.

AA

FUEL RAILS

FUEL RAIL INSPECTION

AA

Condition	Code	Procedure
-----------	------	-----------

Attaching hardware broken .....	A	...	Require repair or replacement of hardware.
------------------------------------	---	-----	---



GASKETS

GASKET INSPECTION

Condition	Code	Procedure
Leaking .....	A .....	(1) Require repair or replacement.

(1) - Require inspection of mating and sealing surface and repair or replace as necessary.

GROMMETS (VALVE COVER)

GROMMET (VALVE COVER) INSPECTION

Condition	Code	Procedure
Leaking .....	2 .....	(1) Suggest repair or replacement.

(1) - Require inspection of mating and sealing surface and repair or replace as necessary.

HARMONIC DAMPERS

HARMONIC DAMPER INSPECTION

Condition	Code	Procedure
Application incorrect ...	B .....	Require replacement.
Attaching hardware broken .....	A ..	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ..	Require repair or replacement of hardware.
Cracked .....	A .....	Require replacement.
Dented (fluid type only) .....	A .....	Require replacement.
Keyway distorted .....	A .	Require repair or replacement.
Leaking (Fluid damper only) .....	A .....	Require replacement.
Loose .....	A .....	Require replacement.
Noisy .....	A .....	Require replacement.
Outer ring slipped out of position .....	A .....	Require replacement.
Positioned incorrectly ..	A .	Require repair or replacement.
Rubber damping material deteriorated .....	1 .....	Suggest replacement.
Seal surface worn, causing a leak .....	A .	Require repair or replacement.
Threads damaged .....	A .	Require repair or replacement.
Threads stripped (threads missing) .....	A .....	Require replacement.

HEATER CONTROL VALVES

HEATER CONTROL VALVE INSPECTION

AA

Condition	Code	Procedure
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Bypassed .....	A .....	Require replacement.
Coolant leak .....	A ..	Require repair or replacement.
Malfunctioning .....	A .....	(1) Require repair or replacement.
Missing .....	C .....	Require replacement.
Restricted .....	A ..	Require repair or replacement.
Vacuum leak .....	A ..	Require repair or replacement.

(1) - Includes inoperative, intermittent operation, or failure to perform all functions.

AA

HEATER CORES

HEATER CORE INSPECTION

AA

Condition	Code	Procedure
Air flow restriction ....	A ..	Require repair or replacement.
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Bypassed .....	A ..	Require repair or replacement.
Connection leaking .....	A ..	Require repair or replacement.
Corroded .....	1 ..	Suggest repair or replacement.
Fins damaged, affecting performance .....	A ..	Require repair or replacement.
Fins damaged, not affecting performance ..	2 ..	Suggest repair or replacement.
Internal restrictions, affecting performance ..	A ..	Require repair or replacement.
Leaking .....	A ..	Require repair or replacement.
Missing .....	C .....	Require replacement.

AA

HOSE AND TUBE COUPLERS, CONNECTORS AND CLAMPS

NOTE: When replacing fuel lines and hoses, replace with product that meets or exceeds OEM design specifications.

HOSE AND TUBE COUPLER, CONNECTOR AND CLAMP INSPECTION

AA

Condition	Code	Procedure
-----------	------	-----------

Application incorrect ...	B	.....	Require replacement.
Connected incorrectly ...	A	.....	Require repair.
Corroded, not reusable ..	1	.....	Suggest replacement.
Cracked .....	A	.....	Require replacement.
Insufficient clamping force, allowing hose to leak .....	A	..	Require repair or replacement.
Leaking .....	A	..	Require repair or replacement.
Missing .....	C	.....	Require replacement.
Safety clip missing (not leaking) .....	C	...	Require replacement of safety clip.
Stripped .....	A	.....	Require replacement.

AA

HOSE CLAMPS

See HOSE AND TUBE COUPLERS, CONNECTORS AND CLAMPS.

HOSE CONNECTORS

See HOSE AND TUBE COUPLERS, CONNECTORS AND CLAMPS.

HOSE COUPLERS

See HOSE AND TUBE COUPLERS, CONNECTORS AND CLAMPS.

HOSES AND TUBES (FUEL LINES, RADIATOR, VACUUM, BY PASS,  
HEATER, RECOVERY TANK AND OIL COOLERS)

HOSE AND TUBE (FUEL LINE, RADIATOR, VACUUM, BY PASS, HEATER,  
RECOVERY TANK AND OIL COOLER) INSPECTION  
AA

Condition	Code		Procedure
-----------	------	--	-----------

Application incorrect ...	B	.....	Require replacement.
Connected incorrectly ...	A	.....	Require repair.
Corroded, not reusable ..	1	.....	Suggest replacement.
Cracked .....	A	.....	Require replacement.
Dry-rotted .....	1	..	Suggest repair or replacement.
Hard .....	1	..	Suggest repair or replacement.
Inner fabric (webbing) damaged .....	A	.....	Require replacement.
Insufficient clamping force, allowing hose to leak .....	A	..	Require repair or replacement.
Leaking .....	A	..	Require repair or replacement.
Maintenance intervals ...	3	.....	Suggest replacement.
Melted .....	1	..	Suggest repair or replacement.
Missing .....	C	.....	Require replacement.
Outer covering damaged ..	1	.....	Suggest replacement.
Outer covering damaged to the extent that the inner fabric is visible .....	A	.....	Require replacement.
Protective sleeves damaged .....	2	.	Suggest replacement of sleeves.
Protective sleeves missing .....	2	.	Suggest replacement of sleeves.
Restricted, affecting performance .....	A	..	Require repair or replacement.
Restricted, not affecting performance .....	2	..	Suggest repair or replacement.
Routed incorrectly .....	2	..	Suggest repair or replacement.
Safety clip missing .....	C	.....	Require replacement.

Spongy .....	1	..	Suggest repair or replacement.
Stripped .....	A	.....	Require replacement.
Swollen .....	B	.....	Require replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Type incorrect .....	1	..	Suggest repair or replacement.

AA

HOUSINGS

See THERMOSTATS AND HOUSINGS.

IDLE AIR CONTROLS

IDLE AIR CONTROL INSPECTION

AA

Condition	Code		Procedure
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware threads damaged .....	A	...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	...	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Contaminated .....	A	.....	(2) Require repair or replacement.
Inoperative .....	B	.....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.
Restricted, affecting performance .....	A	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors			

exposed ..... B .. Require repair or replacement.  
 Wire lead corroded ..... A .. Require repair or replacement.  
 Wire lead open ..... A .. Require repair or replacement.  
 Wire lead shorted ..... A .. Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

IDLE SPEED CONTROL ACTUATORS

IDLE SPEED CONTROL ACTUATOR INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware threads damaged .....	A ...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A ...	Require repair or replacement of hardware.
Connector broken .....	A ..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	C .....	Require replacement.
Contaminated .....	A .....	(2) Require repair or replacement.
Inoperative .....	B .....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A ..	Require repair or replacement.
Missing .....	C .....	Require replacement.
Resistance out of specification .....	B ..	Require repair or replacement.
Terminal broken .....	A ..	Require repair or replacement.
Terminal burned, affecting performance .....	A .....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A ..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B ..	Require repair or replacement.
Terminal loose, not affecting performance ..	1 ..	Suggest repair or replacement.
Threads damaged .....	A ..	Require repair or replacement.
Threads stripped (threads missing) .....	A .....	Require replacement.
Wire lead conductors		

exposed ..... B .. Require repair or replacement.  
 Wire lead corroded ..... A .. Require repair or replacement.  
 Wire lead open ..... A .. Require repair or replacement.  
 Wire lead shorted ..... A .. Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

IGNITION BOOTS

See

IGNITION WIRES, BOOTS, COIL TOWERS AND TERMINALS (SECONDARY).

IGNITION COIL TOWERS

See

IGNITION WIRES, BOOTS, COIL TOWERS AND TERMINALS (SECONDARY).

IGNITION COILS

IGNITION COIL INSPECTION

AA

Condition	Code	Procedure
Arcing .....	A .....	Require replacement.
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Connector broken .....	A ..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	C .....	Require replacement.
Corroded, affecting performance .....	A .....	Require replacement.
Corroded, not affecting performance .....	2 .....	Suggest replacement.
Distorted .....	.. ....	(2) No service suggested or required.
Inoperative .....	A .....	(3) Require replacement.
Oil leaking .....	A .....	Require replacement.
Out of specification ....	B .....	Require replacement.
Terminal broken .....	A ..	Require repair or replacement.
Terminal burned, affecting performance .....	A .....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A ..	Require repair or replacement.

Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

(2) - Distortion may be the result of overheating; coil should be tested.

(3) - Inoperative includes intermittent operation.

AA

IGNITION CONTROL MODULES (ICM)

IGNITION CONTROL MODULE (ICM) INSPECTION

AA

Condition	Code		Procedure
Application incorrect ...	B	.....	Require replacement.
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware threads damaged .....	A	...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	...	Require repair or replacement of hardware.
Code set (if applicable) .....	A	.....	(1) Further inspection required.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(2) Require repair or replacement.
Connector missing .....	A	.....	Require repair.
Contaminated .....	A	.....	(3) Require repair or replacement.
Leaking .....	A	..	Require repair or replacement.
Malfunctioning .....	A	.....	(4) Require repair or replacement.
Missing .....	C	.....	Require replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(2) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not			

affecting performance .. 1 .. Suggest repair or replacement.  
 Threads damaged ..... A .. Require repair or replacement.  
 Wire lead conductors  
 exposed ..... B .. Require repair or replacement.  
 Wire lead corroded ..... A .. Require repair or replacement.  
 Wire lead open ..... A .. Require repair or replacement.  
 Wire lead shorted ..... A .. Require repair or replacement.

- (1) - Refer to manufacturer's diagnostic trouble code procedure and require repair or replacement of affected component(s).
- (2) - Determine cause and correct prior to repair or replacement of part.
- (3) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (4) - Includes inoperative, intermittent operation, or failure to perform all functions.

AA

IGNITION SWITCHES

See SWITCHES.

IGNITION TERMINALS

See

IGNITION WIRES, BOOTS, COIL TOWERS AND TERMINALS (SECONDARY).

IGNITION WIRES, BOOTS, COIL TOWERS AND TERMINALS (SECONDARY)

NOTE: You are not required to replace ignition wires in sets. However, you may suggest replacement of the entire secondary wire set for preventive maintenance.

IGNITION WIRE, BOOT, COIL TOWER AND TERMINAL (SECONDARY) INSPECTION

AA

Condition	Code	Procedure
Application incorrect ...	B .....	Require replacement.
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Carbon-tracked .....	A .....	Require replacement.
Corroded .....	1 ..	Suggest repair or replacement.
Insulation leaking (shorted) .....	A ..	Require repair or replacement.
Metal heat shield bent ..	2 ..	Suggest repair or replacement.
Missing .....	C .....	Require replacement.
Oil-soaked (spongy) .....	1 .....	Suggest replacement.
Resistance incorrect ....	B .....	Require replacement.
Routed incorrectly .....	2 .....	(1) Suggest repair.
Terminal broken .....	A ..	Require repair or replacement.
Terminal burned, affecting performance .....	A .....	(2) Require repair or replacement.
Terminal burned, not affecting performance ..	2 ..	Suggest repair or replacement.

Terminal corroded,  
affecting performance .. A .. Require repair or replacement.  
Terminal corroded, not  
affecting performance .. 2 .. Suggest repair or replacement.  
Terminal loose, affecting  
performance ..... B .. Require repair or replacement.  
Terminal loose, not  
affecting performance .. 1 .. Suggest repair or replacement.

(1) - If improper routing affects the performance of other systems, require repair. Proper routing, hardware, heatshields, etc., are intended to prevent premature failure of secondary ignition components.

(2) - Determine cause and correct prior to repair or replacement of part.

AA

#### IN-TANK FUEL STRAINERS

##### IN-TANK FUEL STRAINER INSPECTION

AA

Condition	Code	Procedure
Missing .....	C .....	Require replacement.
Restricted .....	A ..	Require repair or replacement.
Torn .....	A .....	Require replacement.

AA

#### INERTIA FUEL SHUT-OFF SWITCHES

##### INERTIA FUEL SHUT-OFF SWITCH INSPECTION

AA

Condition	Code	Procedure
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Connector broken .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	C .....	Require replacement.
Contaminated .....	A .....	(2) Require replacement.
Inoperative .....	A .....	(3) Require repair or replacement.
Missing .....	C .....	Require replacement.
Terminal broken .....	A ..	Require repair or replacement.
Terminal burned, affecting performance .....	A .....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A ..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B ..	Require repair or replacement.
Terminal loose, not		

affecting performance ..	1	..	Suggest repair or replacement.
Wire lead conductors			
exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification.

AA

INTAKE AIR TEMPERATURE SENSORS

INTAKE AIR TEMPERATURE SENSOR INSPECTION

AA

Condition	Code		Procedure
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware threads damaged .....	A	...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	...	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Contaminated .....	A	.....	(2) Require repair or replacement.
Inoperative .....	B	.....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.
Restricted, affecting performance .....	A	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.

Threads stripped (threads missing) ..... A ..... Require replacement.  
 Wire lead conductors exposed ..... B .. Require repair or replacement.  
 Wire lead corroded ..... A .. Require repair or replacement.  
 Wire lead open ..... A .. Require repair or replacement.  
 Wire lead shorted ..... A .. Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

INTAKE MANIFOLDS

INTAKE MANIFOLD INSPECTION

AA

Condition	Code	Procedure
Corroded, affecting sealability .....	A ..	Require repair or replacement.
Integrated air or fuel control components inoperative .....	A .....	(1) Require repair or replacement.
Internal air or fuel components damaged, affecting performance ..	A ...	Require repair or replacement of component.
Internal air or fuel components damaged, not affecting performance ..	.. ..	..... No service suggested or required.
Internal air or fuel components missing .....	C .....	Require replacement of component.
Leaking .....	A ..	Require repair or replacement.
Out of specification ....	B .....	Require replacement.
Restricted .....	A ..	Require repair or replacement.
Threads damaged .....	A ..	Require repair or replacement.
Threads stripped (threads missing) .....	A ..	Require repair or replacement.
Warped .....	B ..	Require repair or replacement.

- (1) - Inoperative includes intermittent operation or out of OEM specification.

AA

INTERCOOLERS

See CHARGE AIR COOLERS "INTERCOOLERS" (CAC).

KNOCK SENSORS

KNOCK SENSOR INSPECTION

AA

Condition	Code	Procedure
-----------	------	-----------

Attaching hardware

missing .....	C	.....	Require replacement of hardware.
Attaching hardware threads damaged .....	A	...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	...	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Inoperative .....	B	.....	(2) Require repair or replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

(2) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

LIQUID VAPOR SEPARATORS

LIQUID VAPOR SEPARATOR INSPECTION

AA

Condition	Code	Procedure
Inoperative .....	A	..... (1) Require repair or replacement.
Leaking .....	A	..... Require replacement.
Missing .....	C	..... Require replacement.
Restricted .....	A	.. Require repair or replacement.

(1) - Inoperative includes intermittent operation or out of OEM specification.

AA

MANIFOLD ABSOLUTE PRESSURE (MAP) SENSORS

MANIFOLD ABSOLUTE PRESSURE (MAP) SENSOR INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C	..... Require replacement of hardware.
Attaching hardware threads damaged .....	A	... Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	... Require repair or replacement of hardware.
Connector broken .....	A	.. Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	.. Require repair or replacement.
Connector melted .....	A	..... (1) Require repair or replacement.
Connector missing .....	C	..... Require replacement.
Contaminated .....	A	..... (2) Require repair or replacement.
Inoperative .....	B	..... (3) Require repair or replacement. Further inspection required.
Leaking .....	A	.. Require repair or replacement.
Missing .....	C	..... Require replacement.
Resistance out of specification .....	B	.. Require repair or replacement.
Restricted, affecting performance .....	A	.. Require repair or replacement.
Terminal broken .....	A	.. Require repair or replacement.
Terminal burned, affecting performance .....	A	..... (1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	.. Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	.. Require repair or replacement.
Terminal corroded, not affecting performance ..	2	.. Suggest repair or replacement.
Terminal loose, affecting performance .....	B	.. Require repair or replacement.
Terminal loose, not affecting performance ..	1	.. Suggest repair or replacement.
Threads damaged .....	A	.. Require repair or replacement.
Threads stripped (threads missing) .....	A	..... Require replacement.
Wire lead conductors exposed .....	B	.. Require repair or replacement.
Wire lead corroded .....	A	.. Require repair or replacement.
Wire lead open .....	A	.. Require repair or replacement.
Wire lead shorted .....	A	.. Require repair or replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

(2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or

replacement.

(3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

MASS AIR FLOW (MAF) SENSORS

MASS AIR FLOW (MAF) SENSOR INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C	Require replacement of hardware.
Attaching hardware threads damaged .....	A	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	Require repair or replacement of hardware.
Connector broken .....	A	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	Require repair or replacement.
Connector melted .....	A	(1) Require repair or replacement.
Connector missing .....	C	Require replacement.
Contaminated .....	A	(2) Require repair or replacement.
Inoperative .....	B	(3) Require repair or replacement. Further inspection required.
Leaking .....	A	Require repair or replacement.
Missing .....	C	Require replacement.
Resistance out of specification .....	B	Require repair or replacement.
Restricted, affecting performance .....	A	Require repair or replacement.
Terminal broken .....	A	Require repair or replacement.
Terminal burned, affecting performance .....	A	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	Require repair or replacement.
Terminal loose, not affecting performance ..	1	Suggest repair or replacement.
Threads damaged .....	A	Require repair or replacement.
Threads stripped (threads missing) .....	A	Require replacement.
Wire lead conductors exposed .....	B	Require repair or replacement.
Wire lead corroded .....	A	Require repair or replacement.
Wire lead open .....	A	Require repair or replacement.
Wire lead shorted .....	A	Require repair or replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

METAL AIR MANIFOLDS AND PIPES

METAL AIR MANIFOLD AND PIPE INSPECTION

AA

Condition	Code	Procedure
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Broken .....	A .....	Require repair of injection tube or replacement of manifold.
Corroded, affecting structural integrity ...	1 .....	Suggest replacement of injection tube or manifold.
Leaking .....	A .....	Require repair of injection tube or replacement of manifold.
Loose .....	A .....	Require repair.
Missing .....	C .....	Require replacement.
Restricted .....	A .....	Require replacement of injection tube or manifold.
Threads damaged .....	A .....	Require repair.
Threads stripped (threads missing) .....	A .....	Require replacement.

AA

METAL AIR PIPES

See METAL AIR MANIFOLDS AND PIPES.

MIX CONTROL SOLENOIDS

MIX CONTROL SOLENOID INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware threads damaged .....	A ...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A ...	Require repair or replacement of hardware.
Connector broken .....	A ..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A ..	Require repair or replacement.

Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Contaminated .....	A	.....	(2) Require repair or replacement.
Inoperative .....	B	.....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.
Restricted, affecting performance .....	A	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

MOTOR MOUNTS

MOTOR MOUNT INSPECTION

AA

Condition	Code	Procedure
Attaching hardware broken .....	A	... Require repair or replacement of hardware.
Attaching hardware missing .....	C	..... Require replacement of hardware.
Attaching hardware not functioning .....	A	... Require repair or replacement of hardware.
Broken .....	A	..... Require replacement.
Leaking (hydraulic		

mount) .....	A	.....	Require replacement.
Mounting hole worn, affecting performance ..	A	.....	Require replacement.
Mounting hole worn, not affecting performance .. ..	..	.....	No service suggested or required.
Rubber deteriorated, affecting performance ..	A	.....	Require replacement.
Rubber deteriorated, not affecting performance .. ..	..	.....	No service suggested or required.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
AA			

O-RINGS, GASKETS, SEALS AND SPRING LOCKS

O-RING, GASKET, SEAL AND SPRING LOCK INSPECTION  
 AA

Condition	Code		Procedure
Leaking .....	A	.....	(1) Require repair or replacement.

(1) - Require inspection of mating and sealing surface and  
 repair or replace as necessary.  
 AA

O2 SENSORS

O2 SENSOR INSPECTION  
 AA

Condition	Code		Procedure
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware threads damaged .....	A	...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	..	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Contaminated .....	A	.....	(2) Require repair or replacement.
Inoperative .....	B	.....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.
Maintenance intervals ...	3	...	Suggest replacement to comply with vehicle's OEM recommended service intervals.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.
Restricted, affecting			

performance .....	A	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

(2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.

(3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

OIL PANS

See the following:

- ENGINE COVERS
- GASKETS
- GROMMETS (VALVE COVER)

OIL PRESSURE SENDING UNITS

OIL PRESSURE SENDING UNIT INSPECTION

AA

Condition	Code		Procedure
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Inoperative .....	A	.....	(2) Require repair or replacement.
Leaking .....	A	.....	Require replacement.
Output signal incorrect .	B	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.

Terminal corroded, affecting performance ..	A ..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B ..	Require repair or replacement.
Terminal loose, not affecting performance ..	1 ..	Suggest repair or replacement.
Threads damaged .....	A ..	Require repair or replacement.
Threads stripped (threads missing) .....	A .....	Require replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

(2) - Inoperative includes intermittent operation or out of OEM specification.

AA

OIL PUMP PICK-UP SCREENS

OIL PUMP PICK-UP SCREEN INSPECTION

AA

Condition	Code	Procedure
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Bypass stuck .....	A ..	Require repair or replacement.
Cracked .....	A ..	Require repair or replacement.
Loose .....	A ..	Require repair or replacement.
Missing .....	C .....	Require replacement.
Positioned incorrectly ..	A ..	Require repair or replacement.
Restricted .....	A ..	Require repair or replacement.
Screen torn .....	A .....	Require replacement.

AA

OIL PUMPS

OIL PUMP INSPECTION

AA

Condition	Code	Procedure
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ..	Require repair or replacement of hardware.
Broken .....	A ..	Require repair or replacement.
Housing cracked .....	A ..	Require repair or replacement.
Leaking .....	A ..	Require repair or replacement.
Pressure relief valve stuck .....	A ..	Require repair or replacement.
Seized .....	A ..	Require repair or replacement.
Worn beyond		

specifications ..... B .. Require repair or replacement.  
 ~~~~~

PARK NEUTRAL POSITION SWITCHES

PARK NEUTRAL POSITION SWITCH INSPECTION  
 ~~~~~

Condition	Code	Procedure
Attaching hardware missing .....	C	Require replacement of hardware.
Attaching hardware threads damaged .....	A	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	Require repair or replacement of hardware.
Connector broken .....	A	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	Require repair or replacement.
Connector melted .....	A	(1) Require repair or replacement.
Connector missing .....	C	Require replacement.
Contaminated .....	A	(2) Require repair or replacement.
Inoperative .....	B	(3) Require repair or replacement. Further inspection required.
Leaking .....	A	Require repair or replacement.
Missing .....	C	Require replacement.
Resistance out of specification .....	B	Require repair or replacement.
Terminal broken .....	A	Require repair or replacement.
Terminal burned, affecting performance .....	A	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	Require repair or replacement.
Terminal loose, not affecting performance ..	1	Suggest repair or replacement.
Threads damaged .....	A	Require repair or replacement.
Threads stripped (threads missing) .....	A	Require replacement.
Wire lead conductors exposed .....	B	Require repair or replacement.
Wire lead corroded .....	A	Require repair or replacement.
Wire lead open .....	A	Require repair or replacement.
Wire lead shorted .....	A	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable;

check for accepted cleaning procedure.

AA

PCV BREATHER ELEMENTS

PCV BREATHER ELEMENT INSPECTION

AA

Condition	Code	Procedure
Attaching hardware broken.....	A	... Require repair or replacement of hardware.
Attaching hardware missing .....	C	..... Require replacement of hardware.
Attaching hardware not functioning .....	A	... Require repair or replacement of hardware.
Leaking .....	A	..... Require replacement.
Maintenance intervals ...	3	... Suggest replacement to comply with vehicle's OEM recommended service intervals.
Melted .....	A	..... Required replacement.
Missing .....	C	..... Require replacement.
Restricted, affecting performance .....	A	..... Require replacement.
Restricted, not affecting performance .....	1	..... Suggest replacement.
Water-contaminated .....	A	..... Require replacement.

AA

PCV ORIFICES

PCV ORIFICE INSPECTION

AA

Condition	Code	Procedure
Leaking .....	A	..... Require replacement.
Maintenance interval ....	3	... Suggest repair or replacement to comply with OEM recommended service intervals.
Missing .....	C	..... Require replacement.
Restricted .....	A	.. Require repair or replacement.

AA

PCV VALVES

PCV VALVE INSPECTION

AA

Condition	Code	Procedure
Application incorrect ...	B	..... Require replacement.
Attaching hardware broken .....	A	... Require repair or replacement of hardware.
Attaching hardware missing .....	C	..... Require replacement of hardware.
Attaching hardware not functioning .....	A	... Require repair or replacement of hardware.
Grommet broken .....	A	... Require repair or replacement of grommet.
Grommet missing .....	C	. Require replacement of grommet.

Grommet not functioning .....	A	...	Require repair or replacement of grommet.
Inoperative .....	A	.....	(1) Require replacement.
Leaking .....	A	.....	Require replacement.
Maintenance interval ....	3	...	Suggest replacement to comply with vehicle's OEM recommended service intervals.
Missing .....	C	.....	Require replacement.
Restricted .....	A	.....	Require replacement.

(1) - Inoperative includes intermittent operation or out of OEM specification.

AA

PICK-UP ASSEMBLIES (INCLUDES MAGNETIC, HALL EFFECT AND OPTICAL)

PICK-UP ASSEMBLY (MAGNETIC, HALL EFFECT AND OPTICAL) INSPECTION  
 AA

Condition	Code		Procedure
Adjustment incorrect ....	B	.....	Require repair.
Attaching hardware broken .....	A	...	Require repair or replacement of hardware.
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware not functioning .....	A	...	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Inoperative .....	B	.....	(2) Require replacement.
Oil-soaked .....	A	.....	Require replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

(2) - Inoperative includes intermittent operation or out of OEM specification. Refer to OEM recommended service'

procedures.

AA

POWER STEERING PRESSURE SENSORS

POWER STEERING PRESSURE SENSOR INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C	..... Require replacement of hardware.
Attaching hardware threads damaged .....	A	... Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	... Require repair or replacement of hardware.
Connector broken .....	A	.. Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	.. Require repair or replacement.
Connector melted .....	A	..... (1) Require repair or replacement.
Connector missing .....	C	..... Require replacement.
Contaminated .....	A	..... (2) Require repair or replacement.
Inoperative .....	B	..... (3) Require repair or replacement. Further inspection required.
Leaking .....	A	.. Require repair or replacement.
Missing .....	C	..... Require replacement.
Resistance out of specification .....	B	.. Require repair or replacement.
Restricted, affecting performance .....	A	.. Require repair or replacement.
Terminal broken .....	A	.. Require repair or replacement.
Terminal burned, affecting performance .....	A	..... (1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	.. Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	.. Require repair or replacement.
Terminal corroded, not affecting performance ..	2	.. Suggest repair or replacement.
Terminal loose, affecting performance .....	B	.. Require repair or replacement.
Terminal loose, not affecting performance ..	1	.. Suggest repair or replacement.
Threads damaged .....	A	.. Require repair or replacement.
Threads stripped (threads missing) .....	A	..... Require replacement.
Wire lead conductors exposed .....	B	.. Require repair or replacement.
Wire lead corroded .....	A	.. Require repair or replacement.
Wire lead open .....	A	.. Require repair or replacement.
Wire lead shorted .....	A	.. Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.

(3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

POWERTRAIN CONTROL MODULES (PCM) AND PROM

POWERTRAIN CONTROL MODULE (PCM) AND PROM INSPECTION

AA

Condition	Code	Procedure
Application incorrect ...	B .....	Require replacement.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware threads damaged .....	A ...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A ...	Require repair or replacement of hardware.
Code set (if applicable) .....	A .....	(1) Further inspection required.
Connector broken .....	A ..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(2) Require repair or replacement.
Connector missing .....	A .....	Require repair.
Contaminated .....	A .....	(3) Require repair or replacement.
Leaking .....	A ..	Require repair or replacement.
Malfunctioning .....	A .....	(4) Require repair or replacement.
Missing .....	C .....	Require replacement.
Terminal broken .....	A ..	Require repair or replacement.
Terminal burned, affecting performance .....	A .....	(2) Require repair or replacement.
Terminal burned, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A ..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B ..	Require repair or replacement.
Terminal loose, not affecting performance ..	1 ..	Suggest repair or replacement.
Threads damaged .....	A ..	Require repair or replacement.
Threads stripped (threads missing) .....	A .....	Require replacement.
Wire lead conductors exposed .....	B ..	Require repair or replacement.
Wire lead corroded .....	A ..	Require repair or replacement.
Wire lead open .....	A ..	Require repair or replacement.
Wire lead shorted .....	A ..	Require repair or replacement.

(1) - Refer to manufacturer's diagnostic trouble code procedure and require repair or replacement of affected component(s).

(2) - Determine cause and correct prior to repair or

replacement of part.

(3) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.

(4) - Includes inoperative, intermittent operation, failure to perform all functions, or out of OEM specification.

AA

POWERTRAIN CONTROL PROM

See POWERTRAIN CONTROL MODULES (PCM) AND PROM.

PRESSURIZED EXPANSION TANK CAPS

See RADIATOR CAPS AND PRESSURIZED EXPANSION TANK CAPS.

RADIATOR CAPS AND PRESSURIZED EXPANSION TANK CAPS

RADIATOR CAP AND PRESSURIZED EXPANSION TANK CAP INSPECTION

AA

Condition	Code	Procedure
Application incorrect	B	Require replacement.
Coolant recovery check valve inoperative	A	(1) Require replacement.
Fails to maintain proper pressure	B	Require replacement.
Gasket missing	C	Require replacement of gasket.
Missing	C	Require replacement.
Seal missing	C	Require replacement of seal.

(1) - Inoperative includes intermittent operation or out of OEM specification.

AA

RADIATOR FAN BLADES

RADIATOR FAN BLADE INSPECTION

AA

Condition	Code	Procedure
Application incorrect	B	Require replacement.
Attaching hardware broken	A	Require repair or replacement of hardware.
Attaching hardware missing	C	Require replacement of hardware.
Attaching hardware not functioning	A	Require repair or replacement of hardware.
Bent	A	Require replacement.
Broken	A	Require replacement.
Cracked	A	Require replacement.
Loose	A	Require repair or replacement.
Missing	C	Require replacement.

AA

RADIATOR FAN CLUTCHES

NOTE: Some lateral movement, measured at the fan blade tip, may be normal.

RADIATOR FAN CLUTCH INSPECTION

AA

Condition	Code	Procedure
Attaching hardware broken .....	A	... Require repair or replacement of hardware.
Attaching hardware missing .....	C	..... Require replacement of hardware.
Attaching hardware not functioning .....	A	... Require repair or replacement of hardware.
Bearing noisy .....	A	..... Require replacement.
Bearing worn .....	A	..... Require replacement.
Fastener loose .....	A	... Require repair or replacement of fastener.
Inoperative .....	A	..... (1) Require replacement.
Leaking .....	1	..... Suggest replacement.
Seized .....	A	..... Require replacement.
Slips (insufficient fan speed) .....	A	..... Require replacement.
Thermal control incorrect .....	B	.. Require repair or replacement.

(1) - Inoperative includes intermittent operation or out of OEM specification.

AA

RADIATORS

RADIATOR INSPECTION

AA

Condition	Code	Procedure
Air flow restriction ....	A	..... Require repair.
Application incorrect ...	B	..... Require replacement.
Attaching hardware broken .....	A	... Require repair or replacement of hardware.
Attaching hardware missing .....	C	..... Require replacement of hardware.
Attaching hardware not functioning .....	A	.. Require repair or replacement of hardware.
Connection leaking .....	A	.. Require repair or replacement.
Corroded .....	1	.. Suggest repair or replacement.
Fins damaged, affecting performance .....	A	.. Require repair or replacement.
Fins damaged, not affecting performance ..	2	.. Suggest repair or replacement.
Internal oil cooler leaking .....	A	.. Require repair or replacement.
Internal restrictions, affecting performance ..	B	.. Require repair or replacement.
Internal restrictions, not affecting performance ..	2	.. Suggest repair or replacement.
Leaking .....	A	.. Require repair or replacement.
Threads damaged .....	A	.. Require repair or replacement.
Threads stripped (threads missing) .....	A	.. Require repair or replacement.
Tubes damaged, affecting performance .....	A	.. Require repair or replacement.
Tubes damaged, not		

affecting performance .. .. . No service suggested or required.

AA

ROLL OVER VALVES

ROLL OVER VALVE INSPECTION

AA

Condition	Code	Procedure
Inoperative .....	A .....	(1) Require replacement.
Leaking .....	A .....	Require replacement.
Missing .....	C .....	Require replacement.

(1) - Inoperative includes intermittent operation or out of OEM specification.

AA

SEALING COMPOUNDS

SEALING COMPOUND INSPECTION

AA

Condition	Code	Procedure
Leaking .....	A .....	(1) Require repair or replacement.

(1) - Require inspection of mating and sealing surface and repair or replace as necessary.

AA

SEALS

SEAL INSPECTION

AA

Condition	Code	Procedure
Leaking .....	A .....	(1) Require repair or replacement.

(1) - Require inspection of mating and sealing surface and repair or replace as necessary.

AA

SECONDARY AIR INJECTION SYSTEM MANAGEMENT DEVICES

SECONDARY AIR INJECTION SYSTEM MANAGEMENT DEVICE INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware threads damaged .....	A ...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A ..	Require repair or replacement of hardware.
Connector broken .....	A ..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or

				replacement.
Connector missing	.....	C	.....	Require replacement.
Contaminated	.....	A	.....	(2) Require repair or replacement.
Inoperative	.....	B	.....	(3) Require repair or replacement. Further inspection required.
Leaking	.....	A	..	Require repair or replacement.
Missing	.....	C	.....	Require replacement.
Resistance out of specification	.....	B	..	Require repair or replacement.
Restricted, affecting performance	.....	A	..	Require repair or replacement.
Terminal broken	.....	A	..	Require repair or replacement.
Terminal burned, affecting performance	.....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance	..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance	..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance	..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance	.....	B	..	Require repair or replacement.
Terminal loose, not affecting performance	..	1	..	Suggest repair or replacement.
Threads damaged	.....	A	..	Require repair or replacement.
Threads stripped (threads missing)	.....	A	.....	Require replacement.
Wire lead conductors exposed	.....	B	..	Require repair or replacement.
Wire lead corroded	.....	A	..	Require repair or replacement.
Wire lead open	.....	A	..	Require repair or replacement.
Wire lead shorted	.....	A	..	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

SENSORS AND ACTUATORS

NOTE: Conditions pertaining to the sensors and actuators listed in this section may be found under the name of the sensor or actuator.

SENSOR ABBREVIATION TABLE

AA

Sensor	Abbreviation
Accelerator Pedal Position Sensor	APP
Air Conditioning Cycling Switch	AC
Air Conditioning Pressure Sensor	..
Air Fuel Ratio Sensor	..
Barometric Pressure Sensor	BARO
Camshaft Position Sensor	CMP
Clutch Pedal Position Switch	CPP
Cooling Fan Motor Sensors and Switches	..

Crankshaft Position Sensor .....	CKP
Electronic Transmission Feedback Devices .....	..
Engine Coolant Temperature Sensor .....	ECT
Evaporative Emission feedback devices .....	..
Exhaust Gas Recirculation feedback devices .....	..
Fan Control Sensor .....	FC
Intake Air Temperature Sensor .....	IAT
Knock Sensor .....	KS
Manifold Absolute Pressure Sensor .....	MAP
Mass Air Flow Sensor .....	MAF
O2 Sensor .....	O2S
Park Neutral Position Switch .....	PNP
Power Steering Pressure Sensor .....	PSP
Thermal Vacuum Valve .....	TVV
Throttle Position Sensor .....	TP Sensor
Throttle Position Switch .....	..
Transmission Range Switch .....	TR Switch
Vehicle Speed Sensor .....	VSS
Volume Air Flow Sensor .....	VAF
AA	

ACTUATOR ABBREVIATION TABLE

AA	
Actuator	Abbreviation
Air Injection Control Solenoid .....	..
Electronic Transmission control devices .....	..
Evaporative Emission Canister .....	EVAP
Purge Device .....	..
Exhaust Gas Recirculation Device .....	EGR
Fuel Injector .....	..
Idle Air Control .....	IAC
Idle Speed Control Actuator .....	ISC
Mix Control Solenoid .....	MC Solenoid
Secondary Air Injection System Management Device ....	AIR, PAIR
Vacuum Regulator Solenoid .....	..
Waste Gate Control Solenoid .....	..
AA	

SHROUDS, BAFFLES AND DEFLECTORS

SHROUD, BAFFLE AND DEFLECTOR INSPECTION

AA		
Condition	Code	Procedure
Application incorrect, affecting cooling system performance .....	A	. Require repair or replacement.
Attaching hardware broken .....	A	.. Require repair or replacement of hardware.
Attaching hardware missing .....	C	..... Require replacement of hardware.
Attaching hardware not functioning .....	A	.. Require repair or replacement of hardware.
Bent, affecting cooling system performance .....	A	. Require repair or replacement.
Blocked, affecting cooling system performance .....	A	. Require repair or replacement.
Broken, affecting cooling system performance .....	A	. Require repair or replacement.
Cracked, affecting cooling		

system performance ..... A . Require repair or replacement.  
 Loose, affecting cooling  
 system performance ..... A ..... Require repair.  
 Loose, not affecting  
 cooling system  
 performance ..... 2 ..... Suggest repair.  
 Missing, affecting cooling  
 system performance ..... C ..... Require replacement.  
 ~~~~~

SPARK PLUGS

NOTE: You are not required to replace spark plugs in sets.  
 However, you may suggest replacement of the other plugs  
 for preventive maintenance.

SPARK PLUG INSPECTION

~~~~~  
 Condition Code Procedure  
 Application incorrect ... B ..... Require replacement.  
 Electrode eroded ..... 1 ..... Suggest replacement.  
 Fouled ..... A ..... (1) Require repair or  
 replacement.  
 Gap incorrect ..... B .. Require repair or replacement.  
 Insulation broken ..... A ..... Require replacement  
 Insulator cracked ..... A ..... Require replacement.  
 Leaking compression ..... A .. Require repair or replacement.  
 Maintenance interval .... 3 ..... Suggest replacement.  
 Threads damaged ..... A .. Require repair or replacement.  
 Threads stripped (threads  
 missing) ..... A ..... Require replacement.

(1) - Determine cause of fouling and suggest repair.

~~~~~

SPRING LOCKS

SPRING LOCK INSPECTION

~~~~~  
 Condition Code Procedure  
 Leaking ..... A ..... (1) Require repair or  
 replacement.

(1) - Require inspection of mating and sealing surface and  
 repair or replace as necessary.

~~~~~

SUPER CHARGERS

SUPER CHARGER INSPECTION

~~~~~  
 Condition Code Procedure  
 Attaching hardware  
 damaged, affecting  
 operation or  
 performance ..... A ... Require repair or replacement  
 of hardware.  
 Attaching hardware  
 missing ..... C ..... Require replacement of  
 hardware.  
 Bearing noisy ..... A ..... Require replacement.

Bearing worn .....	A	.....	Require replacement.
Boost pressure incorrect .....	A	.....	(1) Require repair or replacement.
Clearance out of specification .....	B	..	Require repair or replacement.
Leaking .....	A	..	Require repair or replacement.
Noisy .....	2	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	..	Require repair or replacement.

(1) - Boost pressure problems may be caused by other systems or components.

AA

SWITCHES

SWITCH INSPECTION

AA

Condition	Code		Procedure
Attaching hardware broken .....	A	...	Require repair or replacement of hardware.
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware not functioning .....	A	...	Require repair or replacement of hardware.
Binding, affecting performance .....	A	..	Require repair or replacement.
Binding, not affecting performance .....	2	..	Suggest repair or replacement.
Broken .....	A	..	Require repair or replacement.
Burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Burned, not affecting performance .....	2	.....	(1) Suggest repair or replacement.
Cracked, affecting performance .....	A	..	Require repair or replacement.
Cracked, not affecting performance .....	1	..	Suggest repair or replacement.
Leaking .....	A	..	Require repair or replacement.
Malfunctioning .....	A	.....	(2) Require repair or replacement.
Melted, affecting performance .....	A	.....	(1) Require repair or replacement.
Melted, not affecting performance .....	2	.....	(1) Suggest repair or replacement.
Missing .....	C	.....	Require replacement.
Out of adjustment .....	B	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded,			

affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Won't return .....	A	..	Require repair or replacement.
Worn .....	1	.....	Suggest replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

(2) - Includes inoperative, intermittent operation, or failure to perform all functions.

AA

THERMAL VACUUM VALVES

THERMAL VACUUM VALVE INSPECTION

AA

Condition	Code		Procedure
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Contaminated .....	A	.....	(2) Require repair or replacement.
Inoperative .....	B	.....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.
Restricted, affecting performance .....	A	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

(2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.

(3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

THERMOSTATIC AIR DOOR ASSEMBLIES

THERMOSTATIC AIR DOOR ASSEMBLY INSPECTION

AA

Condition	Code	Procedure
Attaching hardware damaged, affecting operation or performance .....	A	... Require repair or replacement of hardware.
Attaching hardware missing .....	C	..... Require replacement of hardware.
Binding .....	A	.. Require repair or replacement.
Leaking .....	A	.. Require repair or replacement.
Missing .....	C	..... Require replacement.
Seized .....	A	.. Require repair or replacement.

AA

THERMOSTATS AND HOUSINGS

THERMOSTAT AND HOUSING INSPECTION

AA

Condition	Code	Procedure
Application incorrect ...	B	..... Require replacement.
Attaching hardware broken .....	A	... Require repair or replacement of hardware.
Attaching hardware corroded .....	A	... Require repair or replacement of hardware.
Attaching hardware missing .....	C	..... Require replacement of hardware.
Attaching hardware not functioning .....	A	... Require repair or replacement of hardware.
Housing corroded .....	1	.. Suggest replacement of housing.
Inoperative .....	A	..... (1) Require replacement.
Installation incorrect ..	B	.. Require repair or replacement.
Leaking .....	A	.. Require repair or replacement.
Thermostat missing .....	C	..... Require replacement of thermostat.
Threads damaged .....	A	.. Require repair or replacement.
Threads stripped (threads missing) .....	A	.. Require repair or replacement.

(1) - Inoperative includes intermittent operation or out of OEM specification.

AA

THROTTLE BODIES

THROTTLE BODY INSPECTION

AA

Condition	Code	Procedure
Connector broken .....	A ..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	C .....	Require replacement.
Contaminated .....	A .....	(2) Require repair or replacement.
Deposits on throttle body components .....	A .....	(3) Require repair.
Leaking .....	A ..	Require repair or replacement.
Restricted, affecting performance .....	A .....	(4) Require repair.
Restricted, not affecting performance .....	2 .....	Suggest repair.
Terminal broken .....	A ..	Require repair or replacement.
Terminal burned, affecting performance .....	A .....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A ..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2 ..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B ..	Require repair or replacement.
Terminal loose, not affecting performance ..	1 ..	Suggest repair or replacement.
Threads damaged .....	A ..	Require repair or replacement.
Threads stripped (threads missing) .....	A ..	Require repair or replacement.
Throttle shaft binding, affecting performance ..	A ..	Require repair or replacement.
Throttle shaft worn, affecting performance ..	A ..	Require repair or replacement.
Throttle shaft worn, not affecting performance ..	1 ..	Suggest repair or replacement.
Wire lead conductors exposed .....	B ..	Require repair or replacement.
Wire lead corroded .....	A ..	Require repair or replacement.
Wire lead open .....	A ..	Require repair or replacement.
Wire lead shorted .....	A ..	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Some throttles are coated by manufacturer, follow OEM-recommended procedures.
- (4) - Some components may be serviceable; check for accepted cleaning procedure.

AA

THROTTLE CABLES

See THROTTLE LINKAGES AND CABLES.

THROTTLE LINKAGES AND CABLES

THROTTLE LINKAGE AND CABLE INSPECTION

AA

Condition	Code	Procedure
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ..	Require repair or replacement of hardware.
Bent .....	A ..	Require repair or replacement.
Binding .....	A ..	Require repair or replacement.
Bracket bent, affecting performance .....	A ..	Require repair or replacement.
Bracket bent, not affecting performance .. ..	.. ..	..... No service suggested or required.
Bracket broken, affecting performance .....	A	Require replacement.
Bracket broken, not affecting performance .. ..	.. ..	..... No service suggested or required.
Bracket corroded, affecting performance ..	A ..	Require repair or replacement.
Bracket corroded, not affecting performance ..	2 ..	Suggest repair or replacement.
Bracket cracked, affecting performance .....	A ..	Require repair or replacement.
Bracket cracked, not affecting performance ..	1 ..	Suggest repair or replacement.
Bracket loose, affecting performance .....	A ..	Require repair or replacement.
Bracket loose, not affecting performance ..	1 ..	Suggest repair or replacement.
Bracket missing .....	C .....	Require replacement.
Broken .....	A .....	Require replacement.
Cracked .....	A ..	Require repair or replacement.
Disconnected .....	A ..	Require repair or replacement.
Kinked .....	A ..	Require repair or replacement.
Melted .....	A ..	Require repair or replacement.
Missing .....	C .....	Require replacement.
Noisy .....	2 ..	Suggest repair or replacement.
Out of adjustment .....	B .....	(1) Require repair or replacement.
Routed incorrectly .....	2 .....	Suggest repair.
Seized .....	A ..	Require repair or replacement.

(1) - Follow OEM recommended adjustment procedures. Require repair or replacement if out of specification.

AA

THROTTLE POSITION SENSORS

THROTTLE POSITION SENSOR INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware		

threads damaged .....	A	...	Require repair or replacement of hardware.
Attaching hardware			
threads stripped (threads missing) .....	A	...	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Contaminated .....	A	.....	(2) Require repair or replacement.
Inoperative .....	B	.....	(3) Require repair or replacement. Further inspection required.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....			
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	..	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors			
exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

THROTTLE POSITION SWITCHES

THROTTLE POSITION SWITCH INSPECTION

AA

Condition	Code		Procedure
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware threads damaged .....	A	...	Require repair or replacement of hardware.

Attaching hardware threads stripped (threads missing) .....	A	..	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Inoperative .....	B	.....	(2) Require repair or replacement. Further inspection required.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

(2) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

TIMING BELT SPROCKETS

TIMING BELT SPROCKET INSPECTION

AA

Condition	Code		Procedure
Alignment incorrect .....	B	.....	Require repair.
Attaching hardware broken .....	A	...	Require repair or replacement of hardware.
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware not functioning .....	A	...	Require repair or replacement of hardware.
Bent .....	A	.....	Require replacement.
Cracked .....	A	.....	Require replacement.

Key damaged .....	A	.....	Require replacement.
Loose .....	A	..	Require repair or replacement.
Missing .....	C	.....	Require replacement.
Pulley damaged, affecting belt life .....	A	.....	Require replacement.
Sprocket damaged, affecting belt life ....	A	..	Require repair or replacement.
Sprocket loose .....	B	..	Require repair or replacement.
Sprocket-to-shaft alignment incorrect .....	B	..	Require repair or replacement.

AA

TIMING BELTS

TIMING BELT INSPECTION

AA

Condition	Code		Procedure
Adjustment incorrect ....	2	.....	(1) Suggest adjustment.
Alignment incorrect .....	B	.....	(2) Further inspection required.
Broken .....	A	.....	Require replacement.
Cam timing out of specification .....	B	.....	Require repair.
Cracked .....	1	.....	Suggest replacement.
Fluid-soaked .....	1	..	Suggest replacement. Further inspection required.
Frayed .....	1	.....	Suggest replacement.
Maintenance intervals ...	3	..	Suggest replacement to comply with vehicle OEM recommended service intervals.
Missing .....	C	.....	(3) Require replacement.
Noisy .....	2	.....	(4) Further inspection required. See note below.
Plies separated .....	A	.....	Require replacement.
Tension out of specification .....	B	.....	Require adjustment or replacement.
Teeth missing .....	A	.....	Require replacement.

- (1) - Inspect belt tensioners, pulleys, and cover.
  - (2) - Determine cause of incorrect alignment and require repair.
  - (3) - CAUTION: Internal engine damage may result from timing belt damage/failure.
  - (4) - Determine cause of noise and suggest repair.
- AA

TIMING COVERS

See the following:

- ENGINE COVERS
- GASKETS
- GROMMETS (VALVE COVER)

TORQUE STRUTS

TORQUE STRUT INSPECTION

AA

Condition	Code		Procedure
Attaching hardware broken .....	A	..	Require repair or replacement

of hardware.

Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware not functioning .....	A	...	Require repair or replacement of hardware.
Binding .....	A	.....	Require replacement.
Body dented .....	A	.....	(1) Further inspection required.
Body punctured .....	A	.....	Require replacement.
Bushing deteriorated, affecting performance ..	A	.....	Require replacement.
Bushing deteriorated, not affecting performance ..	..	.....	No service suggested or required.
Bushings missing .....	C	.....	Require replacement.
Bushings separated from mounting eye .....	1	.....	Suggest replacement.
Damping (none) .....	A	.....	Require replacement.
Leaking oil, enough for fluid to be running down the body .....	A	.....	Require replacement.
Missing .....	C	.....	Require replacement.
Noisy .....	2	.....	(2) Further inspection required.
Piston rod bent .....	A	.....	Require replacement.
Piston rod broken .....	A	.....	Require replacement.
Seized .....	A	.....	Require replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.

- (1) - Require replacement of units where dents restrict strut piston rod movement. If dents don't restrict movement, no service is suggested or required.
- (2) - If noise is isolated to shock or strut, suggest replacement.
- AA

TRANSMISSION RANGE SWITCHES

TRANSMISSION RANGE SWITCH INSPECTION

AA

Condition	Code		Procedure
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware threads damaged .....	A	...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	...	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Contaminated .....	A	.....	(2) Require repair or replacement.
Inoperative .....	B	.....	(3) Require repair or

					replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.		
Missing .....	C	.....	Require replacement.		
Resistance out of specification .....	B	..	Require repair or replacement.		
Terminal broken .....	A	..	Require repair or replacement.		
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.		
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.		
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.		
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.		
Terminal loose, affecting performance .....	B	..	Require repair or replacement.		
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.		
Threads damaged .....	A	..	Require repair or replacement.		
Threads stripped (threads missing) .....	A	.....	Require replacement.		
Wire lead conductors exposed .....	B	..	Require repair or replacement.		
Wire lead corroded .....	A	..	Require repair or replacement.		
Wire lead open .....	A	..	Require repair or replacement.		
Wire lead shorted .....	A	..	Require repair or replacement.		

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

TUBE CLAMPS

See HOSE AND TUBE COUPLERS, CONNECTORS AND CLAMPS.

TUBE CONNECTORS

See HOSE AND TUBE COUPLERS, CONNECTORS AND CLAMPS.

TUBE COUPLERS

See HOSE AND TUBE COUPLERS, CONNECTORS AND CLAMPS.

TUBES

See HOSES AND TUBES (FUEL LINES, RADIATOR, BY PASS, HEATER, RECOVERY TANK AND OIL COOLERS).

TURBO CHARGERS

TURBO CHARGER INSPECTION

AA

Condition	Code	Procedure
-----------	------	-----------

Attaching hardware broken .....	A	... Require repair or replacement
---------------------------------	---	-----------------------------------

of hardware.

Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware not functioning .....	A	...	Require repair or replacement of hardware.
Boost pressure incorrect .....	A	.....	(1) Require repair or replacement.
Leaking .....	A	..	Require repair or replacement.
Noisy .....	2	..	Suggest repair or replacement.
Oil seal (internal) leaking .....	A	..	Require repair or replacement.
Vibrates .....	A	..	Require repair or replacement.

(1) - Boost pressure problems may be caused by other systems or components.

AA

VACUUM CONNECTIONS

See VACUUM HOSES, TUBES AND CONNECTIONS (NON-METALLIC).

VACUUM HOSES, TUBES AND CONNECTIONS (NON-METALLIC)

VACUUM HOSE, TUBE AND CONNECTION (NON-METALLIC) INSPECTION

AA

Condition	Code		Procedure
Leaking .....	A	..	Require repair or replacement.
Melted .....	A	.....	Require replacement.
Missing .....	C	.....	Require replacement.
Oil-soaked (spongy) .....	1	.....	Suggest replacement.
Restricted .....	A	..	Require repair or replacement.
Surface cracks (dry-rotted) .....	1	.....	Suggest replacement.

AA

VACUUM REGULATOR SOLENOIDS

VACUUM REGULATOR SOLENOID INSPECTION

AA

Condition	Code		Procedure
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware threads damaged .....	A	...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	...	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Contaminated .....	A	.....	(2) Require repair or replacement.
Inoperative .....	B	.....	(3) Require repair or

				replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.	
Missing .....	C	.....	Require replacement.	
Resistance out of specification .....	B	..	Require repair or replacement.	
Restricted, affecting performance .....	A	..	Require repair or replacement.	
Terminal broken .....	A	..	Require repair or replacement.	
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.	
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.	
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.	
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.	
Terminal loose, affecting performance .....	B	..	Require repair or replacement.	
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.	
Threads damaged .....	A	..	Require repair or replacement.	
Threads stripped (threads missing) .....	A	.....	Require replacement.	
Wire lead conductors exposed .....	B	..	Require repair or replacement.	
Wire lead corroded .....	A	..	Require repair or replacement.	
Wire lead open .....	A	..	Require repair or replacement.	
Wire lead shorted .....	A	..	Require repair or replacement.	

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

VACUUM TUBES

See VACUUM HOSES, TUBES AND CONNECTIONS (NON-METALLIC).

VALVE COVERS

See the following:

- ENGINE COVERS
- GASKETS
- GROMMETS (VALVE COVER)

VEHICLE SPEED SENSORS

VEHICLE SPEED SENSOR INSPECTION

AA

Condition	Code	Procedure
Attaching hardware missing .....	C	..... Require replacement of hardware.
Attaching hardware threads damaged .....	A	... Require repair or replacement

of hardware.

Attaching hardware threads stripped (threads missing) .....	A	...	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Contaminated .....	A	.....	(2) Require repair or replacement.
Inoperative .....	B	.....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

VOLUME AIR FLOW SENSORS

VOLUME AIR FLOW SENSOR INSPECTION

AA

Condition	Code		Procedure
Attaching hardware missing .....	C	.....	Require replacement of hardware.
Attaching hardware threads damaged .....	A	...	Require repair or replacement

of hardware.

Attaching hardware threads stripped (threads missing) .....	A	...	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Contaminated .....	A	.....	(2) Require repair or replacement.
Inoperative .....	B	.....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.
Restricted, affecting performance .....	A	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

WASTE GATE CONTROL SOLENOIDS

WASTE GATE CONTROL SOLENOID INSPECTION

AA

Condition	Code	Procedure
-----------	------	-----------

Attaching hardware missing .....	C	.....	Require replacement of hardware.
----------------------------------	---	-------	----------------------------------

Attaching hardware threads damaged .....	A	...	Require repair or replacement of hardware.
Attaching hardware threads stripped (threads missing) .....	A	...	Require repair or replacement of hardware.
Connector broken .....	A	..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A	..	Require repair or replacement.
Connector melted .....	A	.....	(1) Require repair or replacement.
Connector missing .....	C	.....	Require replacement.
Contaminated .....	A	.....	(2) Require repair or replacement.
Inoperative .....	B	.....	(3) Require repair or replacement. Further inspection required.
Leaking .....	A	..	Require repair or replacement.
Missing .....	C	.....	Require replacement.
Resistance out of specification .....	B	..	Require repair or replacement.
Restricted, affecting performance .....	A	..	Require repair or replacement.
Terminal broken .....	A	..	Require repair or replacement.
Terminal burned, affecting performance .....	A	.....	(1) Require repair or replacement.
Terminal burned, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal corroded, affecting performance ..	A	..	Require repair or replacement.
Terminal corroded, not affecting performance ..	2	..	Suggest repair or replacement.
Terminal loose, affecting performance .....	B	..	Require repair or replacement.
Terminal loose, not affecting performance ..	1	..	Suggest repair or replacement.
Threads damaged .....	A	..	Require repair or replacement.
Threads stripped (threads missing) .....	A	.....	Require replacement.
Wire lead conductors exposed .....	B	..	Require repair or replacement.
Wire lead corroded .....	A	..	Require repair or replacement.
Wire lead open .....	A	..	Require repair or replacement.
Wire lead shorted .....	A	..	Require repair or replacement.

- (1) - Determine cause and correct prior to repair or replacement of part.
- (2) - Determine source of contamination, such as engine coolant, fuel, metal particles, or water. Require repair or replacement.
- (3) - Inoperative includes intermittent operation or out of OEM specification. Some components may be serviceable; check for accepted cleaning procedure.

AA

WASTE GATES AND BOOST CONTROL MECHANISMS

WASTE GATE AND BOOST CONTROL MECHANISM INSPECTION

AA

Condition	Code	Procedure
-----------	------	-----------

Boost pressure

incorrect ..... A ..... (1) Require repair or replacement. Further inspection required.  
 Leaking ..... A .. Require repair or replacement.

(1) - Incorrect boost pressure includes intermittent operation or out of OEM specification.

AA

WATER PUMPS (ELECTRIC)

WATER PUMP (ELECTRIC) INSPECTION

AA

Condition	Code	Procedure
Attaching hardware broken	A ...	Require repair or replacement of hardware.
Attaching hardware missing	C .....	Require replacement of hardware.
Attaching hardware not functioning	A ...	Require repair or replacement of hardware.
Connector broken	A ..	Require repair or replacement.
Connector (Weatherpack type) leaking	A ..	Require repair or replacement.
Connector melted	A .....	(1) Require repair or replacement.
Connector missing	C .....	Require replacement.
Inoperative	A .....	(2) Require replacement.
Leaking	A ..	Require repair or replacement.
Missing	C .....	Require replacement.
Noisy	2 .....	Suggest replacement.
Rotation incorrect for application	B ..	Require repair or replacement.
Terminal broken	A ..	Require repair or replacement.
Terminal burned, affecting performance	A .....	(1) Require repair or replacement.
Terminal burned, not affecting performance	.. 2 ..	Suggest repair or replacement.
Terminal corroded, affecting performance	.. A ..	Require repair or replacement.
Terminal corroded, not affecting performance	.. 2 ..	Suggest repair or replacement.
Terminal loose, affecting performance	B ..	Require repair or replacement.
Terminal loose, not affecting performance	.. 1 ..	Suggest repair or replacement.
Vibration	1 .....	Suggest replacement.
Wire lead conductors exposed	B ..	Require repair or replacement.
Wire lead corroded	A ..	Require repair or replacement.
Wire lead open	A ..	Require repair or replacement.
Wire lead shorted	A ..	Require repair or replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

(2) - Check fan motor/controls. Inoperative includes intermittent operation or out of OEM specification.

AA

WATER PUMPS (NON-ELECTRIC)

WATER PUMP (NON-ELECTRIC) INSPECTION

AA

Condition	Code	Procedure
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware corroded .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Corrosion (internal) is excessive, affecting performance .....	A .....	Require replacement.
Corrosion (internal) is excessive, not affecting performance .....	2 .	Suggest cooling system service.
Inoperative .....	A .....	(1) Require replacement.
Leaking .....	A .....	Require replacement.
Noisy .....	A .....	Require replacement.
Rotation incorrect for application .....	B ..	Require repair or replacement.
Shaft bent .....	A .....	Require replacement.

(1) - Inoperative includes intermittent operation or out of OEM specification.

AA

WIRING HARNESSSES AND CONNECTORS

WIRING HARNESS AND CONNECTOR INSPECTION

AA

Condition	Code	Procedure
Application incorrect ...	B ..	Require repair or replacement.
Attaching hardware broken .....	A ...	Require repair or replacement of hardware.
Attaching hardware missing .....	C .....	Require replacement of hardware.
Attaching hardware not functioning .....	A ...	Require repair or replacement of hardware.
Connector broken .....	A ..	Require repair or replacement.
Connector (Weatherpack type) leaking .....	A ..	Require repair or replacement.
Connector melted .....	A .....	(1) Require repair or replacement.
Connector missing .....	C .....	Require replacement.
Insulation damaged, conductors exposed .....	A ..	Require repair or replacement.
Insulation damaged, conductors not exposed .	1 .....	Suggest replacement.
Open .....	A ..	Require repair or replacement.
Protective shield (conduit) melted .....	2 .....	(1) Suggest repair or

replacement.

- Protective shield  
(conduit) missing ..... 2 .. Suggest repair or replacement.
- Resistance (voltage drop)  
out of specification ... A .. Require repair or replacement.
- Routed incorrectly ..... B ..... Require repair.
- Secured incorrectly ..... B ..... Require repair.
- Shorted ..... A .. Require repair or replacement.
- Terminal broken ..... A .. Require repair or replacement.
- Terminal burned, affecting  
performance ..... A ..... (1) Require repair or  
replacement.
- Terminal burned, not  
affecting performance .. 2 .. Suggest repair or replacement.
- Terminal corroded,  
affecting performance .. A .. Require repair or replacement.
- Terminal corroded, not  
affecting performance .. 2 .. Suggest repair or replacement.
- Terminal loose, affecting  
performance ..... B .. Require repair or replacement.
- Terminal loose, not  
affecting performance .. 1 .. Suggest repair or replacement.
- Voltage drop out of  
specification ..... A .. Require repair or replacement.

(1) - Determine cause and correct prior to repair or replacement of part.

AA

END OF ARTICLE