

You can search this page by using your browser's EDIT --> FIND (on this Page) Commands

The flow rates shown are at 100% duty cycle (static) and are for gasoline.

Although we do show some rating pressure most injectors are designed to operate 36.25 PSI / 2.5 BAR or 43.5 PSI / 3 BAR - Chrysler and Porsche some times use 55 PSI / 3.7 BAR

Remember this is a pressure differential across the injector, this becomes important in Turbo/Supercharged (SC) engines, where you need to use a regulator that increases fuel pressure as boost increases.

Injectors are rated at "X" psi, but most will work and flow more fuel at a higher pressure.

There is a calculator on my [Home Page](#) to convert flow numbers from one fuel pressure differential to another.

Fuel pump flow decreases as the pressure goes higher, so make sure your fuel pump has enough flow at the pressure you raise it to.

Estimated Horsepower figures are calculated at 80% duty cycle and 95% duty cycle also based on BSFC (Brake Specific Fuel Consumption).

.36 BSFC - Turbocharged Intercooled Diesel

.38 BSFC - Turbocharged Non-Intercooled Diesel

.42 BSFC - Race Engine or Older Diesel Engine *

.47 BSFC - Hi Performance Engine *

.52 BSFC - Modern Stock Engine or Light Modifications Engine *

.57 BSFC - Supercharged (SC) / Turbocharged Non Intercooled Engine


* - These include N/A engines or Supercharged/Turbocharged Intercooled Engines.

Since only one BSFC is now listed in the table Please use the [Peak Horse Power per Injector Table](#) which is at the bottom of this page.

Electronic fuel injectors come in two types Low (1-5 ohms) and High (12-16 ohms) Resistance (Impedance). NOTE this can be measured between the 2 pins with a multi-meter.

Like with other engine parts Bigger is not always better.

These numbers were compiled from various magazines, web sites, and manufactures catalogs, and **should only be used as a Guide**. Always check with the Manufacturer.

 Please send comments about this table or suggestions for updates.

I would appreciate it if you find wrong data in the table if you would send me a message.

Check out the [Screenshots](#) from [CARFOR](#) our Automotive Performance Software.

[\[Accel\]](#) [\[Bendix\]](#) [\[Bosch\]](#) [\[Bosch - Ford\]](#) [\[Chrysler - Mopar\]](#) [\[Delphi\]](#) [\[Edelbrock\]](#) [\[Ford\]](#) [\[Holley\]](#) [\[Honda - Acura\]](#) [\[Lucas\]](#) [\[MSD\]](#)
[\[Nippon Denso\]](#) [\[Nissan - Infiniti\]](#) [\[RC Engineering\]](#) [\[Rochester / GM\]](#) [\[Siemens Deka\]](#) [\[Subaru\]](#) [\[Toyota - Lexus\]](#) [\[Trick Flow\]](#)
[\[Weber\]](#) [Peak Horse Power per Injector Table](#)

Electronic Fuel Injector (EFI) Flow Data Table

Accel COPYRIGHT © 2002-2011 Stan Weiss — World Wide Enterprises													
Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Drive Circuit	Impedance	Application
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%				
150X14	14.0	147.1	105.8	43.5	3.0	14	147.1	21.5	25.6	-	12v Saturated	High	-
150X15	15.0	157.7	113.4	43.5	3.0	15	157.7	23.1	27.4	-	-	High	-
150X17	17.0	178.7	128.5	43.5	3.0	17	178.7	26.2	31.1	-	12v Saturated	High	-
150X19	19.0	199.7	143.6	43.5	3.0	19	199.7	29.2	34.7	-	-	High	-
150X21	21.0	220.7	158.8	43.5	3.0	21	220.7	32.3	38.4	-	12v Saturated	High	-
150X23	23.0	241.7	173.9	43.5	3.0	23	241.7	35.4	42	-	-	High	-
150X24	24.0	252.2	181.4	43.5	3.0	24	252.2	36.9	43.8	-	-	High	-
150X26	26.0	273.3	196.6	43.5	3.0	26	273.3	40	47.5	-	12v Saturated	High	-
150X30	30.0	315.3	226.8	43.5	3.0	30	315.3	46.2	54.8	-	12v Saturated	High	-
150X32	32.0	336.3	241.9	43.5	3.0	32	336.3	49.2	58.5	-	12v Saturated	High	-
150X36	36.0	378.4	272.2	43.5	3.0	36	378.4	55.4	65.8	-	12v Saturated	High	-
150X40	40.0	420.4	302.4	43.5	3.0	40	420.4	61.5	73.1	-	12v Saturated	High	-
150X44	44.0	462.4	332.6	43.5	3.0	44	462.4	67.7	80.4	-	12v	High	-

150X48	48.0	504.5	362.9	43.5	3.0	48	504.5	73.8	87.7	-	Saturated 12v Saturated	High	-
151195	18.55	195	140.2	43.5	3.0	18.55	195	28.5	33.9	-	-	Low	-
151255	24.25	254.9	183.3	43.5	3.0	24.25	254.9	37.3	44.3	-	4\1A Peak and Hold	Low	Accord Prelude Civic CRX, SOHC 16v, DOHC 16v
151370	35.2	370	266.1	43.5	3.0	35.2	370	54.2	64.3	-	4\1A Peak and Hold	Low	Acura Honda NSX Prelude 2.2l 3.0l
153195	18.55	195	140.2	43.5	3.0	18.55	195	28.5	33.9	Top	-	High	Honda
74120	120.0	1261	907.2	43.5	3.0	120	1261	184	219	Top	12v Saturated	Low	-
74160	160.0	1681	1209	43.5	3.0	160	1681	246	292	-	-	Low	-
74607	83.0	872.3	627.5	43.5	3.0	83	872.3	127	151	-	-	Low	-
74612	55.0	578.1	415.8	43.5	3.0	55	578.1	84.6	100	-	12v Saturated	Low	-
74615L	37.0	388.9	279.7	43.5	3.0	37	388.9	56.9	67.6	-	-	Low	-
74616	72.0	756.7	544.3	43.5	3.0	72	756.7	110	131	-	-	Low	-
74618	96.0	1009	725.7	43.5	3.0	96	1009	147	175	-	-	Low	-
74620l	62.0	651.6	468.7	43.5	3.0	62	651.6	95.4	113	-	-	High	Ford 3.9l, v8-4.6l, v8-5.4l
74620s	62.0	651.6	468.7	43.5	3.0	62	651.6	95.4	113	-	-	High	Chevy 4.8l, 5.3l, 5.7l, 6.0l, 6.2l, 7.0l

X in the Part Number = 1, or 8 and is equal to the number of injectors that are in the kit.

Bendix

COPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Impedance	Application
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%			
1181247	38.0	399.4	287.3	-	-	-	-	58.5	69.4	-	Low	Cadillac v8-8.2l - Feedback Gary Kosier
1181281	38.0	399.4	287.3	-	-	-	-	58.5	69.4	-	Low	Cadillac v8-5.7l, v8-7.0l
Red 25500139	82.0	861.8	619.9	45.0	3.1	80.62	847.3	126	149	-	Low	-
White - Alcohol / Nethanol	180.0	1891	1360	45.0	3.1	176.9	1860	276	328	-	Low	-

A "Y" in the n-H Colnum means that the data came from Bosch and the injector was flowed using n-Heptane

Bosch

COPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Impedance	Application	n-H
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%				
0-280-150-001	25.2	264.9	190.5	43.5	3.0	25.2	264.9	38.8	46	-	-	M B 3.5l, Saab 1.7l	-
0-280-150-002	25.2	264.9	190.5	43.5	3.0	25.2	264.9	38.8	46	-	-	-	-
0-280-150-003	36.15	379.9	273.3	43.5	3.0	36.15	379.9	55.6	66	-	-	-	-
0-280-150-007	25.2	264.9	190.5	43.5	3.0	25.2	264.9	38.8	46	-	Low	VW 1.6l, 1.7l	-
0-280-150-008	25.2	264.9	190.5	43.5	3.0	25.2	264.9	38.8	46	EV1	Low	-	-
0-280-150-009	25.2	264.9	190.5	43.5	3.0	25.2	264.9	38.8	46	-	Low	Porsche 914 1.7l	-
0-280-150-010	-	-	-	-	-	-	-	-	-	-	Low	-	-
0-280-150-014	-	-	-	-	-	-	-	-	-	-	-	Jaguar v12-5.3l	-
0-280-150-015	36.15	379.9	273.3	43.5	3.0	36.15	379.9	55.6	66	-	-	-	-
0-280-150-													

016	-	-	-	-	-	-	-	-	-	-	Top	Low	Renault 4-1.6	-
0-280-150-019	-	-	-	-	-	-	-	-	-	-	-	Low	Porsche 4-1.8l, 4-2.0l	-
0-280-150-023	33.5	352.1	253.3	43.5	3.0	33.5	352.1	51.5	61.2	-	-	High	Jaguar V12, Saab Turbo 99-2004 tronic7 - Feedback - Jak Stoll	-
0-280-150-024	36.15	379.9	273.3	43.5	3.0	36.15	379.9	55.6	66	-	-	Low	M B, Volvo	-
0-280-150-026	36.15	379.9	273.3	43.5	3.0	36.15	379.9	55.6	66	-	-	-	M B, Volvo	-
0-280-150-030	-	-	-	-	-	-	-	-	-	-	-	Low	-	-
0-280-150-034	-	-	-	43.5	-	-	-	-	-	-	-	Low	M B v8-3.5l, SAAB 1.7l	-
0-280-150-035	30.5	320.6	230.6	29	2.0	37.35	392.6	46.9	55.7	-	-	Low	M B 6-2.8l, Jaguar v12-5.3l	-
0-280-150-036	36.15	379.9	273.3	43.5	3.0	36.15	379.9	55.6	66	EV1	-	Low	M B v8-4.5l, Volvo 2.0l, 6-3.0l, Mercury Outboard	-
0-280-150-036	48.19	-	364.3	43.5	3.0	-	-	-	-	EV1	-	Low	-	Y
0-280-150-038	-	-	-	-	-	-	-	-	-	-	-	Low	Porsche 4-1.8l, 2.0l	-
0-280-150-039	-	-	-	-	-	-	-	-	-	-	-	Low	-	-
0-280-150-040	-	-	-	-	-	-	-	-	-	-	-	Low	-	-
0-280-150-041	45.7	480.3	345.5	43.5	3.0	45.7	480.3	70.3	83.5	-	-	Low	M B, Cadillac	-
0-280-150-043	36.15	379.9	273.3	43.5	3.0	36.15	379.9	55.6	66	-	-	-	BMW 6-3.0l, Citroen 4-2.1l, 4-2.3l, M B v8-4.5l, Volvo 4-2.0l, 6-3.0l	-
0-280-150-044	32.15	337.9	243	-	-	-	-	49.5	58.7	-	-	Low	M B v8-3.5l, VW 1.6l, 4-1.7l	-
0-280-150-045	38.1	400.4	288	-	-	-	-	58.6	69.6	-	-	Low	M B 6-2.5l, 6-2.9l, Jaguar v12-5.3l, Saab 4-2.0l	-
0-280-150-053	-	-	-	-	-	-	-	-	-	-	-	Low	Ford	-
0-280-150-055	-	-	-	-	-	-	-	-	-	-	-	Low	Ford	-
0-280-150-057	-	-	-	-	-	-	-	-	-	-	-	Low	Ford	-
0-280-150-063	-	-	-	-	-	-	-	-	-	-	-	Low	Chrysler	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle						Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H	
0-280-150-065	-	-	-	-	-	-	-	-	-	-	Low	Ford v6-3.2l, 6-3.9l	-	
0-280-150-067	-	-	-	-	-	-	-	-	-	-	Low	Chrysler	-	
0-280-150-069	-	-	-	-	-	-	-	-	-	-	Low	Audi, VW	-	
0-280-150-070	-	-	-	14.5	-	-	-	-	-	-	High	Peugeot	-	
0-280-150-071	-	-	-	14.5	-	-	-	-	-	-	Low	Audi, VW 1.8l	-	
0-280-150-100	17.6	185	133.1	43.5	3.0	17.6	185	27.1	32.2	Top	Low	-	-	
0-280-150-101	-	-	-	-	-	-	-	-	-	-	Low	-	-	
0-280-150-102	-	-	-	-	-	-	-	-	-	-	Low	-	-	
0-280-150-103	-	-	-	-	-	-	-	-	-	-	Low	-	-	
0-280-150-104	-	-	-	-	-	-	-	-	-	Top	Low	-	-	
0-280-150-105	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	Top	Low	Alfa v6-2.5l, v6-3.0l, Jaguar XJS, Opel 4-1.9l, Porsche 4-2.0l, Renault 4-1.6l, Range Rover v8-3.5l, Triumph 2.0l, v8-3.5l	-	
0-280-150-														

106											Top	Low		
0-280-150-107	-	-	-	-	-	-	-	-	-	-	-	Low	-	-
0-280-150-108	-	-	-	-	-	-	-	-	-	-	-	Low	-	-
0-280-150-109	-	-	-	-	-	-	-	-	-	-	-	Low	-	-
0-280-150-112	18.1	190.2	136.8	-	-	-	-	27.8	33.1	-	-	Low	Porsche 4-1.8l, VW 1.6l	-
0-280-150-114	18.1	190.2	136.8	-	-	-	-	27.8	33.1	Top	-	Low	VW 4-1.8l, 4-2.0l	-
0-280-150-116	18.1	190.2	136.8	-	-	-	-	27.8	33.1	Top	-	Low	VW 4-1.6l	-
0-280-150-117	18.1	190.2	136.8	-	-	-	-	27.8	33.1	-	-	Low	-	-
0-280-150-118	18.1	190.2	136.8	-	-	-	-	27.8	33.1	-	-	Low	-	-
0-280-150-119	18.1	190.2	136.8	-	-	-	-	27.8	33.1	-	-	Low	-	-
0-280-150-121	16.95	178.1	128.1	43.5	3.0	16.95	178.1	26.1	31	Top	-	Low	Alfa 2.0l, Fiat 2.0l, Lancia 4-2.0l, Pininfarina 4-2.0l	-
0-280-150-123	18.2	191.3	137.6	-	-	-	-	28	33.3	Top	-	Low	Bertone 4-1.5l, Fiat 4-1.5l, Triumph 2.0l, v8-3.5l	-
0-280-150-124	-	-	-	-	-	-	-	-	-	Top	-	Low	Triumph 4-2.0l	-
0-280-150-125	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	Top	-	Low	Renault 4-1.6l, 4-1.6l Turbo, 4-1.7l, Triumph 2.0l	-
0-280-150-126	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	EV1	-	Low	BMW 6-2.7l, 3.0l, Renault 4-1.7l, 4-2.2l, Eagle 6-3.0l	-
0-280-150-127	-	-	-	-	-	-	-	-	-	Top	-	Low	Alfa 2.0l, Fiat 2.0l, Lancia 4-2.0l	-
0-280-150-128	15.9	167.1	120.2	43.5	3.0	15.9	167.1	24.5	29	Top	-	Low	Alfa 2.0l, Fiat 2.0l, Lancia 4-2.0l	-
0-280-150-129	18.2	191.3	137.6	-	-	-	-	28	33.3	-	-	Low	Jaguar 6-3.2l, 6-3.6l	-
0-280-150-130	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	Top	-	Low	Renault v6-2.8l	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle						Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance		Application	n-H
0-280-150-133	18.2	191.3	137.6	-	-	-	-	28	33.3	-	-	Low	Jaguar 6-4.0l	-
0-280-150-135	18.2	191.3	137.6	-	-	-	-	28	33.3	EV1	-	Low	Nissan 4-2.0l	-
0-280-150-135	19.5	-	147.4	43.5	3.0	-	-	-	-	EV1	-	Low	Nissan 4-2.0l	Y
0-280-150-136	18.2	191.3	137.6	-	-	-	-	28	33.3	-	-	Low	-	-
0-280-150-150	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	-	-	Rover v8-3.5l	-
0-280-150-151	22.9	240.7	173.1	29	2.0	28.05	294.8	35.2	41.8	Top	-	Low	BMW 6-3.0l, 6-3.2l, Jaguar 6-4.2l	-
0-280-150-151	29.0	304.8	219.2	43.5	3.0	29	304.8	44.6	53	Top	-	Low	BMW 6-3.0l, Volvo	-
0-280-150-152	22.5	236.5	170.1	-	-	-	-	34.6	41.1	-	-	Low	Alfa Turbo, BMW 6-2.8l, 6-3.2l, Porsche	-
0-280-150-153	22.5	236.5	170.1	43.5	3.0	22.5	236.5	34.6	41.1	EV1	-	Low	-	-
0-280-150-154	22.5	236.5	170.1	43.5	3.0	22.5	236.5	34.6	41.1	-	-	Low	Porsche 8-4.6l	-
0-280-150-157	20.4	214.4	154.2	36.25	2.5	22.35	234.9	31.4	37.3	Top	-	Low	Jaguar 3.6l, 6-4.2l	-
0-280-150-157	22.83	239.9	172.6	43.5	3.0	22.83	239.9	35.1	41.7	Top	-	Low	Jaguar 3.6l, 6-4.2l	-
0-280-150-158	21.8	229.1	164.8	36.25	2.5	23.88	251	33.5	39.8	EV1	-	Low	Porsche 4-2.5l, 4-2.7l, 6-3.2l	y
0-280-150-158	22.83	239.9	172.6	43.5	3.0	22.83	239.9	35.1	41.7	EV1	-	Low	Porsche 4-2.5l, 4-2.7l, 6-3.2l	-
0-280-150-159	24.35	255.9	184.1	-	-	-	-	37.5	44.5	EV1	-	Low	Ford 2.3l	-
0-280-150-160	17.6	185	133.1	-	-	-	-	27.1	32.2	EV1	-	Low	Eagle v6-3.0l, Ford 2.3l	-

0-280-150-160	19.0	199.7	143.6	43.5	3.0	19	199.7	29.2	34.7	EV1	Low	-	-
0-280-150-161	17.2	180.8	130	43.5	3.0	17.2	180.8	26.5	31.4	Top	Low	-	-
0-280-150-162	17.2	180.8	130	43.5	3.0	17.2	180.8	26.5	31.4	Top	Low	-	-
0-280-150-163	17.2	180.8	130	43.5	3.0	17.2	180.8	26.5	31.4	Top	Low	Jaguar v12-5.3l	-
0-280-150-164	17.2	180.8	130	43.5	3.0	17.2	180.8	26.5	31.4	Top	Low	Jaguar v12-5.3l	-
0-280-150-165	22.2	233.3	167.8	43.5	3.0	22.2	233.3	34.2	40.6	-	Low	Jaguar 3.6l, 6-4.0l	-
0-280-150-166	20.3	213.4	153.5	43.5	3.0	20.3	213.4	31.2	37.1	EV1	Low	Jaguar 6-4.2l	-
0-280-150-166	24.56	-	185.7	43.5	3.0	-	-	-	-	EV1	Low	-	Y
0-280-150-200	28.6	300.6	216.2	43.5	3.0	28.6	300.6	44	52.3	Top	Low	BMW, Peugeot	-
0-280-150-201	22.5	236.5	170.1	36.25	2.5	24.65	259	34.6	41.1	EV1	Low	BMW 4-1.0l, 4-2.3l, 6-3.2l, 6-3.4l, 6-3.5l, Chrysler 2.2l, 2.5l, Pontiac 1.8l, Porsche 4-2.5l	y
0-280-150-201	24.55	258	185.6	43.5	3.0	24.55	258	37.8	44.9	EV1	Low	BMW 4-1.0l, 4-2.3l, 6-3.2l, 6-3.4l, 6-3.5l, Chrysler 2.2l, 2.5l, Pontiac 1.8l, Porsche 4-2.5l	y
0-280-150-203	17.6	185	133.1	36.25	2.5	19.28	202.6	27.1	32.2	EV1	High	BMW 6-2.8l, 6-3.4l, Fiat 4-2.0l, Ford 6-4.1l, v8-5.0l, Holden 6-3.3l	-
0-280-150-204	16.0	168.2	121	36.25	2.5	17.53	184.2	24.6	29.2	EV1	High	Volvo 4-2.1l	-
0-280-150-205	16.2	170.3	122.5	36.25	2.5	17.75	186.5	24.9	29.6	-	High	Holden 4-1.8l, MB	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-280-150-206	16.0	168.2	121	36.25	2.5	17.53	184.2	24.6	29.2	EV1	High	VW 1.9l, 4-2.1l	-
0-280-150-207	16.3	171.3	123.2	36.25	2.5	17.86	187.7	25.1	29.8	EV1	High	VW	-
0-280-150-208	12.65	133	95.68	36.25	2.5	13.86	145.6	19.5	23.1	EV1	High	BMW 6-2.0l, 6-2.3l, Renault 4-1.4l	-
0-280-150-208	13.7	144	103.6	39.15	2.7	14.44	151.8	21.1	25	EV1	High	Renault 1.4l	-
0-280-150-209	16.0	168.2	121	36.25	2.5	17.53	184.2	24.6	29.2	EV1	Low	Range Rover 8-3.5l, Volvo 4-2.3l	-
0-280-150-210	12.85	135.1	97.19	36.25	2.5	14.08	147.9	19.8	23.5	EV1	High	BMW Motorcycle	-
0-280-150-211	14.04	147.6	106.1	43.5	3.0	14.04	147.6	21.6	25.7	EV1	High	BMW 1.8l, Renault 4-2.2l	-
0-280-150-213	33.0	346.8	249.5	43.5	3.0	33	346.8	50.8	60.3	EV1	High	Ford 1.8l, 2.3l, Porsche	-
0-280-150-214	17.9	188.1	135.3	43.5	3.0	17.9	188.1	27.5	32.7	-	High	Fiat 4-2.0l	-
0-280-150-215	20.4	214.4	154.2	36.25	2.5	22.35	234.9	31.4	37.3	EV1	High	Ford 6-4.1l	-
0-280-150-215	24.78	-	187.3	43.5	3.0	-	-	-	-	EV1	High	-	Y
0-280-150-216	20.4	214.4	154.2	36.25	2.5	22.35	234.9	31.4	37.3	-	High	-	-
0-280-150-217	16.0	168.2	121	36.25	2.5	17.53	184.2	24.6	29.2	EV1	High	Buick v6-3.8l	-
0-280-150-218	29.7	312.1	224.5	45	3.1	29.2	306.9	45.7	54.3	EV1	High	Buick GN v6-3.8l Turbo	-
0-280-150-219	16.0	168.2	121	36.25	2.5	17.53	184.2	24.6	29.2	-	High	Ford 4-2.0l	-
0-280-150-220	14.1	148.2	106.6	43.5	3.0	14.1	148.2	21.7	25.8	EV1	High	Buick v6-3.0l	-
0-280-150-221	14.1	148.2	106.6	43.5	3.0	14.1	148.2	21.7	25.8	EV1	High	Buick v6-3.0l	-
0-280-150-222	16.0	168.2	121	36.25	2.5	17.53	184.2	24.6	29.2	EV1	High	-	-
0-280-150-223	21.35	224.4	161.4	36	2.48	23.47	246.7	32.8	39	EV1	High	Vette v8-5.7l	-

0-280-150-224	-	-	-	-	-	-	-	-	-	-	-	High	-	-
0-280-150-225	-	-	-	-	-	-	-	-	-	-	-	High	-	-
0-280-150-226	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	High	Peugeot 4-2.2l	-	
0-280-150-227	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	EV1	High	Range Rover 8-3.5l	-	
0-280-150-228	-	-	-	-	-	-	-	-	-	EV1	High	Lancia 4-2.0l	-	
0-280-150-229	-	-	-	-	-	-	-	-	-	EV1	High	Ford 1.9l, 2.3l, v6-3.0l, v6-3.8l, v8-5.0l	-	
0-280-150-230	17.5	183.9	132.3	-	-	-	-	26.9	32	-	High	-	-	
0-280-150-231	14.1	148.2	106.6	-	-	-	-	21.7	25.8	EV1	High	Buick 3.0l	-	
0-280-150-232	-	-	-	-	-	-	-	-	-	-	High	Vette v8-5.7l	-	
0-280-150-233	14.1	148.2	106.6	-	-	-	-	21.7	25.8	EV1	High	Cadillac v8-4.1l	-	
0-280-150-234	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	High	-	-	
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle						Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H	
0-280-150-235	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	EV1	High	Buick v6-3.8l	-	
0-280-150-237	14.55	152.9	110	43.5	3.0	14.55	152.9	22.4	26.6	EV1	High	Buick v6-3.0l	-	
0-280-150-238	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	EV1	High	Chevy v8-5.0l	-	
0-280-150-239	21.35	224.4	161.4	36	2.48	23.47	246.7	32.8	39	EV1	High	Vette v8-5.7l	-	
0-280-150-252	24.75	260.1	187.1	-	-	-	-	38.1	45.2	-	High	Porsche v8-4.7l	-	
0-280-150-254	24.75	260.1	187.1	36.25	2.5	27.11	284.9	38.1	45.2	-	High	Citroen 4-2.5l - Feedback Mikael Westerberg	-	
0-280-150-255	24.35	255.9	184.1	-	-	-	-	37.5	44.5	-	High	Peugeot 4-2.5l	-	
0-280-150-257	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	High	-	-	
0-280-150-300	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	-	
0-280-150-302	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	-	
0-280-150-303	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	-	
0-280-150-306	49.5	520.2	374.2	43.5	3.0	49.5	520.2	76.2	90.4	-	Low	-	-	
0-280-150-309	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	-	
0-280-150-310	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	-	
0-280-150-314	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	-	
0-280-150-315	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	-	
0-280-150-317	-	-	-	-	-	-	-	-	-	-	Low	-	-	
0-280-150-318	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	-	
0-280-150-319	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	-	
0-280-150-320	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	-	
0-280-150-321	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	-	
0-280-150-322	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	-	
0-280-150-323	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	-	

0-280-150-324	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	-
0-280-150-325	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	-
0-280-150-326	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	-
0-280-150-327	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	-
0-280-150-334	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	-
0-280-150-335	28.6	300.6	216.2	43.5	3.0	28.6	300.6	44	52.3	-	-	Volvo 2.3l Turbo	-
0-280-150-351	71.0	746.2	536.8	43.5	3.0	71	746.2	109	129	-	Low	Chrysler 2.2l	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-280-150-352	25.7	270.1	194.3	43.5	3.0	25.7	270.1	39.5	47	EV1	Low	BMW 2.3l, 6-3.2l, 6-3.4l, Plymouth 4-2.2l, 4-2.5l, Pontiac 1.8l, Porsche 2.5l	-
0-280-150-353	-	-	-	-	-	-	-	-	-	EV1	Low	Ford 1.6l	-
0-280-150-355	37.0	388.9	279.7	-	-	-	-	56.9	67.6	-	Low	Volvo	-
0-280-150-355	28.6	300.6	216.2	43.5	3.0	28.6	300.6	44	52.3	-	Low	Volvo 4-2.3l	-
0-280-150-357	28.6	300.6	216.2	43.5	3.0	28.6	300.6	44	52.3	Top	Low	Volvo 4-2.3l Turbo	-
0-280-150-360	25.7	270.1	194.3	43.5	3.0	25.7	270.1	39.5	47	EV1	Low	BMW 2.3l, 6-3.2l, 6-3.4l, Plymouth 4-2.2l, 4-2.5l, Pontiac 1.8l, Porsche 2.5l	-
0-280-150-361	26.9	282.7	203.4	43.5	3.0	26.9	282.7	41.4	49.1	-	Low	-	-
0-280-150-362	25.7	270.1	194.3	43.5	3.0	25.7	270.1	39.5	47	EV1	Low	BMW 2.3l, 6-3.2l, 6-3.4l, Plymouth 4-2.2l, 4-2.5l, Pontiac 1.8l, Porsche 2.5l	-
0-280-150-363	71.0	746.2	536.8	43.5	3.0	71	746.2	109	129	EV1	Low	Plymouth 4-2.2l	-
0-280-150-363	63.47	-	479.8	43.5	3.0	-	-	-	-	EV1	Low	-	Y
0-280-150-364	25.7	270.1	194.3	43.5	3.0	25.7	270.1	39.5	47	EV1	Low	BMW 2.3l, 6-3.2l, 6-3.4l, Plymouth 4-2.2l, 4-2.5l, Pontiac 1.8l, Porsche 2.5l	-
0-280-150-365	25.7	270.1	194.3	43.5	3.0	25.7	270.1	39.5	47	-	Low	-	-
0-280-150-368	25.5	268	192.8	43.5	3.0	25.5	268	39.2	46.6	-	Low	-	-
0-280-150-369	25.5	268	192.8	43.5	3.0	25.5	268	39.2	46.6	-	Low	-	-
0-280-150-400	41.6	437.2	314.5	43.5	3.0	41.6	437.2	64	76	Top	Low	Ford 5.0l	-
0-280-150-400	46.0	483.5	347.8	-	-	-	-	70.8	84	Top	Low	Ford 5.0l	-
0-280-150-401	41.6	437.2	314.5	43.5	3.0	41.6	437.2	64	76	-	Low	Ford	-
0-280-150-402	32.15	337.9	243	43.5	3.0	32.15	337.9	49.5	58.7	Top	Low	Ford v6-3.8l	-
0-280-150-402	37.0	388.9	279.7	-	-	-	-	56.9	67.6	Top	Low	Ford v6-3.8l	-
0-280-150-403	47.86	503	361.8	43.5	3.0	47.86	503	73.6	87.4	EV1	Low	Ford 5.0l HO	-
0-280-150-403	53.28	-	402.8	43.5	3.0	-	-	-	-	EV1	Low	Ford 5.0l HO	Y
0-280-150-413	18.65	196	141	-	-	-	-	28.7	34.1	-	High	Opel	-
0-280-150-414	14.65	154	110.8	-	-	-	-	22.5	26.8	-	High	BMW 6-2.0l	-
0-280-150-415	18.1	190.2	136.8	50.75	3.5	16.76	176.1	27.8	33.1	Top	High	BMW 6-2.5l	-
0-280-150-416	14.25	149.8	107.7	-	-	-	-	21.9	26	-	High	Audi v8-3.6l, Ferrari	-
0-280-150-	14.25	149.8	107.7	-	-	-	-	21.9	26	-	High	-	-

Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Impedance	Application	n-H
417 0-280-150-418	25.0	262.8	189	-	-	-	-	38.5	45.7	-	High	Opel	-
0-280-150-419	18.9	198.6	142.9	-	-	-	-	29.1	34.5	-	High	Ferrari f12-4.9l	-
0-280-150-420	28.9	303.7	218.5	-	-	-	-	44.5	52.8	-	High	Holden 4-2.0l, Opel	-
0-280-150-421	18.25	191.8	138	-	-	-	-	28.1	33.3	-	High	Fiat	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
0-280-150-422	24.9	261.7	188.2	39.15	2.7	26.25	275.9	38.3	45.5	-	High	Fiat	-
0-280-150-423	18.65	196	141	-	-	-	-	28.7	34.1	-	High	Peugeot 4-2.0l	-
0-280-150-424	16.5	173.4	124.7	-	-	-	-	25.4	30.1	EV1	High	Audi v8-4.2l	-
0-280-150-425	16.5	173.4	124.7	-	-	-	-	25.4	30.1	-	High	-	-
0-280-150-427	22.95	241.2	173.5	-	-	-	-	35.3	41.9	-	High	Opel	-
0-280-150-428	18.65	196	141	-	-	-	-	28.7	34.1	-	High	Holden v6-2.5l, Opel, Saab v6-2.5l	-
0-280-150-429	18.65	196	141	-	-	-	-	28.7	34.1	-	High	Fiat	-
0-280-150-431	34.15	358.9	258.2	-	-	-	-	52.5	62.4	Top	High	Saab 4-2.0l Turbo, 4-2.3l Turbo	-
0-280-150-431	33.3	350	251.7	43.5	3.0	33.3	350	51.2	60.8	Top	High	-	-
0-280-150-432	22.85	240.2	172.7	-	-	-	-	35.2	41.7	Top	High	Saab 4-2.0l, 4-2.3l	-
0-280-150-432	23.8	250.1	179.9	43.5	3.0	23.8	250.1	36.6	43.5	Top	High	-	-
0-280-150-433	22.85	240.2	172.7	-	-	-	-	35.2	41.7	-	High	Hyundai	-
0-280-150-438	16.25	170.8	122.8	-	-	-	-	25	29.7	-	High	Toyota	-
0-280-150-439	16.0	168.2	121	-	-	-	-	24.6	29.2	-	High	Toyota	-
0-280-150-440	23.8	250.1	179.9	50.75	3.5	22.03	231.6	36.6	43.5	Top	High	BMW 6-2.8l	-
0-280-150-441	19.3	202.8	145.9	-	-	-	-	29.7	35.3	-	High	Audi v8-3.7l, v8-4.2l	-
0-280-150-442	19.3	202.8	145.9	-	-	-	-	29.7	35.3	-	High	-	-
0-280-150-443	18.25	191.8	138	-	-	-	-	28.1	33.3	-	High	Fiat	-
0-280-150-444	14.25	149.8	107.7	-	-	-	-	21.9	26	-	High	Audi 4-1.8l, VW 4-1.8l	-
0-280-150-445	14.25	149.8	107.7	-	-	-	-	21.9	26	-	High	-	-
0-280-150-446	16.75	176	126.6	-	-	-	-	25.8	30.6	-	High	-	-
0-280-150-447	20.0	210.2	151.2	43.5	3.0	20	210.2	30.8	36.5	EV6	High	Audi 4-1.8l Turbo, VW 4-1.8l Turbo	-
0-280-150-447	22.9	240.7	173.1	-	-	-	-	35.2	41.8	EV6	High	Audi 4-1.8l Turbo, VW 4-1.8l Turbo	-
0-280-150-448	22.9	240.7	173.1	-	-	-	-	35.2	41.8	-	High	-	-
0-280-150-449	22.9	240.7	173.1	-	-	-	-	35.2	41.8	-	High	Ferrari v12-5.5l	-
0-280-150-450	31.9	335.3	241.2	-	-	-	-	49.1	58.3	-	High	Fiat	-
0-280-150-452	22.85	240.2	172.7	-	-	-	-	35.2	41.7	-	High	-	-
0-280-150-453	26.0	273.3	196.6	-	-	-	-	40	47.5	-	High	-	-
0-280-150-454	18.2	191.3	137.6	-	-	-	-	28	33.3	-	High	Audi	-
0-280-150-	21.0	220.7	158.8	-	-	-	-	32.3	38.4	-	High	Porsche 6-2.5l, 6-2.7l, 6-3.2l, 6-	-

455	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle				3.4l	Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-280-150-456	18.2	191.3	137.6	-	-	-	-	28	33.3	-	High	Audi	-
0-280-150-457	14.25	149.8	107.7	-	-	-	-	21.9	26	-	High	Audi	-
0-280-150-458	14.25	149.8	107.7	-	-	-	-	21.9	26	-	High	-	-
0-280-150-459	15.6	164	117.9	-	-	-	-	24	28.5	-	High	Audi	-
0-280-150-460	15.6	164	117.9	-	-	-	-	24	28.5	-	High	-	-
0-280-150-461	22.85	240.2	172.7	-	-	-	-	35.2	41.7	-	High	-	-
0-280-150-462	22.55	237	170.5	-	-	-	-	34.7	41.2	-	High	Audi, VW	-
0-280-150-463	18.25	191.8	138	-	-	-	-	28.1	33.3	-	High	Audi v8-4.2l	-
0-280-150-464	23.7	249.1	179.2	-	-	-	-	36.5	43.3	EV6	High	VW 4-1.8l Turbo	-
0-280-150-465	23.7	249.1	179.2	-	-	-	-	36.5	43.3	-	High	-	-
0-280-150-466	26.0	273.3	196.6	-	-	-	-	40	47.5	-	High	BMW	-
0-280-150-467	26.0	273.3	196.6	-	-	-	-	40	47.5	-	High	Audi 1.8l Turbo	-
0-280-150-468	21.0	220.7	158.8	-	-	-	-	32.3	38.4	-	High	Audi	-
0-280-150-469	21.0	220.7	158.8	-	-	-	-	32.3	38.4	-	High	-	-
0-280-150-470	-	-	-	-	-	-	-	-	-	-	High	Porsche 6-3.4l	-
0-280-150-500	18.25	191.8	138	-	-	-	-	28.1	33.3	Top	High	KIA	-
0-280-150-500	20.15	211.8	152.3	43.5	3.0	20.15	211.8	31	36.8	Top	High	-	-
0-280-150-501	18.25	191.8	138	-	-	-	-	28.1	33.3	-	High	BMW 4-1.9l	-
0-280-150-502	22.85	240.2	172.7	-	-	-	-	35.2	41.7	-	High	KIA 4-2.0l	-
0-280-150-503	18.25	191.8	138	-	-	-	-	28.1	33.3	Top	High	-	-
0-280-150-503	20.15	211.8	152.3	43.5	3.0	20.15	211.8	31	36.8	-	High	-	-
0-280-150-504	22.85	240.2	172.7	-	-	-	-	35.2	41.7	-	High	KIA 4-2.0l	-
0-280-150-505	18.25	191.8	138	-	-	-	-	28.1	33.3	-	High	Volvo	-
0-280-150-506	22.85	240.2	172.7	-	-	-	-	35.2	41.7	-	High	KIA	-
0-280-150-507	22.85	240.2	172.7	-	-	-	-	35.2	41.7	-	High	-	-
0-280-150-508	-	-	-	-	-	-	-	-	-	-	High	Audi	-
0-280-150-509	16.5	173.4	124.7	-	-	-	-	25.4	30.1	-	High	Audi	-
0-280-150-550	26.0	273.3	196.6	-	-	-	-	40	47.5	-	High	-	-
0-280-150-551	14.25	149.8	107.7	-	-	-	-	21.9	26	-	High	Audi 1.8l	-
0-280-150-552	14.25	149.8	107.7	-	-	-	-	21.9	26	-	High	Audi v6-2.6l, v6-2.8l	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-280-150-553	26.0	273.3	196.6	-	-	-	-	40	47.5	-	High	VW	-

0-280-150-554	26.0	273.3	196.6	-	-	-	-	40	47.5	-	High	-	-
0-280-150-555	9.6	100.9	72.62	-	-	-	-	14.8	17.5	-	High	-	-
0-280-150-556	18.25	191.8	138	-	-	-	-	28.1	33.3	Top	High	Range Rover v8-3.9l, Land Rover Discovery v8-4.01l	-
0-280-150-556	20.0	210.2	151.2	43.5	3.0	20	210.2	30.8	36.5	Top	High	Ford	-
0-280-150-557	20.0	210.2	151.2	43.5	3.0	20	210.2	30.8	36.5	-	High	-	-
0-280-150-558	40.0	420.4	302.4	43.5	3.0	40	420.4	61.5	73.1	EV1	High	Ford	-
0-280-150-558	43.23	-	326.8	43.5	3.0	-	-	-	-	EV1	High	-	Y
0-280-150-559	39.75	417.8	300.5	-	-	-	-	61.2	72.6	-	High	-	-
0-280-150-560	20.0	210.2	151.2	43.5	3.0	20	210.2	30.8	36.5	-	High	-	-
0-280-150-561	22.0	231.2	166.3	-	-	-	-	33.8	40.2	Top	High	Range Rover, Vette	-
0-280-150-569	20.17	212	152.5	43.5	3.0	20.17	212	31	36.8	Top	High	-	-
0-280-150-588	40.0	420.4	302.4	-	-	-	-	61.5	73.1	-	High	-	-
0-280-150-601	48.5	509.7	366.7	36.25	2.5	53.13	558.4	74.6	88.6	-	-	Ford 2.5l	-
0-280-150-603	-	-	-	-	-	-	-	-	-	-	High	VW	-
0-280-150-604	86.77	912	656	43.5	3.0	86.77	912	133	158	Side	Low	-	-
0-280-150-608	42.0	441.4	317.5	36.25	2.5	46.01	483.6	64.6	76.7	-	-	Ford	-
0-280-150-614	18.0	189.2	136.1	43.5	3.0	18	189.2	27.7	32.9	-	-	Renault	-
0-280-150-651	78.0	819.8	589.7	43.5	3.0	78	819.8	120	142	-	Low	Audi, VW	-
0-280-150-653	98.0	1030	740.9	43.5	3.0	98	1030	150	179	-	Low	Chrysler 2.2l, 2.5l	-
0-280-150-655	98.0	1030	740.9	43.5	3.0	98	1030	150	179	-	Low	Dodge	-
0-280-150-657	81.0	851.3	612.3	43.5	3.0	81	851.3	124	148	-	Low	Dodge, Rover	-
0-280-150-661	60.0	630.6	453.6	43.5	3.0	60	630.6	92.3	109	Side	Low	-	-
0-280-150-665	60.0	630.6	453.6	43.5	3.0	60	630.6	92.3	109	Side	Low	-	-
0-280-150-672	-	-	-	-	-	-	-	-	-	-	High	-	-
0-280-150-674	-	-	-	-	-	-	-	-	-	-	-	Dodge v6-3.9l	-
0-280-150-668	-	-	-	-	-	-	-	-	-	-	Low	VW 1.8l	-
0-280-150-692	90.2	948	681.9	14.5	1.0	156.2	1642	138	164	-	Low	Citroen / Peugeot 1360 cc	-
0-280-150-701	22.85	240.2	172.7	-	-	-	-	35.2	41.7	EV1	High	Alfa v6-3.0l, BMW 6-3.0l, 6-3.5l, Citroen 4-2.0l, Fiat	-
0-280-150-701	21.5	226	162.5	43.5	3.0	21.5	226	33.1	39.3	EV1	High	-	-
	Flow			Rating @			Flow @ 43.5 PSI / 3 Bars	.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-280-150-702	18.0	189.2	136.1	43.5	3.0	18	189.2	27.7	32.9	Top	High	Alfa 4-1.7l, 4-2.0l, v6-2.5l, v6-3.0l, Fiat, Ford 4-2.0l, Nissan	-
0-280-150-703	14.2	149.2	107.4	43.5	3.0	14.2	149.2	21.8	25.9	-	High	Alfa 4-1.7l, Rover 1.4l	-
0-280-150-704	16.2	170.3	122.5	43.5	3.0	16.2	170.3	24.9	29.6	-	High	BMW 4-1.8l	-
0-280-150-705	14.35	150.8	108.5	-	-	-	-	22.1	26.2	-	High	BMW 4-1.0l, 4-1.1l, 4-1.2l, Yugo 1.3l	-
0-280-150-706	20.35	213.9	153.8	36.25	2.5	22.29	234.3	31.3	37.2	EV1	High	HSV v8-5.0l, Mitsubishi 4-2.6l, Porsche v8-5.0l, Saab 4-2.0l Turbo	-

0-280-150-706	24.7	-	186.7	43.5	3.0	-	-	-	-	EV1	High	-	Y
0-280-150-707	18.27	192	138.1	36.25	2.5	20.01	210.3	28.1	33.4	-	High	Alfa	-
0-280-150-708	14.35	150.8	108.5	36.25	2.5	15.72	165.2	22.1	26.2	-	High	Alfa	-
0-280-150-710	13.5	141.9	102.1	36.25	2.5	14.79	155.4	20.8	24.7	EV1	High	Ford 1.9l, 2.3l, v6-3.0l, v6-3.8l, v8-5.0l	-
0-280-150-711	18.25	191.8	138	-	-	-	-	28.1	33.3	EV1	High	Saab 4-2.0l	-
0-280-150-712	20.35	213.9	153.8	36.25	2.5	22.29	234.3	31.3	37.2	Top	High	Saab 4-2.0l Turbo	-
0-280-150-714	20.35	213.9	153.8	-	-	-	-	31.3	37.2	EV1	High	BMW 4-1.8l, 6-3.4l	-
0-280-150-714	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	EV1	High	BMW 4-1.8l, 6-3.4l	-
0-280-150-715	14.5	152.4	109.6	43.5	3.0	14.5	152.4	22.3	26.5	Top	High	BMW 4-1.6l, 4-1.8l, 6-2.5l, v12-5.0l, v12-5.4l	-
0-280-150-716	12.75	134	96.43	43.5	3.0	12.75	134	19.6	23.3	-	High	BMW 4-1.0l, 4-2.0l, 6-2.7l	-
0-280-150-718	19.0	199.7	143.6	32	2.21	22.15	232.8	29.2	34.7	EV1	High	Ford/Trucks v8-5.0l	-
0-280-150-718	17.22	181	130.2	39.2	2.7	18.14	190.7	26.5	31.5	EV1	High	Ford v8-5.0l	-
0-280-150-719	14.4	151.3	108.9	43.5	3.0	14.4	151.3	22.2	26.3	-	High	VW	-
0-280-150-720	14.4	151.3	108.9	43.5	3.0	14.4	151.3	22.2	26.3	-	High	-	-
0-280-150-721	18.2	191.3	137.6	43.5	3.0	18.2	191.3	28	33.3	-	High	VW	-
0-280-150-722	18.2	191.3	137.6	43.5	3.0	18.2	191.3	28	33.3	-	High	-	-
0-280-150-725	16.4	172.4	124	36.25	2.5	17.97	188.8	25.2	30	-	High	Holden 4-1.8l, 4-2.0l, GM 4-2.0l, Nissan 4-1.8l, Opel, Peugeot 4-1.9l, 4-2.2l, 6-2.8l, Volvo 4-2.3l, v6-2.8l, v6-3.0l	-
0-280-150-726	18.65	196	141	-	-	-	-	28.7	34.1	-	High	Ford 6-4.1l	-
0-280-150-727	14.0	147.1	105.8	33	2.28	16.07	168.9	21.5	25.6	EV1	High	Ford/Trucks v8-5.0l, 6-4.9l	-
0-280-150-727	12.45	130.8	94.17	36.3	2.5	13.63	143.2	19.2	22.7	EV1	High	Ford/Trucks v8-5.0l, v6-3.0l, v6-3.8l, 6-4.9l	-
0-280-150-728	24.0	252.2	181.4	43	2.96	24.14	253.7	36.9	43.8	EV1	High	Ford 8-7.5l Truck	-
0-280-150-729	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	Opel	-
0-280-150-730	18.45	193.9	139.5	43.5	3.0	18.45	193.9	28.4	33.7	Top	High	Porsche v8-5.0l, v8-5.4l	-
0-280-150-731	18.45	193.9	139.5	43.5	3.0	18.45	193.9	28.4	33.7	Top	High	Ferrari v8-3.4l, Porsche 6-3.6l	-
0-280-150-734	19.03	200	143.9	36.25	2.5	20.85	219.1	29.3	34.8	-	High	Citrogen 4-1.9l, Peugeot 4-1.9l, 4-2.2l, v6-2.85l, Volvo 4-2.0l, 4-2.3l, v6-2.8l, v6-3.0l	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-280-150-736	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	Ford	-
0-280-150-737	29.0	304.8	219.2	43.5	3.0	29	304.8	44.6	53	Top	High	Audi 2.2l Turbo, Rover, VW	-
0-280-150-738	29.0	304.8	219.2	-	-	-	-	44.6	53	-	High	-	-
0-280-150-740	14.27	150	107.9	43.5	3.0	14.27	150	22	26.1	-	High	Volvo	-
0-280-150-741	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	High	Volvo	-
0-280-150-742	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	High	Hyundai 4-1.5l, 4-1.6l	-
0-280-150-743	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	High	Ford	-
0-280-150-744	20.35	213.9	153.8	36.25	2.5	22.29	234.3	31.3	37.2	-	High	Holden 4-2.0l, GM 4-2.0l 16v, Opel	-

0-280-150-745	22.35	234.9	169	-	-	-	-	34.4	40.8	-	High	Hyundai 4-1.6l, 4-1.8l, v6-3.0l	-
0-280-150-746	26.35	276.9	199.2	-	-	-	-	40.5	48.1	-	High	Hyundai 4-2.4l	-
0-280-150-747	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	High	Opel	-
0-280-150-748	14.37	151	108.6	43.5	3.0	14.37	151	22.1	26.3	-	High	Opel	-
0-280-150-749	20.75	218.1	156.9	-	-	-	-	31.9	37.9	Top	High	MG 4-1.8l, Rover 4-1.8l, Volvo 4-2.3l	-
0-280-150-749	18.85	198.1	142.5	43.5	3.0	18.85	198.1	29	34.4	Top	High	-	-
0-280-150-750	13.13	138	99.31	-	-	-	-	20.2	24	-	High	Ford	-
0-280-150-751	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	High	Daewoo	-
0-280-150-752	14.2	149.2	107.4	43.5	3.0	14.2	149.2	21.8	25.9	-	High	Audi	-
0-280-150-754	22.65	238.1	171.2	-	-	-	-	34.8	41.4	-	High	Hyundai 4-2.0l	-
0-280-150-756	30.55	321.1	231	43.5	3.0	30.55	321.1	47	55.8	EV1	High	Ford v6-3.8l SC, GM v6-4.3l Turbo	-
0-280-150-756	32.0	336.3	241.9	45	3.1	31.46	330.7	49.2	58.5	EV1	High	GM v6-4.3l Turbo Truck	-
0-280-150-757	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	High	VW	-
0-280-150-758	22.85	240.2	172.7	-	-	-	-	35.2	41.7	-	High	VW	-
0-280-150-759	21.5	226	162.5	39.15	2.7	22.66	238.2	33.1	39.3	EV1	High	Ford 460 Truck	-
0-280-150-760	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	EV1	High	Saab 4-2.0l	-
0-280-150-761	22.65	238.1	171.2	-	-	-	-	34.8	41.4	-	High	Saab 4-2.0l Turbo	-
0-280-150-762	20.35	213.9	153.8	43.5	3.0	20.35	213.9	31.3	37.2	Top	High	Citroen 4-1.9l, Peugeot 4-1.9l, Volvo 4-2.3l	-
0-280-150-763	17.9	188.1	135.3	43.5	3.0	17.9	188.1	27.5	32.7	-	High	KIA	-
0-280-150-764	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	High	Fiat	-
0-280-150-766	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	EV1	High	Ford 6-4.9l	-
0-280-150-767	13.13	138	99.31	-	-	-	-	20.2	24	Top	High	Ford	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-280-150-767	17.9	188.1	135.3	43.5	3.0	17.9	188.1	27.5	32.7	Top	High	-	-
0-280-150-769	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	High	Alfa	-
0-280-150-770	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	High	Cosworth	-
0-280-150-771	14.37	151	108.6	43.5	3.0	14.37	151	22.1	26.3	-	High	Opel	-
0-280-150-773	14.27	150	107.9	43.5	3.0	14.27	150	22	26.1	-	High	Hyundai 1.5l	-
0-280-150-774	18.5	194.4	139.9	-	-	-	-	28.5	33.8	Top	High	Buick / Olds / Pontiac v6-3.8l, Chrysler/Dodge 6-3.0l	-
0-280-150-775	18.65	196	141	47.9	3.3	17.77	186.8	28.7	34.1	EV1	High	HSV v8-5.7l, Mitsubishi 4-2.6l	-
0-280-150-775	24.7	-	186.7	43.5	3.0	-	-	-	-	EV1	High	-	Y
0-280-150-776	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	High	Hyundai 1.5l	-
0-280-150-777	26.35	276.9	199.2	-	-	-	-	40.5	48.1	-	High	GM	-
0-280-150-778	18.17	191	137.4	43.5	3.0	18.17	191	28	33.2	Top	High	BMW v8-3.0l, v8-3.5l, v8-4.0l, v8-4.4l	-
0-280-150-779	19.0	199.7	143.6	43.5	3.0	19	199.7	29.2	34.7	Top	High	Volvo 5-2.5l	-
0-280-150-													

783	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	High	KIA 4-2.0l	-	
0-280-150-784	28.83	303	218	-	-	-	-	44.4	52.7	-	High	BMW	-	
0-280-150-785	29.5	310	223	57	3.93	25.77	270.9	45.4	53.9	Top	High	Volvo 5-2.4l	-	
0-280-150-786	22.17	233	167.6	43.5	3.0	22.17	233	34.1	40.5	Top	High	Porsche 6-3.6l	-	
0-280-150-788	19.3	202.8	145.9	-	-	-	-	29.7	35.3	-	High	Mitsubishi v6-3.0l	-	
0-280-150-789	14.37	151	108.6	43.5	3.0	14.37	151	22.1	26.3	-	High	-	-	
0-280-150-790	18.17	191	137.4	43.5	3.0	18.17	191	28	33.2	EV1	High	Ford 6-3.9, 6-4.0l	-	
0-280-150-790	19.8	-	149.7	43.5	3.0	-	-	-	-	EV1	High	-	Y	
0-280-150-791	37.77	397	285.5	-	-	-	-	58.1	69	EV1	High	Porsche 6-3.6l	-	
0-280-150-791	41.14	-	311.0	43.5	3.0	-	-	-	-	EV1	High	-	Y	
0-280-150-792	23.3	244.9	176.1	-	-	-	-	35.8	42.6	-	High	BMW 6-3.2l, v8-5.0l	-	
0-280-150-793	10.75	113	81.31	-	-	-	-	16.5	19.6	-	High	BMW 4-1.2l	-	
0-280-150-802	25.8	271.2	195	36.25	2.5	28.26	297	39.7	47.1	Top	Low	Volvo	-	
0-280-150-802	27.02	284	204.3	43.5	3.0	27.02	284	41.6	49.4	Top	Low	Peugeot 2.2l Turbo, Renault Turbo, Volvo Turbo	-	
0-280-150-803	37.1	389.9	280.5	39.15	2.7	39.11	411	57.1	67.8	EV1	Low	Porsche 944 Turbo 4-2.5l	-	
0-280-150-803	37.91	-	286.6	43.5	3.0	-	-	-	-	EV1	Low	-	Y	
0-280-150-804	32.07	337.1	242.4	43.5	3.0	32.07	337.1	49.3	58.6	Top	Low	Peugeot, Volvo 4-2.3l Turbo	-	
0-280-150-806	32.0	336.3	241.9	43.5	3.0	32	336.3	49.2	58.5	-	Low	Chrysler	-	
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle						Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H	
0-280-150-807	-	-	-	-	-	-	-	-	-	-	Low	-	-	
0-280-150-808	31.5	331.1	238.1	55	3.79	28.01	294.4	48.5	57.5	EV1	Low	Mazda, Chrysler 2.2l Turbo, Holden v6-3.8l	-	
0-280-150-809	-	-	-	-	-	-	-	-	-	-	Low	-	-	
0-280-150-810	28.45	299	215.1	-	-	-	-	43.8	52	EV1	Low	Pontiac 2.0l Turbo	-	
0-280-150-811	28.35	298	214.3	50.8	3.5	26.23	275.7	43.6	51.8	Top	Low	Porsche 944 4-3.0l	-	
0-280-150-812	19.32	203.1	146.1	-	-	-	-	29.7	35.3	EV1	Low	Chrysler v6-3.0l	-	
0-280-150-813	28.45	299	215.1	-	-	-	-	43.8	52	EV1	Low	Chrysler 2.5l Turbo	-	
0-280-150-814	36.53	383.9	276.2	43.5	3.0	36.53	383.9	56.2	66.7	-	Low	-	-	
0-280-150-818	22.65	238.1	171.2	-	-	-	-	34.8	41.4	-	Low	-	-	
0-280-150-819	22.65	238.1	171.2	-	-	-	-	34.8	41.4	-	Low	-	-	
0-280-150-820	22.65	238.1	171.2	-	-	-	-	34.8	41.4	-	Low	-	-	
0-280-150-821	16.93	177.9	128	-	-	-	-	26	30.9	-	Low	GM	-	
0-280-150-823	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	Low	-	-	
0-280-150-824	20.75	218.1	156.9	-	-	-	-	31.9	37.9	-	Low	Porsche	-	
0-280-150-825	18.07	189.9	136.6	43.5	3.0	18.07	189.9	27.8	33	-	Low	-	-	
0-280-150-826	21.22	223	160.4	-	-	-	-	32.6	38.8	-	Low	Chrysler v6-3.8l	-	
0-280-150-	21.22	223	160.4	-	-	-	-	32.6	38.8	-	Low	-	-	

827 0-280-150-828	22.35	234.9	169	-	-	-	-	34.4	40.8	-	Low	Renault	-
0-280-150-829	19.32	203.1	146.1	-	-	-	-	29.7	35.3	EV1	Low	-	-
0-280-150-830	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	Low	Renault	-
0-280-150-831	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	Low	Renault	-
0-280-150-834	37.77	397	285.5	43.5	3.0	37.77	397	58.1	69	Top	Low	Chrysler 2.5l Flex Fuel	-
0-280-150-835	37.77	397	285.5	43.5	3.0	37.77	397	58.1	69	-	Low	Chrysler	-
0-280-150-837	150.35	1580	1136	43.5	3.0	150.3	1580	231	274	Top	Low	Chrysler	-
0-280-150-838	150.35	1580	1136	43.5	3.0	150.3	1580	231	274	-	Low	-	-
0-280-150-839	152.25	1600	1151	43.5	3.0	152.2	1600	234	278	Top	Low	-	-
0-280-150-840	-	-	-	-	-	-	-	-	-	-	Low	-	-
0-280-150-841	59.18	622	447.4	-	-	-	-	91	108	-	Low	-	-
0-280-150-842	150.35	1580	1136	43.5	3.0	150.3	1580	231	274	EV1	Low	-	-
0-280-150-842	159.69	-	1207.2	43.5	3.0	-	-	-	-	EV1	Low	-	Y
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-280-150-845	59.2	622.2	447.5	-	-	-	-	91.1	108	Top	Low	-	-
0-280-150-845	64.5	677.9	487.6	43.5	3.0	64.5	677.9	99.2	117	Top	Low	-	-
0-280-150-846	160.0	1681	1209	43.5	3.0	160	1681	246	292	Top	Low	-	-
0-280-150-846	152.25	1600	1151	43.5	3.0	152.2	1600	234	278	Top	Low	-	-
0-280-150-901	18.55	195	140.2	43.5	3.0	18.55	195	28.5	33.9	EV1	High	GM v6-3.8l, v8-5.0l, Holden v6-3.8l, v8-5.0l, HSV v8-5.0l, Toyota v6-3.8l	-
0-280-150-901	19.35	-	146.3	43.5	3.0	-	-	-	-	EV1	High	-	Y
0-280-150-902	18.75	197.1	141.7	-	-	-	-	28.8	34.3	Top	High	Audi 4-2.0l, VW 4-1.8l	-
0-280-150-902	20.75	218.1	156.9	43.5	3.0	20.75	218.1	31.9	37.9	Top	High	-	-
0-280-150-903	18.75	197.1	141.7	-	-	-	-	28.8	34.3	-	High	VW 1.8l	-
0-280-150-905	23.3	244.9	176.1	-	-	-	-	35.8	42.6	Top	High	Audi, VW 1.8l	-
0-280-150-905	25.1	263.8	189.8	43.5	3.0	25.1	263.8	38.6	45.9	Top	High	-	-
0-280-150-906	23.3	244.9	176.1	-	-	-	-	35.8	42.6	-	High	BMW 4-1.8l	-
0-280-150-908	23.4	245.9	176.9	-	-	-	-	36	42.8	-	High	Ford	-
0-280-150-911	30.0	315.3	226.8	39.15	2.7	31.62	332.4	46.2	54.8	Top	High	Ford v6-3.8l SC	-
0-280-150-911	32.55	342.1	246.1	45	3.1	32	336.4	50.1	59.5	Top	High	Ford v6-3.8l SC	-
0-280-150-912	30.55	321.1	231	43.5	3.0	30.55	321.1	47	55.8	-	High	Ford v6-3.8l SC	-
0-280-150-913	24.4	256.4	184.5	39.15	2.7	25.72	270.3	37.5	44.6	-	High	Ford Truck 8-7.5l	-
0-280-150-914	24.4	256.4	184.5	39.15	2.7	25.72	270.3	37.5	44.6	-	High	-	-
0-280-150-917	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	EV1	High	GM v6-3.8l	-
0-280-150-921	14.27	150	107.9	43.5	3.0	14.27	150	22	26.1	-	High	Audi 4-2.8l, v6-2.6l, v6-2.8l	-

0-280-150-822	14.27	150	107.9	43.5	3.0	14.27	150	22	26.1	-	High	-	-
0-280-150-923	29.3	307.9	221.5	-	-	-	-	45.1	53.5	-	High	Audi, VW	-
0-280-150-924	29.3	307.9	221.5	-	-	-	-	45.1	53.5	-	High	-	-
0-280-150-925	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	High	Dodge Truck v6-3.9l	-
0-280-150-926	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	High	Dodge Truck v6-3.9l	-
0-280-150-927	21.8	229.1	164.8	-	-	-	-	33.5	39.8	Top	High	Chrysler v6-3.8l, Dodge Truck v6-3.9l	-
0-280-150-928	21.8	229.1	164.8	-	-	-	-	33.5	39.8	-	High	Chrysler v6-3.8l, Dodge Truck v6-3.9l	-
0-280-150-929	14.37	151	108.6	43.5	3.0	14.37	151	22.1	26.3	-	High	Audi, VW 6-2.8l	-
0-280-150-930	14.37	151	108.6	43.5	3.0	14.37	151	22.1	26.3	-	High	-	-
0-280-150-931	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	EV1	High	Ford Truck v6-4.0l	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-280-150-932	28.83	303	218	-	-	-	-	44.4	52.7	-	High	Audi, VW	-
0-280-150-933	29.02	305	219.4	-	-	-	-	44.6	53	-	High	-	-
0-280-150-934	28.07	295	212.2	-	-	-	-	43.2	51.3	Top	High	Dodge v6-3.0l, Pontiac v6-3.8l SC	-
0-280-150-934	29.3	307.9	221.5	43.5	3.0	29.3	307.9	45.1	53.5	Top	High	-	-
0-280-150-935	16.45	172.9	124.4	-	-	-	-	25.3	30.1	-	Low	Fiat	-
0-280-150-936	18.07	189.9	136.6	43.5	3.0	18.07	189.9	27.8	33	-	Low	-	-
0-280-150-937	13.5	141.9	102.1	-	-	-	-	20.8	24.7	Top	High	Ford 1.9l, 2.3l, 6-4.9l	-
0-280-150-937	14.45	151.9	109.2	43.5	3.0	14.45	151.9	22.2	26.4	Top	High	-	-
0-280-150-938	13.5	141.9	102.1	-	-	-	-	20.8	24.7	-	High	Ford 1.9l, 2.3l, 6-4.9l	-
0-280-150-939	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	EV1	High	Ford v6-3.8l, v8-4.6l	-
0-280-150-940	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	-	-
0-280-150-941	14.1	148.2	106.6	43.5	3.0	14.1	148.2	21.7	25.8	Top	High	Ford 1.9l, 2.3l	-
0-280-150-942	14.1	148.2	106.6	43.5	3.0	14.1	148.2	21.7	25.8	-	High	-	-
0-280-150-943	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	EV1	High	Ford v6-3.8l, v8-4.6l	-
0-280-150-944	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	-	-
0-280-150-945	28.55	300.1	215.8	-	-	-	-	43.9	52.2	Top	High	Ford v6-3.8l SC	-
0-280-150-945	29.97	315	226.6	-	-	-	-	46.1	54.8	Top	High	Ford v6-3.8l SC	-
0-280-150-946	28.55	300.1	215.8	-	-	-	-	43.9	52.2	-	High	-	-
0-280-150-947	24.27	255.1	183.5	39.15	2.7	25.58	268.9	37.3	44.3	EV1	High	Ford v8-5.0l, Truck v8-7.5l	-
0-280-150-948	24.25	254.9	183.3	39.15	2.7	25.56	268.7	37.3	44.3	-	High	-	-
0-280-150-951	32.92	346	248.9	43.5	3.0	32.92	346	50.6	60.1	Top	High	Audi 5-2.2l Turbo, Porsche, VW	-
0-280-150-951	28.55	300.1	215.8	43.5	3.0	28.55	300.1	43.9	52.2	Top	High	Feedback - Mihkel	-
0-280-150-952	25.02	263	189.1	-	-	-	-	38.5	45.7	-	High	-	-
0-280-150-953	19.5	204.9	147.4	-	-	-	-	30	35.6	Top	High	Audi, VW v6-2.8l	-
0-280-150-954	17.9	188.1	135.3	-	-	-	-	27.5	32.7	-	High	-	-

0-280-150-955	16.75	176	126.6	-	-	-	-	25.8	30.6	Top	High	Audi, VW 2.0l	-
0-280-150-955	18.65	196	141	43.5	3.0	18.65	196	28.7	34.1	Top	High	-	-
0-280-150-956	16.75	176	126.6	-	-	-	-	25.8	30.6	-	High	-	-
0-280-150-957	21.22	223	160.4	-	-	-	-	32.6	38.8	-	High	Chrysler v6-3.8l, Dodge Truck v6-3.9l	-
0-280-150-958	21.22	223	160.4	-	-	-	-	32.6	38.8	-	High	Chrysler v6-3.8l, Dodge Truck v6-3.9l	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-280-150-960	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	EV1	High	Holden v6-3.8l, v8-5.0l, HSV v8-5.0l, Toyota v6-3.8l	-
0-280-150-960	19.91	-	150.5	43.5	3.0	-	-	-	-	EV1	High	-	Y
0-280-150-962	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	High	Opel	-
0-280-150-963	17.7	186	133.8	-	-	-	-	27.2	32.3	-	High	Nissan	-
0-280-150-964	17.7	186	133.8	-	-	-	-	27.2	32.3	-	High	-	-
0-280-150-965	21.03	221	159	-	-	-	-	32.4	38.4	Top	High	Chrysler / Dodge / Plymouth 4-2.0l	-
0-280-150-965	22.65	238.1	171.2	43.5	3.0	22.65	238.1	34.8	41.4	Top	High	-	-
0-280-150-966	21.03	221	159	-	-	-	-	32.4	38.4	-	High	-	-
0-280-150-967	33.9	356.3	256.3	43.5	3.0	33.9	356.3	52.2	61.9	EV1	High	Ford 3.0l, v6-3.8l SC	-
0-280-150-967	35.68	-	269.7	43.5	3.0	-	-	-	-	EV1	High	-	Y
0-280-150-968	33.9	356.3	256.3	43.5	3.0	33.9	356.3	52.2	61.9	-	High	Ford	-
0-280-150-969	42.0	441.4	317.5	43.5	3.0	42	441.4	64.6	76.7	-	Low	GM	-
0-280-150-971	22.35	234.9	169	-	-	-	-	34.4	40.8	-	High	Hyundai	-
0-280-150-972	21.03	221	159	-	-	-	-	32.4	38.4	-	High	Ford	-
0-280-150-973	18.65	196	141	43.5	3.0	18.65	196	28.7	34.1	Top	High	Buick, Holden v6-3.8l, v8-5.0l, HSV v8-5.0l, Toyota v6-3.8l	-
0-280-150-973	19.8	208.1	149.7	43.5	3.0	19.8	208.1	30.5	36.2	Top	High	Buick, Holden v6-3.8l, v8-5.0l, HSV v8-5.0l, Toyota v6-3.8l	-
0-280-150-974	28.92	303.9	218.6	-	-	-	-	44.5	52.8	-	High	Fiat	-
0-280-150-975	20.17	212	152.5	-	-	-	-	31	36.8	-	High	GM	-
0-280-150-976	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	High	Ford	-
0-280-150-977	18.75	197.1	141.7	43.5	3.0	18.75	197.1	28.8	34.3	-	High	Audi, VW	-
0-280-150-978	18.75	197.1	141.7	43.5	3.0	18.75	197.1	28.8	34.3	-	High	-	-
0-280-150-979	19.8	208.1	149.7	-	-	-	-	30.5	36.2	-	High	Audi, VW	-
0-280-150-980	19.8	208.1	149.7	-	-	-	-	30.5	36.2	-	High	-	-
0-280-150-981	16.75	176	126.6	-	-	-	-	25.8	30.6	-	High	Fiat	-
0-280-150-982	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	High	Audi, VW	-
0-280-150-983	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	High	Daewoo	-
0-280-150-984	32.92	346	248.9	-	-	-	-	50.6	60.1	-	High	Porsche	-
0-280-150-985	36.63	385	276.9	-	-	-	-	56.4	66.9	-	High	-	-
0-280-150-987	14.37	151	108.6	-	-	-	-	22.1	26.3	-	High	Citroen 4-1.6l	-

0-280-150-988	20.35	213.9	153.8	-	-	-	-	31.3	37.2	-	High	Alfa	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-280-150-989	16.75	176	126.6	-	-	-	-	25.8	30.6	-	High	-	-
0-280-150-990	16.75	176	126.6	-	-	-	-	25.8	30.6	-	High	VW	-
0-280-150-991	21.03	221	159	-	-	-	-	32.4	38.4	Top	High	Ford, Vette	-
0-280-150-991	24.0	252.2	181.4	-	-	-	-	36.9	43.8	Top	High	Ford, Vette	-
0-280-150-992	21.03	221	159	-	-	-	-	32.4	38.4	-	High	-	-
0-280-150-993	10.47	110	79.20	-	-	-	-	16.1	19.1	-	High	Ford	-
0-280-150-995	10.65	111.9	80.56	-	-	-	-	16.4	19.5	-	High	Renault	-
0-280-150-996	12.55	131.9	94.92	-	-	-	-	19.3	22.9	-	High	-	-
0-280-150-997	9.61	101	72.70	-	-	-	-	14.8	17.6	-	High	Ford	-
0-280-150-998	21.03	221	159	-	-	-	-	32.4	38.4	Top	High	Chrysler	-
0-280-150-999	21.03	221	159	-	-	-	-	32.4	38.4	-	High	-	-
0-280-155-002	-	-	-	-	-	-	-	-	-	-	High	Saab 4-2.3l	-
0-280-155-003	25.12	264	189.9	43.5	3.0	25.12	264	38.6	45.9	Top	High	-	-
0-280-155-007	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	-	Low	Jaguar v12-5.3l, v12-6.0l	-
0-280-155-008	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	Top	High	Saab 4-2.1l	-
0-280-155-009	32.95	346.3	249.1	39.15	2.7	34.73	365	50.7	60.2	-	High	Saab 2.3l Turbo	-
0-280-155-010	32.5	341.6	245.7	-	-	-	-	50	59.4	Top	High	Porsche 4-3.0l	-
0-280-155-012	-	-	-	-	-	-	-	-	-	-	High	Ford, Cosworth	-
0-280-155-013	-	-	-	-	-	-	-	-	-	-	High	Ferrari v8-3.5l	-
0-280-155-101	24.35	255.9	184.1	43.5	3.0	24.35	255.9	37.5	44.5	Top	High	Chrysler / Dodge v10-8.0l	-
0-280-155-104	31.4	330	237.4	43.5	3.0	31.4	330	48.3	57.4	Top	High	Bentley v8-6.8l, R R v8-6.8l	-
0-280-155-127	39.2	412	296.3	43.5	3.0	39.2	412	60.3	71.6	Top	High	-	-
0-280-155-201	18.8	197.6	142.1	-	-	-	-	28.9	34.3	-	High	M B v12-6.0l	-
0-280-155-203	18.8	197.6	142.1	-	-	-	-	28.9	34.3	-	High	M B v8-5.0l	-
0-280-155-205	18.8	197.6	142.1	-	-	-	-	28.9	34.3	-	High	M B 6-3.2l	-
0-280-155-207	-	-	-	-	-	-	-	-	-	-	-	M B v8-4.2l, v8-5.0l	-
0-280-155-209	18.8	197.6	142.1	-	-	-	-	28.9	34.3	-	high	M B 4-1.8l, 4-2.0l, 4-2.2l, 4-2.3l, 6-2.8l, 6-3.6l	-
0-280-155-213	18.35	192.9	138.7	43.5	3.0	18.35	192.9	28.2	33.5	-	High	Ferrari	-
0-280-155-216	19.85	208.6	150.1	-	-	-	-	30.5	36.3	-	High	Citroen 4-2.0l, Peugeot 4-2.0l - Feedback - Mikael Westerberg	-
0-280-155-217	18.8	197.6	142.1	-	-	-	-	28.9	34.3	-	High	M B v8-4.2l, v8-5.0l	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-280-155-219	18.8	197.6	142.1	-	-	-	-	28.9	34.3	-	High	M B v12-6.0l	-

0-280-155-503	18.2	191.3	137.6	43.5	3.0	18.2	191.3	28	33.3	-	High	Ford	-
0-280-155-504	24.35	255.9	184.1	43.5	3.0	24.35	255.9	37.5	44.5	-	High	Ford	-
0-280-155-505	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	-	-
0-280-155-600	16.55	173.9	125.1	43.5	3.0	16.55	173.9	25.5	30.2	-	High	VW	-
0-280-155-602	24.3	255.4	183.7	43.5	3.0	24.3	255.4	37.4	44.4	-	High	-	-
0-280-155-604	13.1	137.7	99.08	-	-	-	-	20.2	23.9	-	High	VW 4-2.0l, 5-2.5l	-
0-280-155-606	20.5	215.5	155	43.5	3.0	20.5	215.5	31.5	37.5	-	High	VW	-
0-280-155-607	25.0	262.8	189	43.5	3.0	25	262.8	38.5	45.7	-	High	-	-
0-280-155-609	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	Cosworth	-
0-280-155-611	24.9	261.7	188.2	43.5	3.0	24.9	261.7	38.3	45.5	-	High	-	-
0-280-155-613	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	high	Citroen v6-3.0l, Peugeot 6-3.0l	-
0-280-155-700	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	Top	High	Ford v8-5.0l	-
0-280-155-702	19.0	199.7	143.6	43.5	3.0	19	199.7	29.2	34.7	-	High	Volvo	-
0-280-155-703	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	Top	High	Chrysler 4-2.4l, Dodge 4-2.0l	-
0-280-155-705	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	Top	High	Ford	-
0-280-155-706	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	Ford	-
0-280-155-707	12.9	135.6	97.57	43.5	3.0	12.9	135.6	19.8	23.6	-	High	Ford	-
0-280-155-708	12.9	135.6	97.57	43.5	3.0	12.9	135.6	19.8	23.6	-	High	Ford	-
0-280-155-710	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	Ford 5.0 5.8 4.6 v8	-
0-280-155-712	19.4	203.9	146.7	43.5	3.0	19.4	203.9	29.8	35.4	-	High	Holden v6-2.5l, Opel, Saab v6-2.5l, v6-3.0l	-
0-280-155-715	22.45	235.9	169.7	43.5	3.0	22.45	235.9	34.5	41	Top	High	Ford 3.0l, v8	-
0-280-155-721	22.4	235.4	169.3	43.5	3.0	22.4	235.4	34.5	40.9	Top	High	Chrysler / Dodge v10-8.0l	-
0-280-155-723	21.6	227	163.3	43.5	3.0	21.6	227	33.2	39.5	-	High	Mitsubishi v6-3.0l	-
0-280-155-724	21.0	220.7	158.8	43.5	3.0	21	220.7	32.3	38.4	-	High	Renault	-
0-280-155-725	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	Ford	-
0-280-155-731	9.15	96.21	69.22	43.5	3.0	9.155	96.21	14.1	16.7	-	High	VW	-
0-280-155-734	22.45	235.9	169.7	43.5	3.0	22.45	235.9	34.5	41	Top	High	Ford v6-4.0l	-
0-280-155-735	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	Ford	-
0-280-155-737	34.55	363.1	261.2	43.5	3.0	34.55	363.1	53.2	63.1	EV6	High	GM v6-3.8l SC	y
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-280-155-739	26.35	276.9	199.2	43.5	3.0	26.35	276.9	40.5	48.1	-	High	-	-
0-280-155-740	21.1	221.8	159.5	43.5	3.0	21.1	221.8	32.5	38.5	Top	High	Chrysler	-
0-280-155-742	15.8	166.1	119.4	43.5	3.0	15.8	166.1	24.3	28.9	-	High	M B 4-1.8l, v6-2.4l, v6-2.8l	-
0-280-155-744	19.0	199.7	143.6	43.5	3.0	19	199.7	29.2	34.7	-	High	-	-
0-280-155-746	19.0	199.7	143.6	43.5	3.0	19	199.7	29.2	34.7	-	High	Volvo 5-2.5l, 6-3.0l	-

0-280-155-748	18.3	192.3	138.3	43.5	3.0	18.3	192.3	28.2	33.4	-	High	Saab	-
0-280-155-749	33.3	350	251.7	43.5	3.0	33.3	350	51.2	60.8	-	High	Saab 4-2.3l Turbo	-
0-280-155-750	22.45	235.9	169.7	43.5	3.0	22.45	235.9	34.5	41	-	High	Saab 4-2.0l Turbo	-
0-280-155-752	28.55	300.1	215.8	-	-	-	-	43.9	52.2	-	-	LS6	-
0-280-155-753	11.8	124	89.25	43.5	3.0	11.8	124	18.2	21.6	-	High	M B 4-1.4, 4-1.6l	-
0-280-155-755	-	-	-	-	-	-	-	-	-	-	-	Ferrari v12-4.7l	-
0-280-155-756	12.7	133.5	96.06	43.5	3.0	12.7	133.5	19.5	23.2	-	High	Ford	-
0-280-155-757	19.0	199.7	143.6	43.5	3.0	19	199.7	29.2	34.7	-	High	-	-
0-280-155-758	19.0	199.7	143.6	43.5	3.0	19	199.7	29.2	34.7	-	High	M B 6-2.8l, v6-3.6l	-
0-280-155-759	30.0	315.3	226.8	43.5	3.0	30	315.3	46.2	54.8	-	High	Volvo 5-2.3l Turbo, 5-2.5l Turbo	-
0-280-155-761	14.0	147.1	105.8	43.5	3.0	14	147.1	21.5	25.6	-	High	VW	-
0-280-155-763	9.1	95.69	68.84	43.5	3.0	9.105	95.69	14	16.6	-	High	VW	-
0-280-155-764	9.1	95.69	68.84	43.5	3.0	9.105	95.69	14	16.6	-	High	Opel	-
0-280-155-765	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	Hyundai	-
0-280-155-766	33.3	350	251.7	43.5	3.0	33.3	350	51.2	60.8	-	High	Volvo 5-2.3l, 5-2.3l Turbo	-
0-280-155-769	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	Alfa Romeo 4-2.0l, Fiat	-
0-280-155-770	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	Fiat	-
0-280-155-773	14.0	147.1	105.8	43.5	3.0	14	147.1	21.5	25.6	-	High	VW	-
0-280-155-774	26.0	273.3	196.6	43.5	3.0	26	273.3	40	47.5	-	High	Ford	-
0-280-155-777	14.25	149.8	107.7	43.5	3.0	14.25	149.8	21.9	26	EV6	High	Holden v6-3.8l	-
0-280-155-777	19.84	-	150.0	43.5	3.0	-	-	-	-	EV6	High	-	Y
0-280-155-780	22.3	234.4	168.6	43.5	3.0	22.3	234.4	34.3	40.7	-	High	Chrysler	-
0-280-155-782	21.3	223.9	161	43.5	3.0	21.3	223.9	32.8	38.9	-	High	Chrysler	-
0-280-155-784	21.3	223.9	161	43.5	3.0	21.3	223.9	32.8	38.9	-	High	Chrysler	-
0-280-155-785	-	-	-	-	-	-	-	-	-	-	-	Volvo 5-2.3l Turbo, 5-2.5l Turbo	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-280-155-786	9.5	99.89	71.86	43.5	3.0	9.505	99.89	14.6	17.4	-	High	Ford	-
0-280-155-787	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	Range Rover - Land Rover Discovery 4.0l, v8-4.6l	-
0-280-155-788	31.0	325.8	234.4	43.5	3.0	31	325.8	47.7	56.6	-	High	BMW 1-0.7l, 4-1.1l, 4-1.2l, Mitsubishi v6-3.0l	-
0-280-155-789	21.0	220.7	158.8	43.5	3.0	21	220.7	32.3	38.4	Top	High	Chrysler	-
0-280-155-791	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	Top	High	VW 4-2.0l	-
0-280-155-793	9.1	95.69	68.84	43.5	3.0	9.105	95.69	14	16.6	-	High	Opel	-
0-280-155-794	12.6	132.4	95.30	43.5	3.0	12.6	132.4	19.4	23	-	High	Citroen 4-1.6l	-
0-280-155-795	11.3	118.8	85.47	43.5	3.0	11.3	118.8	17.4	20.6	-	High	Citroen 4-1.4l	-
0-280-155-798	26.8	281.7	202.6	43.5	3.0	26.8	281.7	41.2	49	-	High	Nissan	-
0-280-155-	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	-	-

800 0-280-155-803	-	-	-	-	-	-	-	-	-	-	-	-	Citroen 4-2.0l, Peugeot 4-2.0l	-
0-280-155-804	33.3	350	251.7	43.5	3.0	33.3	350	51.2	60.8	-	High	-	-	
0-280-155-807	14.25	149.8	107.7	43.5	3.0	14.25	149.8	21.9	26	-	High	KIA	-	
0-280-155-808	14.0	147.1	105.8	43.5	3.0	14	147.1	21.5	25.6	-	High	KIA	-	
0-280-155-809	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	-	-	
0-280-155-810	14.0	147.1	105.8	43.5	3.0	14	147.1	21.5	25.6	-	High	Ford	-	
0-280-155-811	34.3	360.5	259.3	43.5	3.0	34.3	360.5	52.8	62.7	EV1	High	Ford, GM	-	
0-280-155-811	36.25	381	274	43.5	3.0	36.25	381	55.8	66.2	Top	High	Ford, GM - Feedback - John Tiltage	-	
0-280-155-812	9.1	95.69	68.84	43.5	3.0	9.105	95.69	14	16.6	-	High	VW	-	
0-280-155-814	11.5	120.9	86.98	43.5	3.0	11.5	120.9	17.7	21	EV6	High	-	-	
0-280-155-816	14.0	147.1	105.8	43.5	3.0	14	147.1	21.5	25.6	-	High	Fiat	-	
0-280-155-819	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	Ford 4-1.8l	-	
0-280-155-820	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	Ford	-	
0-280-155-821	14.25	149.8	107.7	43.5	3.0	14.25	149.8	21.9	26	EV6	High	Ford v8-5.0l	-	
0-280-155-821	19.84	-	150.0	43.5	3.0	-	-	-	-	EV6	High	-	Y	
0-280-155-822	21.0	220.7	158.8	43.5	3.0	21	220.7	32.3	38.4	-	High	Alfa Romeo 4-2.0l, GM	-	
0-280-155-823	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	BMW v8-3.5l, v8-4.4l, v8-4.6l	-	
0-280-155-824	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	Audi, Ford 4-2.0l	-	
0-280-155-825	21.3	223.9	161	43.5	3.0	21.3	223.9	32.8	38.9	EV12	High	Audi	-	
0-280-155-828	21.3	223.9	161	43.5	3.0	21.3	223.9	32.8	38.9	-	High	VW	-	
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle						Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application		n-H
0-280-155-830	33.3	350	251.7	43.5	3.0	33.3	350	51.2	60.8	-	High	Volvo 5-2.3l Turbo		-
0-280-155-830	34.55	363.1	261.2	43.5	3.0	34.55	363.1	53.2	63.1	EV6	High	-	Y	
0-280-155-831	31.8	334.2	240.4	55.1	3.8	28.26	297	48.9	58.1	-	High	Volvo 5-2.4l, 5-2.4l Turbo, 2.5l Turbo, 6-2.8l Turbo - Feedback - Knut Solem		-
0-280-155-832	22.5	236.5	170.1	43.5	3.0	22.5	236.5	34.6	41.1	-	High	Volvo 6-3.0l		-
0-280-155-835	14.0	147.1	105.8	43.5	3.0	14	147.1	21.5	25.6	-	High	VW		-
0-280-155-837	9.1	95.69	68.84	43.5	3.0	9.105	95.69	14	16.6	-	High	VW		-
0-280-155-839	20.7	217.6	156.5	43.5	3.0	20.7	217.6	31.8	37.8	-	High	M B v8-4.3l		-
0-280-155-842	14.0	147.1	105.8	43.5	3.0	14	147.1	21.5	25.6	-	High	-		-
0-280-155-843	11.1	116.7	83.96	43.5	3.0	11.1	116.7	17.1	20.3	-	High	-		-
0-280-155-844	14.3	150.3	108.1	43.5	3.0	14.3	150.3	22	26.1	EV6	High	Ford v6-4.0l		-
0-280-155-844	19.87	-	150.2	43.5	3.0	-	-	-	-	EV6	High	-	Y	
0-280-155-845	22.3	234.4	168.6	43.5	3.0	22.3	234.4	34.3	40.7	-	High	Ford		-
0-280-155-846	12.9	135.6	97.57	43.5	3.0	12.9	135.6	19.8	23.6	-	High	Ford v6-4.0l, Mazda		-
0-280-155-	14.0	147.1	105.8	43.5	3.0	14	147.1	21.5	25.6	-	High	Ford		-

847 0-280-155-848	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	Opel	-
0-280-155-855	-	-	-	-	-	-	-	-	-	-	-	Ford v6-2.5l	-
0-280-155-857	19.8	208.1	149.7	43.5	3.0	19.8	208.1	30.5	36.2	EV6	High	-	-
0-280-155-861	19.8	208.1	149.7	43.5	3.0	19.8	208.1	30.5	36.2	EV6	High	Ford v8-5.0l, 2.5l	-
0-280-155-863	14.66	154.1	110.8	43.5	3.0	14.66	154.1	22.6	26.8	EV6	High	Ford 3.0l	-
0-280-155-865	25.9	272.2	195.8	43.5	3.0	25.9	272.2	39.8	47.3	EV6	High	Ford v8-4.6l, v8-5.4l	-
0-280-155-868	34.54	363	261.1	43.5	3.0	34.54	363	53.1	63.1	EV6	High	Holden v6-3.8l SC, HSV v6-3.8l SC	y
0-280-155-869	25.4	267	192	43.5	3.0	25.4	267	39.1	46.4	-	High	Ferrari v8-3.5l	-
0-280-155-870	14.0	147.1	105.8	43.5	3.0	14	147.1	21.5	25.6	-	High	Toyota	-
0-280-155-871	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	Honda	-
0-280-155-872	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	VW	-
0-280-155-874	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	VW	-
0-280-155-876	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	KIA	-
0-280-155-884	16.75	176	126.6	-	-	-	-	25.8	30.6	-	High	MG 4-1.8l, Rover 4-1.8l	-
0-280-155-885	14.1	148.2	106.6	43.5	3.0	14.1	148.2	21.7	25.8	-	High	Rover	-
0-280-155-886	11.1	116.7	83.96	43.5	3.0	11.1	116.7	17.1	20.3	-	High	Rover	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-280-155-887	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	EV1	High	Ford	-
0-280-155-890	16.35	171.8	123.6	43.5	3.0	16.35	171.8	25.2	29.9	EV6	High	HSV v8-5.7l LS1	-
0-280-155-890	22.75	-	172.0	43.5	3.0	-	-	-	-	EV6	High	-	Y
0-280-155-892	33.0	346.8	249.5	-	-	-	-	50.8	60.3	EV12	High	Audi 4-1.8l Turbo	-
0-280-155-892	35.58	-	269	43.5	3.0	-	-	-	-	EV12	High	-	Y
0-280-155-893	36.75	386.2	277.8	43.5	3.0	36.75	386.2	56.5	67.1	-	High	VW	-
0-280-155-894	29.9	314.2	226	43.5	3.0	29.9	314.2	46	54.6	-	High	Audi	-
0-280-155-895	29.9	314.2	226	43.5	3.0	29.9	314.2	46	54.6	-	High	Audi	-
0-280-155-897	28.7	301.6	217	43.5	3.0	28.7	301.6	44.2	52.4	EV12	High	Audi 4-1.8l Turbo	y
0-280-155-899	20.5	215.5	155	43.5	3.0	20.5	215.5	31.5	37.5	-	High	Audi	-
0-280-155-900	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	Top	High	Ford	-
0-280-155-905	8.95	94.11	67.71	43.5	3.0	8.955	94.11	13.8	16.4	-	High	Ford	-
0-280-155-909	20.0	210.2	151.2	-	-	-	-	30.8	36.5	-	High	Ford	-
0-280-155-915	25.57	268.7	193.3	43.5	3.0	25.57	268.7	39.3	46.7	EV1	High	-	-
0-280-155-917	13.55	142.4	102.4	43.5	3.0	13.55	142.4	20.8	24.8	EV6	High	Ford v8-5.0l, v8-4.6l, 6.8l	-
0-280-155-917	18.85	198.1	142.5	43.5	3.0	18.85	198.1	29	34.4	EV6	High	Feedback - Shane/Glynn Withey	y
0-280-155-919	9.1	95.69	68.84	43.5	3.0	9.105	95.69	14	16.6	-	High	VW	-
0-280-155-921	16.75	176	126.6	-	-	-	-	25.8	30.6	-	High	Audi v8-4.2l	-

0-280-155-927	23.5	247	177.7	43.5	3.0	23.5	247	36.2	42.9	-	High	VW	-
0-280-155-931	28.55	300.1	215.8	43.5	3.0	28.55	300.1	43.9	52.2	EV6	High	Holden v8-5.7l LS1, HSV v8-5.7l LS1	-
0-280-155-931	24.74	-	187.0	43.5	3.0	-	-	-	-	EV6	High	-	Y
0-280-155-933	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	Holden	-
0-280-155-934	23.6	248	178.4	43.5	3.0	23.6	248	36.3	43.1	Top	High	Dodge v8-5.9l, 3.9l	-
0-280-155-936	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	Toyota	-
0-280-155-937	-	-	-	-	-	-	-	-	-	Top	-	Nissan	-
0-280-155-940	19.0	199.7	143.6	43.5	3.0	19	199.7	29.2	34.7	-	High	Nissan	-
0-280-155-942	15.1	158.7	114.2	43.5	3.0	15.1	158.7	23.2	27.6	-	High	Nissan	-
0-280-155-954	28.55	300.1	215.8	43.5	3.0	28.55	300.1	43.9	52.2	Top	High	-	-
0-280-155-956	24.25	254.9	183.3	43.5	3.0	24.25	254.9	37.3	44.3	Top	High	-	-
0-280-155-962	12.7	133.5	96.06	43.5	3.0	12.7	133.5	19.5	23.2	-	High	Ford	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-280-155-963	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	Ford	-
0-280-155-964	9.1	95.69	68.84	43.5	3.0	9.105	95.69	14	16.6	-	High	Ford	-
0-280-155-965	9.1	95.69	68.84	43.5	3.0	9.105	95.69	14	16.6	-	High	Opel	-
0-280-155-967	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	-	-
0-280-155-968	29.5	310	223	43.5	3.0	29.5	310	45.4	53.9	EV6	High	-	-
0-280-155-968 Green	44.25	465.1	334.5	55.1	3.8	39.32	413.2	68.1	80.8	EV6	High	Volvo S60R, V70R Feedback Jarko Andersson	-
0-280-155-968	41.01	-	310.0	43.5	3.0	-	-	-	-	EV6	High	-	Y
0-280-155-969	14.2	149.2	107.4	43.5	3.0	14.2	149.2	21.8	25.9	-	High	Ford	-
0-280-155-970	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	BMW	-
0-280-155-971	14.2	149.2	107.4	43.5	3.0	14.2	149.2	21.8	25.9	-	High	Fiat	-
0-280-155-976	19.1	200.7	144.4	43.5	3.0	19.1	200.7	29.4	34.9	-	High	Chrysler	-
0-280-155-978	20.9	219.7	158	43.5	3.0	20.9	219.7	32.2	38.2	-	High	Alfa, Fiat	-
0-280-155-981	11.0	115.6	83.20	43.5	3.0	11	115.6	16.9	20.1	-	High	VW	-
0-280-155-983	20.9	219.7	158	43.5	3.0	20.9	219.7	32.2	38.2	-	High	VW	-
0-280-155-985	20.9	219.7	158	43.5	3.0	20.9	219.7	32.2	38.2	-	High	VW	-
0-280-155-988	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	Audi v8-4.2l	-
0-280-155-993	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	VW	-
0-280-155-994	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	Citroen v6-3.0l, Peugeot 6-3.0l	-
0-280-155-995	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	VW	-
0-280-155-997	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	VW	-
0-280-156-001	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	VW	-
0-280-156-002	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	-	VW	-
0-280-156-													

Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
003	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	VW	-
0-280-156-005	14.25	149.8	107.7	43.5	3.0	14.25	149.8	21.9	26	-	High	Ford	-
0-280-156-006	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	GM	-
0-280-156-009	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	Ford	-
0-280-156-010	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	Ford	-
0-280-156-011	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	Ford	-
0-280-156-012	41.02	431.1	310.1	43.5	3.0	41.02	431.1	63.1	74.9	EV6	High	Feedback - Ned Ritchie	y
0-280-156-013	16.35	171.8	123.6	43.5	3.0	16.35	171.8	25.2	29.9	EV6	High	-	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-280-156-013	22.75	-	172.0	43.5	3.0	-	-	-	-	EV6	High	-	Y
0-280-156-014	17.0	178.7	128.5	55.1	3.8	15.1	158.8	26.2	31.1	EV6	High	M B v6-2.6l, Crossfire N/A v6-3.2l, VW v6-2.8l	-
0-280-156-016	18.75	197.1	141.7	43.5	3.0	18.75	197.1	28.8	34.3	-	High	-	-
0-280-156-018	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	Fiat	-
0-280-156-019	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	Toyota	-
0-280-156-021	29.0	304.8	219.2	43.5	3.0	29	304.8	44.6	53	-	High	Opel	-
0-280-156-022	25.9	272.2	195.8	-	-	-	-	39.8	47.3	-	High	Saab 4-2.0l	-
0-280-156-023	35.5	373.1	268.4	43.5	3.0	35.5	373.1	54.6	64.9	-	-	Saab 4-2.0l, 4-2.3l Turbo	-
0-280-156-024	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	MG 4-1.8l, Rover 4-1.8l	-
0-280-156-025	9.1	95.69	68.84	43.5	3.0	9.105	95.69	14	16.6	-	High	-	-
0-280-156-026	28.8	302.7	217.7	43.5	3.0	28.8	302.7	44.3	52.6	-	High	BMW 1-0.7l	-
0-280-156-027	12.7	133.5	96.06	43.5	3.0	12.7	133.5	19.5	23.2	-	High	BMW	-
0-280-156-028	22.8	239.6	172.4	43.5	3.0	22.8	239.6	35.1	41.7	EV1	High	Ford	-
0-280-156-029	20.9	219.7	158	43.5	3.0	20.9	219.7	32.2	38.2	EV1	High	Ford 4.0l	-
0-280-156-034	14.0	147.1	105.8	-	-	-	-	21.5	25.6	-	High	Citroen 4-1.6l, Peugeot 4-1.6l	-
0-280-156-036	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	Top	High	-	-
0-280-156-038	21.35	224.4	161.4	43.5	3.0	21.35	224.4	32.8	39	-	High	Alfa Romeo v6-3.2l, Fiat	-
0-280-156-039	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	Alfa Romeo v6-2.5l, Fiat	-
0-280-156-040	28.8	302.7	217.7	43.5	3.0	28.8	302.7	44.3	52.6	-	High	Rolls Royce	-
0-280-156-045	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	Holden v6-2.6l, Opel	-
0-280-156-046	18.08	190	136.7	43.5	3.0	18.08	190	27.8	33	EV6	High	Ford 2.0l sohc	-
0-280-156-050	12.8	134.5	96.81	43.5	3.0	12.8	134.5	19.7	23.4	-	High	-	-
0-280-156-052	23.5	247	177.7	43.5	3.0	23.5	247	36.2	42.9	-	High	BMW 6-3.2l	-
0-280-156-053	22.75	239.1	172	43.5	3.0	22.75	239.1	35	41.6	-	High	Porsche	-
0-280-156-057	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	-	-
0-280-156-058	7.15	75.19	54.10	43.5	3.0	7.155	75.19	11	13.1	-	High	-	-
0-280-156-	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	VW	-

Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
059 0-280-156-061	30.15	316.9	227.9	43.5	3.0	30.15	316.9	46.4	55.1	EV6	-	Audi, VW	-
0-280-156-062	-	-	-	-	-	-	-	-	-	-	-	Audi 4-1.8l	-
0-280-156-063	33.0	346.8	249.5	-	-	-	-	50.8	60.3	-	High	Audi	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-280-156-063	35.58	373.9	269	43.5	3.0	35.58	373.9	54.7	65	-	High	Audi	y
0-280-156-064	-	-	-	-	-	-	-	-	-	-	-	Audi 4-1.8l	-
0-280-156-065	26.85	282.2	203	43.5	3.0	26.85	282.2	41.3	49.1	EV12	High	Audi, VW 4-1.8l	-
0-280-156-070	26.85	282.2	203	43.5	3.0	26.85	282.2	41.3	49.1	-	High	Audi, VW	-
0-280-156-072	37.7	396.2	285	43.5	3.0	37.7	396.2	58	68.9	-	High	M B v6-3.2l	-
0-280-156-074	27.0	283.8	204.1	43.5	3.0	27	283.8	41.5	49.3	-	High	-	-
0-280-156-080	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	-	High	Opel	-
0-280-156-081	24.75	260.1	187.1	43.5	3.0	24.75	260.1	38.1	45.2	Top	High	-	-
0-280-156-083	14.25	149.8	107.7	43.5	3.0	14.25	149.8	21.9	26	-	High	VW	-
0-280-156-084	14.25	149.8	107.7	43.5	3.0	14.25	149.8	21.9	26	-	High	VW	-
0-280-156-094	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	-	-
0-280-156-103	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	Audi	-
0-280-156-104	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	Audi	-
0-280-156-105	16.75	176	126.6	43.5	3.0	16.75	176	25.8	30.6	-	High	Audi	-
0-280-156-108	16.25	170.8	122.8	43.5	3.0	16.25	170.8	25	29.7	-	High	Ford	-
0-280-156-123	20.25	212.8	153.1	43.5	3.0	20.25	212.8	31.2	37	EV6	High	-	-
0-280-156-123	28.18	-	213.0	43.5	3.0	-	-	-	-	EV6	High	-	Y
0-280-156-124	-	-	-	-	-	-	-	-	-	-	-	Ford 6-4.0l, 6-4.0l Turbo	-
0-280-156-127	41.5	436.2	313.7	43.5	3.0	41.5	436.2	63.8	75.8	Top USCAR	High	SVT Cobra	-
0-280-156-131	23.6	248	178.4	43.5	3.0	23.6	248	36.3	43.1	EV6	High	GM 3.6l	-
0-280-156-155	19.8	208.1	149.7	43.5	3.0	19.8	208.1	30.5	36.2	EV6	High	Ford 2.3l dohc	-
0-280-156-157	13.98	146.9	105.7	49.3	3.4	13.13	138	21.5	25.5	EV6	High	-	-
0-280-156-159	-	-	-	-	-	-	-	-	-	Top	-	Nissan	-
0-280-156-184	25.52	268.2	192.9	43.5	3.0	25.52	268.2	39.3	46.6	EV6	High	Ford 4.0l sohc	-
0-280-156-186	20.25	212.8	153.1	43.5	3.0	20.25	212.8	31.2	37	EV6	High	-	-
0-280-156-186	28.18	-	213.0	43.5	3.0	-	-	-	-	EV6	High	-	Y
0-280-156-188	-	-	-	-	-	-	-	-	-	-	-	KIA 4-1.5l	-
0-280-156-189	-	-	-	-	-	-	-	-	-	-	-	KIA 4-1.8l	-
0-280-156-190	-	-	-	-	-	-	-	-	-	-	-	KIA v6-2.5l	-
0-280-156-193	24.0	252.2	181.4	43.5	3.0	24	252.2	36.9	43.8	EV6	High	-	-
	Flow			Rating @		Flow @ 43.5 PSI / 3		.52 BSFC - Est. HP					Stan Weiss

Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	Bars		Duty Cycle		Feed	Impedance	Application	n-H
						lbs/hr	cc /min	80%	95%				
0-280-156-194	15.35	161.3	116	43.5	3.0	15.35	161.3	23.6	28	EV6	High	-	y
0-280-156-201	33.3	350	251.7	43.5	3.0	33.3	350	51.2	60.8	Top	High	-	-
0-280-156-203	19.8	208.1	149.7	43.5	3.0	19.8	208.1	30.5	36.2	EV6	High	Ford v8-4.6l	-
0-280-156-208	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	Top	High	-	-
0-280-156-300	34.0	357.3	257	43.5	3.0	34	357.3	52.3	62.1	EV6	High	GM 2.8l, 3.6l	-
0-280-156-304	51.6	542.3	390.1	55.1	3.8	45.85	481.9	79.4	94.3	-	High	-	-
0-280-156-937	19.8	208.1	149.7	43.5	3.0	19.8	208.1	30.5	36.2	Top	High	-	-
0-280-158-001	19.5	204.9	147.4	43.5	3.0	19.5	204.9	30	35.6	EV6	High	Ford v8-5.4l	-
0-280-158-003	23.6	248	178.4	43.5	3.0	23.6	248	36.3	43.1	EV6	High	Ford v8-5.4l	-
0-280-158-007	27.23	286.2	205.9	43.5	3.0	27.23	286.2	41.9	49.7	-	High	Nissan	-
0-280-158-013	20.57	216.2	155.5	43.5	3.0	20.57	216.2	31.6	37.6	-	High	Nissan	-
0-280-158-023	23.23	244.1	175.6	43.5	3.0	23.23	244.1	35.7	42.4	EV6	High	-	-
0-280-158-044	20.2	212.3	152.7	43.5	3.0	20.2	212.3	31.1	36.9	EV1	High	Ford v8-5.4l	-
0-280-158-056	25.15	264.3	190.1	43.5	3.0	25.15	264.3	38.7	45.9	EV6	High	Ford 4.0l	-
0-280-158-060	38.0	399.4	287.3	43.5	3.0	38	399.4	58.5	69.4	USCAR	-	-	y
0-280-158-064	11.8	124	89.25	43.5	3.0	11.8	124	18.2	21.6	EV6	High	-	-
0-280-158-075	24.0	252.2	181.4	43.5	3.0	24	252.2	36.9	43.8	EV6	High	Ford 3.0l	-
0-280-158-085	40.0	420.4	302.4	43.5	3.0	40	420.4	61.5	73.1	Top	High	-	-
0-280-159-731	9.15	96.21	69.22	43.5	3.0	9.155	96.21	14.1	16.7	-	High	-	-
0-280-159-732	9.15	96.21	69.22	43.5	3.0	9.155	96.21	14.1	16.7	-	High	-	-
0-280-410-144	41.3	434.1	312.2	43.5	3.0	41.3	434.1	63.5	75.5	-	-	-	-
0-437-502-003	-	-	-	-	-	-	-	-	-	-	-	Volvo 4-2.0l	-
0-437-502-004	-	-	-	-	-	-	-	-	-	-	-	Saab 4-2.0l, 4-2.0l Turbo	-
0-437-502-005	-	-	-	-	-	-	-	-	-	-	-	Peugeot 6-2.7l, Volvo v6-2.7l	-
0-437-502-006	-	-	-	-	-	-	-	-	-	-	-	BMW 4-1.8l	-
0-437-502-007	-	-	-	-	-	-	-	-	-	-	-	BMW 4-2.0l, Volvo 4-2.1l	-
0-437-502-010	-	-	-	-	-	-	-	-	-	-	-	M B 4-2.3l, 6-2.6l, 6-2.7l, 6-3.0l, 6-3.8l, 8-4.5l, 8-5.0l, 8-6.8l	-
0-437-502-012	-	-	-	-	-	-	-	-	-	-	-	Peugeot 4-2.2l, Saab 4-2.0l	-
0-437-502-013	-	-	-	-	-	-	-	-	-	-	-	Peugeot 6-2.7l, Porsche 4-2.0l, Volvo v6-2.7l, v6-2.8l	-
0-437-502-015	-	-	-	-	-	-	-	-	-	-	-	Audi 4-1.6l, 4-1.7l, 5-2.2l, 5-2.2l Turbo, BMW 2.0l, Porsche 4-2.0l, 4-2.0l Turbo, Volvo 4-2.1l, 4-2.3l, VW 4-1.5l, 4-1.6l, 4-1.7l, 4-1.8l, 5-2.2l	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application	n-H
0-437-502-018	-	-	-	-	-	-	-	-	-	-	-	Peugeot 4-2.0l	-

0-437-502-022	-	-	-	-	-	-	-	-	-	-	-	-	Peugeot 6-2.8l, Volvo v6-2.8l	-
0-437-502-023	-	-	-	-	-	-	-	-	-	-	-	-	Audi 4-1.8l, 5-2.2l, VW 4-1.5l, 4-1.6l, 4-1.7l, 4-1.8l, 5-2.2l	-
0-437-502-043	-	-	-	46.2	-	-	-	-	-	-	-	-	Audi 4-2.0l, 4-2.2l, 4-2.2l Turbo, 4-2.3l, Bentley, VW 4-2.0l	-
0-437-502-044	-	-	-	46.2	-	-	-	-	-	-	-	-	Audi 4-1.8l, Bentley	-
0-437-502-045	-	-	-	36.25	-	-	-	-	-	-	-	-	Audi 4-2.2l, 4-2.2l Turbo, Bentley, VW 4-1.8l, 4-2.2l	-
0-437-502-046	-	-	-	36.25	-	-	-	-	-	-	-	-	Bentley	-
0-437-502-047	-	-	-	-	-	-	-	-	-	-	-	-	Ferrari 8-3.0l, 8-3.2l, v12-4.8l, M B 4-2.3l, 6-2.6l, 6-2.7l, 6-3.0l, 6-3.8l, 8-4.5l, 8-5.0l, 8-6.8l	-
1-660-062-060	-	-	-	-	-	-	-	-	-	-	-	-	Holden 6-3.0l, Nissan 6-2.4l, 6-2.8l, 6-3.0l	-
1-660-362-001	-	-	-	-	-	-	-	-	-	-	-	-	Nissan 4-2.0l, v6-3.0l	-
1-660-362-028	-	-	-	-	-	-	-	-	-	-	-	-	Nissan 4-1.5l	-
B-280-214-912	175.0	1839	1323	45	3.1	172	1808	269	319	-	Low	-	-	
B-280-214-913	175.0	1839	1323	45	3.1	172	1808	269	319	-	Low	-	-	
B-280-410-144	41.3	434.1	312.2	43.5	3.0	41.3	434.1	63.5	75.5	-	-	-	-	
B-280-410-153	57.0	599.1	430.9	36.25	2.5	62.44	656.2	87.7	104	-	-	-	-	
B-280-410-153	76.0	798.8	574.6	72.5	5.0	58.87	618.7	116	138	-	-	-	-	
B-280-410-475	77.35	812.9	584.8	43.5	3.0	77.35	812.9	119	141	-	-	-	-	
B-280-412-911	76.0	798.8	574.6	36.25	2.5	83.25	875	116	138	-	-	-	-	
B-280-412-911	106.45	1118	804.7	72.5	5.0	82.46	866.6	163	194	-	-	-	-	
B-280-431-126	34.55	363.1	261.2	43.5	3.0	34.55	363.1	53.2	63.1	EV6	High	-	y	
B-280-431-127-07	34.55	363.1	261.2	43.5	3.0	34.55	363.1	53.2	63.1	EV6	High	-	y	
B-280-431-128	34.65	364.2	261.9	43.5	3.0	34.65	364.2	53.3	63.3	EV6	High	-	-	
B-280-431-128-04	48.19	506.5	364.3	43.5	3.0	48.19	506.5	74.1	88	EV6	High	-	y	
B-280-431-129-03	48.19	506.5	364.3	43.5	3.0	48.19	506.5	74.1	88	EV6	High	-	y	
B-280-431-130	65.23	685.6	493.1	43.5	3.0	65.23	685.6	100	119	EV6	High	-	y	
B-280-431-131-02	65.23	685.6	493.1	43.5	3.0	65.23	685.6	100	119	EV6	Low	-	y	
B-280-432-115	20.65	217	156.1	43.5	3.0	20.65	217	31.8	37.7	-	High	-	-	
B-280-434-499 /1	62.2	653.7	470.2	43.5	3.0	62.2	653.7	95.7	113	-	High	-	-	
B-280-434-499 01	87.04	914.8	658	43.5	3.0	87.04	914.8	133	159	EV6	High	-	y	
B-280-434-499 02	87.04	914.8	658	43.5	3.0	87.04	914.8	133	159	EV6	High	-	y	
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle						Stan Weiss 3
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application		n-H
B-280-436-038 /1	47.9	503.4	362.1	43.5	3.0	47.9	503.4	73.7	87.5	EV6	High	-	-	
B-280-436-038 /1	-	-	658	43.5	-	-	-	-	-	EV6	High	-	Y	
B-280-436-038 01	66.61	700.1	503.6	43.5	3.0	66.61	700.1	102	121	EV14	High	-	y	
B-280-436-038 /2	-	-	503.5	43.5	-	-	-	-	-	EV14	High	-	Y	

B-280-436-038 /3	-	-	387.3	43.5	-	-	-	-	-	-	EV14	High	-	Y
B-280-436-038 /4	-	-	387.3	43.5	-	-	-	-	-	-	EV14	High	-	Y
B-280-436-038 05	51.23	538.4	387.3	43.5	3.0	51.23	538.4	78.8	93.6	EV14	High	-	-	
B-280-436-038 06	51.23	538.4	387.3	43.5	3.0	51.23	538.4	78.8	93.6	EV14	High	-	-	
B-280-436-038 07	66.6	700	503.5	43.5	3.0	66.6	700	102	121	EV14	High	-	-	
B-280-436-038 08	66.6	700	503.5	43.5	3.0	66.6	700	102	121	EV14	High	-	-	
B-280-436-038 09	51.23	538.4	387.3	43.5	3.0	51.23	538.4	78.8	93.6	EV14	High	-	-	
B-280-436-038 10	51.23	538.4	387.3	43.5	3.0	51.23	538.4	78.8	93.6	EV14	High	-	-	
R-280-410-144	41.3	434.1	312.2	-	-	-	-	63.5	75.5	-	-	-	-	
R-280-411-911	80.0	840.8	604.8	43.5	3.0	80	840.8	123	146	-	-	-	-	
R-280-412-911	77.2	811.4	583.6	36.25	2.5	84.57	888.8	118	141	-	Low	-	-	
R-280-412-912	141.9	1491	1072	-	-	-	-	218	259	-	Low	-	-	

Bosch - Ford COPYRIGHT © 2002-2011 Stan Weiss — World Wide Enterprises													
Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Impedance	Application	
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%				
D5B	19.0	199.7	143.6	-	-	-	-	29.2	34.7	-	High	Ford 5.0, 4.6 V8, Mopar 3.9 V6, Jeep 4.0 I6, Jeep 5.2 V8	
F78E	19.0	199.7	143.6	-	-	-	-	29.2	34.7	-	High	Ford 5.0, 4.6 V8, GM 3800 V6, Mopar 3.9 V6, Mopar 5.2, 5.9 V8, Jeep 4.0 I6, Jeep 5.2 V8, BMW I-6	
D9B	21.0	220.7	158.8	-	-	-	-	32.3	38.4	-	High	Ford 5.0, 4.6, 5.8 V8, GM TPI 305/350, GM L98/LT1 350, Ford Truck 4.2	
F5DE	24.0	252.2	181.4	-	-	-	-	36.9	43.8	-	High	Ford 5.0, 4.6 V8 7.5l, Taurus 3.0, Mopar 5.2, 5.9 V8, Jeep 4.0 I6, Jeep 5.2 V8, BMW I6, BMW V8, BMW V12	
F65E	21.0	220.7	158.8	-	-	-	-	32.3	38.4	-	High	Ford 5.0, 4.6, 5.8 V8, GM TPI 305/350, GM L98/LT1 350, Ford Truck 4.2	
F6VE	19.0	199.7	143.6	43.5	3.0	19	199.7	29.2	34.7	-	High	Ford 5.0 5.8 4.6 v8	
FOTE-D9B	22.0	231.2	166.3	-	-	-	-	33.8	40.2	-	High	Range Rover, Vette	
FV6E-EV6	19.0	199.7	143.6	-	-	-	-	29.2	34.7	-	High	-	
XF1E	21.0	220.7	158.8	-	-	-	-	32.3	38.4	-	High	Ford V8	
XR3E	24.0	252.2	181.4	-	-	-	-	36.9	43.8	-	-	Ford DOHC 4.6, 5.4 V8, Mopar 4.7, 5.2, 5.9 V8	

Chrysler - Mopar COPYRIGHT © 2002-2011 Stan Weiss — World Wide Enterprises													
Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Impedance	Application	
	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%				
04854181 Blue	22.5	236.5	170.1	49.0	3.38	21.2	222.8	34.6	41.1	-	High	6-4.0l Jeep	
04891574	44.6	468.7	337.2	43.5	3.0	44.6	468.7	68.6	81.5	EV6	High	-	
33007127 Brown	21.0	220.7	158.8	39.0	2.69	22.18	233.1	32.3	38.4	-	High	6-4.0l Jeep	
4118661	-	-	-	-	-	-	-	-	-	-	-	6-3.3l, 6-3.8l	
4275312	27.0	283.8	204.1	55	3.79	24.01	252.4	41.5	49.3	EV1	-	4-2.2l Turbo	
4275985 -													

TBI	-	-	-	-	-	-	-	-	-	-	-	-	4-2.2l, v8-5.2l
4288276	-	-	-	-	-	-	-	-	-	-	EV1	-	4-2.5l
4300257 - TBI	-	-	-	-	-	-	-	-	-	-	-	-	4-2.2l, 4-2.5l
4306018	32.0	336.3	241.9	55	3.79	28.46	299.1	49.2	58.5	EV1	-	-	4-2.2l Turbo
4306024	27.0	283.8	204.1	55	3.79	24.01	252.4	41.5	49.3	EV1	-	-	4-2.2l Turbo
4307616	-	-	-	-	-	-	-	-	-	-	EV1	-	4-2.5l
4307618	-	-	-	-	-	-	-	-	-	-	EV1	-	4-2.5l
4307619	-	-	-	-	-	-	-	-	-	-	EV1	-	4-2.5l
4307620	-	-	-	-	-	-	-	-	-	-	EV1	-	4-2.5l
4397721	-	-	-	-	-	-	-	-	-	-	-	-	4-2.5l
4418118 - TBI	-	-	-	-	-	-	-	-	-	-	-	-	4-2.5l
4418213	33.25	349.5	251.4	55	3.79	29.57	310.8	51.2	60.7	EV1	Low	-	4-2.2l Turbo, 4-2.5l Turbo
4418258	33.25	349.5	251.4	55	3.79	29.57	310.8	51.2	60.7	EV1	Low	-	4-2.2l Turbo, 4-2.5l Turbo
4418474	27.0	283.8	204.1	55	3.79	24.01	252.4	41.5	49.3	EV1	-	-	4-2.2l Turbo
4418475	27.0	283.8	204.1	55	3.79	24.01	252.4	41.5	49.3	EV1	-	-	2.2l
4418505 TBI	-	-	-	-	-	-	-	-	-	-	-	-	v8-5.9l
4418538 - TBI	-	-	-	-	-	-	-	-	-	-	-	-	4-2.2l, 4-2.5l
4418602 TBI	-	-	-	-	-	-	-	-	-	-	-	-	v8-5.2l
4418604 TBI	-	-	-	-	-	-	-	-	-	-	-	-	v8-5.9l
4418614 TBI	-	-	-	-	-	-	-	-	-	-	-	-	v8-5.2l
4418661	-	-	-	-	-	-	-	-	-	-	-	-	v6-3.3l, v6-3.8l
4418673	-	-	-	-	-	-	-	-	-	-	-	-	4-2.2l, 4-2.5l
4418864 - TBI	-	-	-	-	-	-	-	-	-	-	-	-	4-2.2l, 4-2.5l
4418911 TBI	-	-	-	-	-	-	-	-	-	-	-	-	4-2.5l
4418924 - TBI	-	-	-	-	-	-	-	-	-	-	-	-	4-2.2l, 4-2.5l
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 5
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance		Application
4504322	33.0	346.8	249.5	55	3.79	29.35	308.4	50.8	60.3	EV1	Low	-	4-2.2l Turbo, 4-2.5l Turbo
4532586	52.0	546.5	393.1	55	3.79	46.25	486	80	95	-	-	-	4-2.5l
4554044	-	-	-	-	-	-	-	-	-	-	-	-	v6-3.8l
4554101 - TBI	-	-	-	-	-	-	-	-	-	-	-	-	4-2.2l, 4-2.5l
4554127	-	-	-	-	-	-	-	-	-	-	High	-	6-3.8l, 6-3.9l
4573062	48.5	509.7	366.7	43.5	3.0	48.5	509.7	74.6	88.6	-	High	-	-
4591085	-	-	-	-	-	-	-	-	-	-	-	-	v6-3.3l
4591306	-	-	-	-	-	-	-	-	-	-	-	-	v6-2.7l
4591308	-	-	-	-	-	-	-	-	-	-	-	-	v6-3.2l, v6-3.5l
4591657	-	-	-	-	-	-	-	-	-	-	-	-	v6-2.7l
4591658	-	-	-	-	-	-	-	-	-	-	-	-	v6-3.2l, v6-3.5l
4591756	-	-	-	-	-	-	-	-	-	-	-	-	v6-2.7l
4612402	-	-	-	-	-	-	-	-	-	-	-	-	6-3.3l, 6-3.8l
4612175	24	252.2	181.4	50	3.45	22.39	235.3	36.9	43.8	-	Low	-	6-3.3l, 6-3.8l
4612176	-	-	-	-	-	-	-	-	-	-	-	-	6-3.3l
4612177	-	-	-	-	-	-	-	-	-	-	High	-	v6-3.8l, 6-3.9l
4663376	-	-	-	-	-	-	-	-	-	-	-	-	4-2.0l, v6-3.3l
4669011	-	-	-	-	-	-	-	-	-	-	-	-	4-2.0l
4669471	-	-	-	-	-	-	-	-	-	-	-	-	4-2.0l
4669772	-	-	-	-	-	-	-	-	-	-	-	-	4-2.0l
4669938	-	-	-	-	-	-	-	-	-	-	-	-	4-2.4l
5227386	-	-	-	-	-	-	-	-	-	-	-	-	4-2.0l, 4-2.4l
5245344	-	-	-	-	-	-	-	-	-	-	-	-	10-8.0l
5277098	-	-	-	-	-	-	-	-	-	-	-	-	6-3.0l
5277470	33.3	350	251.7	43.5	3.0	33.3	350	51.2	60.8	EV1	High	-	v6-3.3l
5277739	-	-	-	-	-	-	-	-	-	-	-	-	4-2.0l, 4-2.4l
5277751	-	-	-	-	-	-	-	-	-	-	-	-	6-3.0l

5277757 5277895	34.0	357.3	257	55	3.79	30.24	317.8	52.3	62.1	EV1	Low	6-3.0l 4-2.2l, 4-2.5l, turbo
53003956 Dark Tan	21.0	220.7	158.8	39	2.69	22.18	233.1	32.3	38.4	-	-	6-4.0l Jeep
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle				Stan Weiss 5
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Imped ance	Application
53007232	-	-	-	-	-	-	-	-	-	-	-	4-2.5l
53007809	-	-	-	43.5	-	-	-	-	-	-	High	v8-5.2l
53008487 TBI	-	-	-	-	-	-	-	-	-	-	-	6-3.9l
53030262	24.6	258.5	186	39.0	2.69	25.98	273.1	37.8	44.9	-	High	v8-5.2l, v8-5.9l
53030343 Tan	21.0	220.7	158.8	39.0	2.69	22.18	233.1	32.3	38.4	-	-	6-4.0l Jeep
53030778 Grey	23.2	243.8	175.4	49.0	3.38	21.86	229.7	35.7	42.4	-	-	4-2.5l, 6-4.0l, v8-5.2l, v8-5.9l
53040003	-	-	-	-	-	-	-	-	-	-	-	10-8.0l
53041073	-	-	-	-	-	-	-	-	-	-	-	10-8.0l
MD15143	-	-	-	-	-	-	-	-	-	-	-	6-3.0l
MD15661	-	-	-	-	-	-	-	-	-	-	-	6-3.0l
MD111420	-	-	-	-	-	-	-	-	-	-	-	4-1.5l(Colt/Eagle/Mitsubishi)
MD111421	-	-	-	-	-	-	-	-	-	-	-	4-1.6l(Mitsubishi), 4-1.8l(Mitsubishi), 4- 2.0l(Mitsubishi), 6-3.0l(Mitsubishi)
MD111422	-	-	-	-	-	-	-	-	-	-	-	4-2.4l(Mitsubishi Pickup)
MD114131	-	-	-	-	-	-	-	-	-	-	-	6-3.0l
MD115076	-	-	-	-	-	-	-	-	-	-	-	4-2.0l(Eagle/Mitsubishi)
MD116218	-	-	-	-	-	-	-	-	-	EV1	-	6-3.0l
MD116821	-	-	-	-	-	-	-	-	-	-	-	4-1.6l(Mitsubishi), 4- 2.0l(Eagle/Mitsubishi)
MD127069	-	-	-	-	-	-	-	-	-	-	-	4-2.0l(Eagle/Mitsubishi)
MD132249	-	-	-	-	-	-	-	-	-	EV1	-	6-3.0l
MD141131	-	-	-	-	-	-	-	-	-	EV1	-	v6-3.0l
MD141263	-	-	-	-	-	-	-	-	-	-	-	4-1.6l(Colt/Eagle/Mitsubishi), 4- 1.8l(Colt/Eagle/Mitsubishi), 4- 2.0l(Colt/Mitsubishi), 6-3.0l, 6-3.0l Truck
MD151431	-	-	-	-	-	-	-	-	-	-	-	6-3.0l
MD156661	-	-	-	-	-	-	-	-	-	-	-	6-3.0l
MD156760	-	-	-	-	-	-	-	-	-	-	-	4-1.8l(Mitsubishi), 4-2.0l(Mitsubishi), 6- 3.0l SOHC, 6-3.0l Truck
MD157740	-	-	-	-	-	-	-	-	-	-	-	v6-3.0l, v6-3.3l
MD158484	-	-	-	-	-	-	-	-	-	-	-	v6-3.0l
MD158850	-	-	-	-	-	-	-	-	-	-	-	4-2.0l(Eagle/Mitsubishi)
MD158851	-	-	-	-	-	-	-	-	-	-	-	4-2.4l Truck
MD162524	-	-	-	-	-	-	-	-	-	-	-	4-1.5l(Colt/Eagle), v6-2.5l
MD162525	-	-	-	-	-	-	-	-	-	-	-	6-3.0l DOHC
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle				Stan Weiss 5
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Imped ance	Application
MD164888	-	-	-	-	-	-	-	-	-	-	-	6-3.0l Turbo
MD168410	-	-	-	-	-	-	-	-	-	-	-	v6-3.0l
MD169494	-	-	-	-	-	-	-	-	-	-	-	4-2.4l(Colt/Eagle/Mitsubishi)
MD175075	-	-	-	-	-	-	-	-	-	-	-	4-1.5l(Colt/Eagle/Mitsubishi)
MD175076	-	-	-	-	-	-	-	-	-	-	-	4-1.8l(Colt/Eagle/Mitsubishi)
MD175077	-	-	-	-	-	-	-	-	-	-	-	4-2.0l(Mitsubishi)
MD175078	-	-	-	-	-	-	-	-	-	-	-	4-2.4l(Mitsubishi)
MD186379	-	-	-	-	-	-	-	-	-	-	-	4-2.0l, 4-2.0l(Eagle/Mitsubishi)
MD189023	-	-	-	-	-	-	-	-	-	-	-	6-3.0l SOHC
MD189029	-	-	-	-	-	-	-	-	-	-	-	6-3.0l DOHC
MD193266	-	-	-	-	-	-	-	-	-	-	-	4-2.4l(Eagle/Mitsubishi)
MD319790	-	-	-	-	-	-	-	-	-	-	-	4-1.5l(Mitsubishi)
MD319791	-	-	-	-	-	-	-	-	-	-	-	v6-3.0l, 4-1.8l(Mitsubishi)
MD323733	-	-	-	-	-	-	-	-	-	-	-	4-2.4l(Eagle)
MD614036	-	-	-	-	-	-	-	-	-	-	-	4-2.6l
MD614102	-	-	-	-	-	-	-	-	-	-	-	4-2.6l
P4452204	35.0	367.9	264.6	55	3.79	31.13	327.1	53.8	63.9	-	-	Mopar Perferance

P4452803	30.0	315.3	226.8	55	3.79	26.68	280.4	46.2	54.8	-	-	Mopar Performance
P4452804	36.0	378.4	272.2	55	3.79	32.02	336.5	55.4	65.8	-	-	Mopar Performance
P4529495	42.0	441.4	317.5	55	3.79	37.35	392.6	64.6	76.7	-	-	Mopar Performance
P5249452	52.0	546.5	393.1	55	3.79	46.25	486	80	95	-	Low	Mopar Performance

Delphi

COPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Impedance	Application
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%			
17104487	50.0	525.5	378	43.5	3.0	50	525.5	76.9	91.3	EV1	High	-
17104988	75.0	788.3	567	43.5	3.0	75	788.3	115	137	-	low	-
17113738	50.0	525.5	378	43.5	3.0	50	525.5	76.9	91.3	EV1	High	-
17113739	37.95	398.9	286.9	43.5	3.0	37.95	398.9	58.4	69.3	Top	High	LS1 SUV
17113742	75.0	788.3	567	43.5	3.0	75	788.3	115	137	EV1	low	-
17113743	85.0	893.4	642.6	43.5	3.0	85	893.4	130	155	EV1	low	-
17113744	95.0	998.5	718.2	43.5	3.0	95	998.5	146	173	EV1	low	-
17113798	37.87	398	286.3	43.5	3.0	37.87	398	58.3	69.2	EV1	High	-
17113813	42.0	441.4	317.5	43.5	3.0	42	441.4	64.6	76.7	EV1	High	-
17113814	65.0	683.2	491.4	43.5	3.0	65	683.2	100	118	EV1	Low	-
17113841	55.0	578.1	415.8	43.5	3.0	55	578.1	84.6	100	EV1	Low	-
25176061	37.87	398	286.3	43.5	3.0	37.87	398	58.3	69.2	Top	High	LS1 SUV
25176061	43.77	460	330.9	58.0	4.0	37.91	398.4	67.3	80	Top	High	LS1
25178968	14.27	150	107.9	43.5	3.0	14.27	150	22	26.1	Top	High	-
25313185	23.3	244.9	176.1	43.5	3.0	23.3	244.9	35.8	42.6	Top	High	-
25317628	20.93	220	158.2	43.5	3.0	20.93	220	32.2	38.2	Top	High	-
25317669	18.08	190	136.7	43.5	3.0	18.08	190	27.8	33	Top	High	-
25320287	17.7	186	133.8	43.5	3.0	17.7	186	27.2	32.3	Top	High	-
25320288	20.55	216	155.4	43.5	3.0	20.55	216	31.6	37.5	Top	High	-
25322180	19.03	200	143.9	43.5	3.0	19.03	200	29.3	34.8	Top	High	-
25322971	19.03	200	143.9	43.5	3.0	19.03	200	29.3	34.8	Top	High	-
25322972	19.03	200	143.9	43.5	3.0	19.03	200	29.3	34.8	Top	High	-
25322974	20.93	220	158.2	43.5	3.0	20.93	220	32.2	38.2	Top	High	-
25324743	42.0	441.4	317.5	43.5	3.0	42	441.4	64.6	76.7	EV1	High	-
25324744	55.0	578.1	415.8	43.5	3.0	55	578.1	84.6	100	EV1	Low	-
-	29.5	310	223	43.5	3.0	29.5	310	45.4	53.9	-	Low	-
-	38.0	399.4	287.3	43.5	3.0	38	399.4	58.5	69.4	-	Low	-
-	42.0	441.4	317.5	43.5	3.0	42	441.4	64.6	76.7	-	Low	-
-	84.0	882.8	635	43.5	3.0	84	882.8	129	153	-	Low	-
-	165	1734	1247	43.5	3.0	165	1734	253	301	-	Low	-

Edelbrock

COPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Drive Circuit Type	Impedance	Application
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%				
3508	35	367.9	264.6	43.5	3.0	35	367.9	53.8	63.9	-	12v Saturated	High	-
3574	19	199.7	143.6	43.5	3.0	19	199.7	29.2	34.7	-	12v Saturated	High	-
3583	29	304.8	219.2	43.5	3.0	29	304.8	44.6	53	-	12v Saturated	High	-
3636	35	367.9	264.6	43.5	3.0	35	367.9	53.8	63.9	-	12v Saturated	High	-
3685	44	462.4	332.6	43.5	3.0	44	462.4	67.7	80.4	-	12v Saturated	High	-
3686	60	630.6	453.6	43.5	3.0	60	630.6	92.3	109	-	12v Saturated	High	Ford v8-5.0l, v8-4.6l, v8-5.4l
3687	60	630.6	453.6	43.5	3.0	60	630.6	92.3	109	-	12v Saturated	High	-
3853	29	304.8	219.2	43.5	3.0	29	304.8	44.6	53	-	12v Saturated	High	-

Ford

COPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Impedance	Application
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%			
1L2E-B5A	15.1	158.7	114.2	43.5	3.0	15.1	158.7	23.2	27.6	EV1	High	4.0l
1L2E-C5A	15.2	159.8	114.9	43.5	3.0	15.2	159.8	23.4	27.8	EV1	High	-
1L2E-D4A Orange Tip	15.61	164.1	118	43.5	3.0	15.61	164.1	24	28.5	EV6	High	v8-4.6l sohc
1L5E-C4A Blue Tip	13.33	140.1	100.8	43.5	3.0	13.33	140.1	20.5	24.4	EV6	High	4-2.3l. 3.0l
1L5G-BA	19.8	208.1	149.7	43.5	3.0	19.8	208.1	30.5	36.2	EV6	High	2.3l dohc
1L5Z-CA Blue Tip	13.33	140.1	100.8	43.5	3.0	13.33	140.1	20.5	24.4	EV6	High	4-2.3l. 3.0l
1S4E-A5A	-	-	-	-	-	-	-	-	-	EV6	High	2.0l sohc
1S7E-F7B	14.47	152.1	109.4	43.5	3.0	14.47	152.1	22.3	26.4	EV6	High	-
2L1E-B5A	19.05	200.2	144	43.5	3.0	19.05	200.2	29.3	34.8	EV6	High	v8-5.4l
2M2E-A7B	19.04	200.1	143.9	43.5	3.0	19.04	200.1	29.3	34.8	EV6	High	2.0l DOHC
2M5Z-AA	18.65	196	141	43.5	3.0	18.65	196	28.7	34.1	EV6	High	2.0l
3L1E-B5A	19.8	208.1	149.7	43.5	3.0	19.8	208.1	30.5	36.2	EV6	High	v8-4.6l
3L1Z-BA	19.8	208.1	149.7	43.5	3.0	19.8	208.1	30.5	36.2	-	High	v8-4.6l
3L3E-B5A	23.23	244.1	175.6	43.5	3.0	23.23	244.1	35.7	42.4	EV6	High	-
3L3Z-DA	23.6	248	178.4	43.5	3.0	23.6	248	36.3	43.1	EV6	High	v8-5.4l
4G7V-B5A	38.0	399.4	287.3	43.5	3.0	38	399.4	58.5	69.4	USCAR	-	-
4L2E-E1A	25.52	268.2	192.9	43.5	3.0	25.52	268.2	39.3	46.6	EV6	High	4.0l sohc
4L3E-B4C Light Gray Tip	21.33	224.2	161.3	43.5	3.0	21.33	224.2	32.8	39	EV6	High	v8-4.6l
4L3E-C5A Yellow Band	20.2	212.3	152.7	43.5	3.0	20.2	212.3	31.1	36.9	EV1	High	v8-5.4l
4M8Z-AA	24.0	252.2	181.4	43.5	3.0	24	252.2	36.9	43.8	EV6	High	-
5L2E-D1A	25.15	264.3	190.1	43.5	3.0	25.15	264.3	38.7	45.9	EV6	High	4.0l
5W7Z-AA	11.8	124	89.25	43.5	3.0	11.8	124	18.2	21.6	EV6	High	-
6E5E-A5B	24.0	252.2	181.4	43.5	3.0	24	252.2	36.9	43.8	EV6	High	3.0l
6E5Z-AA	24.0	252.2	181.4	43.5	3.0	24	252.2	36.9	43.8	-	High	3.0l
6F2E-B4A Light Green Tip	22.47	236.2	169.9	43.5	3.0	22.47	236.2	34.6	41.1	EV6	High	4.2l
EOSE-	46.1	484.5	348.5	33.35	2.3	52.65	553.4	70.9	84.2	-	Low	v8-5.0l
E0SE-9F593A1A TBI	-	-	-	-	-	-	-	-	-	-	-	v8-5.0l
E3DZ-9F593A	-	-	-	-	-	-	-	-	-	-	-	4-3.2l SHO
E3EE-9F593AA	14	147.1	105.8	-	-	-	-	21.5	25.6	-	-	4-1.6l
E3EE-9F593AB	14	147.1	105.8	30	2.07	16.86	177.2	21.5	25.6	-	-	4-2.3l, v8-5.0l
Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Impedance	Application
Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Impedance	Application
E3EE-9F593BA	14	147.1	105.8	-	-	-	-	21.5	25.6	-	Low	4-1.6l
E3VE-	37	388.9	279.7	40	2.76	38.58	405.5	56.9	67.6	-	Low	v6-3.8l
E3VE-9F593AA TBI	-	-	-	-	-	-	-	-	-	-	-	6-3.8l
E3VE-9F593-A2A	35.5	373.1	268.4	40	2.76	37.02	389.1	54.6	64.9	-	Low	v6-3.8l
E3VY-9F593A TBI	-	-	-	-	-	-	-	-	-	-	-	6-3.8l
E3ZE-9F593AA	30	315.3	226.8	37	2.55	32.53	341.9	46.2	54.8	EV1	Low	4-2.3l Turbo
E3ZE-9F593BA	30	315.3	226.8	37	2.55	32.53	341.9	46.2	54.8	EV1	Low	4-2.3l Turbo
E3ZE-9F593B1A	30	315.3	226.8	37	2.55	32.53	341.9	46.2	54.8	EV1	Low	4-2.3l Turbo
E43E-9F593A TBI	-	-	-	-	-	-	-	-	-	-	-	4-2.3l
E43E-9F593AC	55.5	583.3	419.6	-	-	-	-	85.4	101	-	Low	-
E4EE-9F593AA	14	147.1	105.8	-	-	-	-	21.5	25.6	EV1	Low	4-1.6l
E4EE-A1A	-	-	-	-	-	-	-	-	-	EV1	-	4-1.6l
E4EE-A2A	-	-	-	-	-	-	-	-	-	EV1	-	4-1.6l
E4EE-A3A	-	-	-	-	-	-	-	-	-	EV1	-	4-1.6l
E4EX-9F593A1A	23	241.7	173.9	-	-	-	-	35.4	42	EV1	Low	4-1.6l Turbo

E4EX-9F593AA	23.7	249.1	179.2	-	-	-	-	36.5	43.3	-	Low	4-1.6l Turbo
E4EX-9F593-BA	23.03	242	174.1	-	-	-	-	35.4	42.1	-	Low	4-1.6l Turbo
E4ZE-	52.4	550.7	396.1	32	2.21	61.09	642.1	80.6	95.7	-	Low	v8-5.0l HO
E4ZE-9F593-CA - TBI	51.95	546	392.7	-	-	-	-	79.9	94.9	-	Low	v8-5.0l
E4ZE-AA	30	315.3	226.8	37	2.55	32.53	341.9	46.2	54.8	-	Low	4-2.3l Turbo
E4ZE-A1A	30	315.3	226.8	37	2.55	32.53	341.9	46.2	54.8	EV1	Low	4-2.3l Turbo
E4ZE-A2A	30	315.3	226.8	37	2.55	32.53	341.9	46.2	54.8	EV1	Low	4-2.3l Turbo
E4ZE-A3A	30	315.3	226.8	37	2.55	32.53	341.9	46.2	54.8	EV1	Low	4-2.3l Turbo
E4ZE-B1A	30	315.3	226.8	37	2.55	32.53	341.9	46.2	54.8	EV1	Low	4-2.3l Turbo
E4ZZ-9F593C TBI	-	-	-	-	-	-	-	-	-	-	-	v8-5.0l
E53E-	64	672.6	483.8	-	-	-	-	98.5	116	-	High	4-2.3l
E53E-9F593AB TBI	-	-	-	-	-	-	-	-	-	-	-	4-2.5l
E53Z-9F593B TBI	-	-	-	-	-	-	-	-	-	-	-	4-2.3l, 4-2.5l
E57E-	19	199.7	143.6	33.35	2.3	21.7	228.1	29.2	34.7	-	High	v8-5.8l
E59E-9F593AA	14	147.1	105.8	30.45	2.1	16.73	175.9	21.5	25.6	EV1	High	4-2.3l, v8-5.0l Truck
		Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle			Stan Weiss 8
Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Impedance	Application
E59E-9F593AB	14	147.1	105.8	30.45	2.1	16.73	175.9	21.5	25.6	EV1	High	4-2.3l, v8-5.0l Truck
E59E-9F593A1A	14	147.1	105.8	30.45	2.1	16.73	175.9	21.5	25.6	EV1	High	4-2.3l
E59E-9F593A2A	14	147.1	105.8	30.45	2.1	16.73	175.9	21.5	25.6	EV1	High	4-2.3l
E59E-9F593A3A	14	147.1	105.8	30.45	2.1	16.73	175.9	21.5	25.6	EV1	High	4-2.3l
E59E-9F593A2B	14	147.1	105.8	30.45	2.1	16.73	175.9	21.5	25.6	EV1	High	4-2.3l
E5TE-	19	199.7	143.6	33.35	2.3	21.7	228.1	29.2	34.7	EV1	High	v8-5.0l
E5TZ-9F593A	-	-	-	-	-	-	-	-	-	EV1	-	4-3.0l, v6-3.8l, v8-5.0l
E5ZE-9F593AA	35	367.9	264.6	37	2.55	37.95	398.9	53.8	63.9	EV1	Low	4-2.3l Turbo
E5ZE-9F593AB	35	367.9	264.6	37	2.55	37.95	398.9	53.8	63.9	EV1	Low	4-2.3l Turbo
E5ZE-9F593A1A	35	367.9	264.6	37	2.55	37.95	398.9	53.8	63.9	EV1	Low	4-2.3l Turbo
E5ZE-9F593A2A	35	367.9	264.6	37	2.55	37.95	398.9	53.8	63.9	EV1	Low	4-2.3l Turbo
E5ZE-9F593A3A	35	367.9	264.6	37	2.55	37.95	398.9	53.8	63.9	EV1	Low	4-2.3l Turbo
E5ZE-9F593A2B	35	367.9	264.6	37	2.55	37.95	398.9	53.8	63.9	EV1	Low	4-2.3l Turbo
E6EE-9F593AB	19	199.7	143.6	40	2.76	19.81	208.2	29.2	34.7	EV1	Low	4-1.9l
E6EE-9F593A3B	19	199.7	143.6	40	2.76	19.81	208.2	29.2	34.7	EV1	Low	4-1.9l
E6EE-9F593A2A	19	199.7	143.6	40	2.76	19.81	208.2	29.2	34.7	EV1	Low	4-1.9l
E6EE-9F593A3A	19	199.7	143.6	40	2.76	19.81	208.2	29.2	34.7	EV1	Low	4-1.9l
E6EE-9F593A1B	19	199.7	143.6	40	2.76	19.81	208.2	29.2	34.7	EV1	Low	4-1.9l
E6EE-9F593A2B	19	199.7	143.6	40	2.76	19.81	208.2	29.2	34.7	EV1	Low	4-1.9l
E6EE-9F593A3B	19	199.7	143.6	40	2.76	19.81	208.2	29.2	34.7	EV1	Low	4-1.9l
E6TE-9F593AB	19	199.7	143.6	32	2.21	22.15	232.8	29.2	34.7	EV1	High	v8-5.0l HO
E6TE-9F593A1B	19	199.7	143.6	32	2.21	22.15	232.8	29.2	34.7	EV1	High	v8-5.0l HO
E6TE-9F593BB	19	199.7	143.6	32	2.21	22.15	232.8	29.2	34.7	EV1	High	v8-5.0l Truck
E6TE-A1B	19	199.7	143.6	32	2.21	22.15	232.8	29.2	34.7	EV1	High	v8-5.0l HO
E6TE-A2B	19	199.7	143.6	32	2.21	22.15	232.8	29.2	34.7	EV1	High	v8-5.0l HO
E6TE-A2B	18.5	194.4	139.9	43.5	3.0	18.5	194.4	28.5	33.8	EV1	High	v8-5.0l HO

E6TE-A3B	19	199.7	143.6	32	2.21	22.15	232.8	29.2	34.7	EV1	High	v8-5.0l HO
E6TE-A3B	18.5	194.4	139.9	43.5	3.0	18.5	194.4	28.5	33.8	EV1	High	v8-5.0l HO
E67C-9F593AB	14	147.1	105.8	33.35	2.3	15.99	168	21.5	25.6	-	High	2.9l, 3.0l
E67E-9F593BB	14	147.1	105.8	33.35	2.3	15.99	168	21.5	25.6	EV1	High	v8-5.0l
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle				Stan Weiss 8
Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Impedance	Application
E67E-9F593B1A	-	-	-	-	-	-	-	-	-	EV1	-	4-1.9l
E67E-9F593B1B	-	-	-	-	-	-	-	-	-	EV1	-	4-1.9l
E67E-B1A	14	147.1	105.8	33.35	2.3	15.99	168	21.5	25.6	EV1	High	4-2.3l
E67E-B1B	14	147.1	105.8	33.35	2.3	15.99	168	21.5	25.6	EV1	High	4-2.3l
E67E-B4B	14	147.1	105.8	33.35	2.3	15.99	168	21.5	25.6	EV1	High	4-2.3l
E67E-B4B	13.4	140.8	101.3	43.5	3.0	13.4	140.8	20.6	24.5	EV1	High	4-2.3l
E7EE-9F593CA TBI	-	-	-	-	-	-	-	-	-	-	-	4-1.9l, 4-2.3l
E7TE-	23	241.7	173.9	43	2.96	23.13	243.1	35.4	42	EV1	High	8-7.5l Truck
E8TE-	23	241.7	173.9	43	2.96	23.13	243.1	35.4	42	EV1	High	8-7.5l Truck
E92Z-9F593A	-	-	-	-	-	-	-	-	-	-	-	4-2.2l
E9BZ-9F593A	-	-	-	-	-	-	-	-	-	-	-	4-1.3l
E9DE-9F593AA TBI	-	-	-	-	-	-	-	-	-	-	-	4-2.5l
E9DZ-9F593A	-	-	-	-	-	-	-	-	-	-	-	6-3.0l SHO
E9SE-	30	315.3	226.8	43.5	3.0	30	315.3	46.2	54.8	EV1	High	v6-3.8l SC
EOSE-9F593-A1A	45.4	477.2	343.2	33.35	2.3	51.85	544.9	69.8	82.9	-	Low	-
F0BZ-9F593A	-	-	-	-	-	-	-	-	-	-	High	4-1.3l
F02Z-9F593A	-	-	-	-	-	-	-	-	-	-	High	4-2.2l Turbo
F02Z-9F593B	-	-	-	-	-	-	-	-	-	-	High	4-2.2l
F0CZ-9F593A	-	-	-	-	-	-	-	-	-	-	-	4-1.8l
F0SE-B5A	14.45	151.9	109.2	43.5	3.0	14.45	151.9	22.2	26.4	EV1	High	-
F0TE-9F593B1A	19	199.7	143.6	-	-	-	-	29.2	34.7	EV1	High	v8-4.6l
F0TE-C3A	19.75	207.6	149.3	43.5	3.0	19.75	207.6	30.4	36.1	EV1	High	-
F0TE-9F593D1A	19	199.7	143.6	-	-	-	-	29.2	34.7	EV1	High	v8-4.6l sohc
F0TE-9F593D1A	-	-	-	-	-	-	-	-	-	EV1	-	v6-3.8l
F0TE-9F593D5A	18.25	191.8	138	43.5	3.0	18.25	191.8	28.1	33.3	EV1	High	v8-4.6l
F0TE-D5B	20.0	210.2	151.2	43.5	3.0	20	210.2	30.8	36.5	EV1	High	-
F1SE-	31	325.8	234.4	43.5	3.0	31	325.8	47.7	56.6	EV1	High	v6-3.8l SC
F1SE-9F	29.6	311.1	223.8	-	-	-	-	45.5	54.1	EV1	High	-
F1SE-E1A	30	315.3	226.8	43.5	3.0	30	315.3	46.2	54.8	EV1	High	v6-3.8l SC
F1SE-9F593E1A	-	-	-	-	-	-	-	-	-	EV1	-	v6-3.8l SC
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle				Stan Weiss 8
Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Impedance	Application
F1TE-9F593D1A	-	-	-	-	-	-	-	-	-	EV1	-	v8-5.0l
F1TE-D5A	24.25	254.9	183.3	39.15	2.7	25.56	268.7	37.3	44.3	EV1	High	v8-5.0l, Truck 8-7.5l
F1TZ-	24	252.2	181.4	43.5	3.0	24	252.2	36.9	43.8	EV1	-	v8-5.0l Cobra
F1TZ-9F	23.7	249.1	179.2	-	-	-	-	36.5	43.3	EV1	-	-
F1ZE-9F	13.8	145	104.3	-	-	-	-	21.2	25.2	EV1	High	4-1.9l, 4-2.3l, v6-3.8l
F1ZE-B4C	14	147.1	105.8	-	-	-	-	21.5	25.6	EV1	High	4-1.9l, 4-2.3l
F2LE-	24	252.2	181.4	-	-	-	-	36.9	43.8	Ev1	High	v8-4.6l DOHC
F2LE-9F	23.7	249.1	179.2	-	-	-	-	36.5	43.3	Ev1	High	-
F2LE-9F593-B2A	24	252.2	181.4	-	-	-	-	36.9	43.8	EV1	High	v8-4.6l DOHC

F2TZ-9F593A F3DE-9F	24.93	262	188.5	-	-	-	-	38.4	45.5	EV1	-	4-2.5l
F3DE-9F593A2B	25	262.8	189	-	-	-	-	38.5	45.7	-	-	v6-3.0l Flex Fuel
F3DE-9F593A2C	-	-	-	-	-	-	-	-	-	-	-	v6-3.0l
F32Z-9F593A	-	-	-	-	-	-	-	-	-	-	-	4-2.0l
F32Z-9F593B	-	-	-	-	-	-	-	-	-	-	-	6-2.5l
F43E-9F593A2C	-	-	-	-	-	-	-	-	-	-	-	6-2.5l
F47E-9F593A2D	13.7	144	103.6	43.5	3.0	13.7	144	21.1	25	-	High	6-3.0l
F47E-B2A	14.47	152.1	109.4	43.5	3.0	14.47	152.1	22.3	26.4	EV1	High	3.0l
F4BZ-9F593A	-	-	-	-	-	-	-	-	-	-	-	4-1.3l
F4SE-9F593B5A	-	-	-	-	-	-	-	-	-	EV1	-	v6-3.8l SC
F5DZ-9F593-B5V	-	-	-	-	-	-	-	-	-	-	-	6-3.0l
F5RZ-9F593C	-	-	-	-	-	-	-	-	-	-	-	4-2.0l
F5TE-9F593B5A	-	-	-	-	-	-	-	-	-	-	-	v8-4.6l
F55E-	-	-	-	-	-	-	-	-	-	-	-	v8-4.6l
F55Y-9F593A	-	-	-	-	-	-	-	-	-	-	-	v8-4.6l
F6CE-9F593A5A	-	-	-	-	-	-	-	-	-	-	-	4-2.0l
F6CZ-AA	-	-	-	-	-	-	-	-	-	-	-	4-2.0l
F6DE-9F593A5A	-	-	-	-	-	-	-	-	-	-	-	v8-3.4l
F6RZ-AC	-	-	-	-	-	-	-	-	-	-	-	4-2.0l
F68F-9F593AB	-	-	-	-	-	-	-	-	-	-	-	4-2.0l
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle				Stan Weiss 8
Part Number	lbs/hr	cc/min	grams /min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Imped ance	Application
F68F-9F593AC	-	-	-	-	-	-	-	-	-	-	-	4-2.0l
F73E-9F593DA TBI	-	-	-	-	-	-	-	-	-	-	-	4-2.3l
F8CF-9F593ASA	-	-	-	-	-	-	-	-	-	-	-	4-2.0l
F8CZ-BB	-	-	-	-	-	-	-	-	-	-	-	4-2.0l
F87E-D2B	14.09	148.1	106.5	43.5	3.0	14.09	148.1	21.7	25.7	EV1	High	2.5l
FOTE-9F	18.75	197.1	141.7	-	-	-	-	28.8	34.3	-	-	-
XF2E-C4B Black Tip	19.42	204.1	146.8	43.5	3.0	19.42	204.1	29.9	35.5	EV6	High	2.5l, 3.0l, 3.8l
XL2E-C2A	13.55	142.4	102.4	43.5	3.0	13.55	142.4	20.8	24.8	EV6	High	v8-4.6l, 6.8l
XL5E-A2A	19.1	200.7	144.4	43.5	3.0	19.1	200.7	29.4	34.9	-	High	-
XL5E-B2A	19.1	200.7	144.4	43.5	3.0	19.1	200.7	29.4	34.9	-	High	-
XR3E-A4B	22.85	240.2	172.7	43.5	3.0	22.85	240.2	35.2	41.7	EV6	High	3.8l
XR3E-C5B	25.9	272.2	195.8	43.5	3.0	25.9	272.2	39.8	47.3	EV6	High	v8-4.6l, v8-5.4l
XS2E-A5B	19.8	208.1	149.7	43.5	3.0	19.8	208.1	30.5	36.2	EV6	High	V8-5.0l, 2.5l
XS4U-AA	18.42	193.6	139.3	43.5	3.0	18.42	193.6	28.3	33.7	EV1	High	2.0l
XW43-CA	22.09	232.2	167	43.5	3.0	22.09	232.2	34	40.4	EV6	High	3.9l
XW4E-A5C	14.5	152.4	109.6	43.5	3.0	14.5	152.4	22.3	26.5	EV6	High	3.0l
XW7E-A5B	20.38	214.2	154.1	43.5	3.0	20.38	214.2	31.4	37.2	EV6	High	v8-4.6l, 6.8l
YF1E-F4A Red Tip	17.14	180.1	129.6	43.5	3.0	17.14	180.1	26.4	31.3	EV6	High	3.0l
YF1E-G4B Light Blue Tip	25.9	272.2	195.8	43.5	3.0	25.9	272.2	39.8	47.3	EV6	High	3.0l
YR3E-A4A Yellow-Orange Tip	22.85	240.2	172.7	43.5	3.0	22.85	240.2	35.2	41.7	EV6	High	4.2l
YR3Z-AA	22.85	240.2	172.7	43.5	3.0	22.85	240.2	35.2	41.7	-	High	4.2l
FMS-M-9593-A302	24.0	252.2	181.4	39.15	2.7	25.3	265.9	36.9	43.8	EV1	High	Ford Motor Sport
FMS-M-9593-AA302	24.0	252.2	181.4	39.15	2.7	25.3	265.9	36.9	43.8	EV6	High	Ford Motor Sport
FMS-M-9593-B302	30.0	315.3	226.8	39.15	2.7	31.62	332.4	46.2	54.8	EV1	High	Ford Motor Sport
FMS-M-9593-C302	19.0	199.7	143.6	39.15	2.7	20.03	210.5	29.2	34.7	EV1	High	Ford Motor Sport
FMS-M-9593-D302 (Dark Blue - F7PU-A4A)	36.0	378.4	272.2	39.15	2.7	37.95	398.8	55.4	65.8	-	High	Ford Motor Sport
												Ford

FMS-M-9593-E302	150.0	1576	1134	39.15	2.7	158.1	1661	230	274	-	Low	Motor Sport
FMS-M-9593-E303	160.0	1681	1209	39.15	2.7	168.6	1772	246	292	EV1	Low	Ford Motor Sport
FMS-M-9593-F302	42.0	441.4	317.5	39.15	2.7	44.27	465.3	64.6	76.7	EV1	High	Ford Motor Sport
FMS-M-9593-G302	47.0	494	355.3	39.15	2.7	49.54	520.7	72.3	85.9	EV12	High	Ford Motor Sport
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle				Stan Weiss 8
Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Impedance	Application
FMS-M-9593-LU60	60.0	630.6	453.6	39.15	2.7	63.25	664.7	92.3	109	EV6	High	Ford Motor Sport
FMS-M-9593-LU80	80.0	840.8	604.8	39.15	2.7	84.33	886.3	123	146	EV6	High	Ford Motor Sport
FMS-M-9593-M23	23.0	241.7	173.9	39.15	2.7	24.24	254.8	35.4	42	EV6	High	Ford Motor Sport
FMS-M-9593-M31	30.0	315.3	226.8	39.15	2.7	31.62	332.4	46.2	54.8	-	High	Ford Motor Sport
FMS-M-9593-M39	39.0	409.9	294.8	39.15	2.7	41.11	432.1	60	71.3	EV6	High	Ford Motor Sport
FMS-M-9593-T46	34.0	357.3	257	39.15	2.7	35.84	376.7	52.3	62.1	EV6	High	Ford Motor Sport

Holley

 COPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Impedance	Application
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%			
522-140X	14.0	147.1	105.8	43	2.96	14.08	148	21.5	25.6	-	High	-
522-190X	19.0	199.7	143.6	43	2.96	19.11	200.8	29.2	34.7	-	High	-
522-240X	24.0	252.2	181.4	43	2.96	24.14	253.7	36.9	43.8	-	High	-
522-300X	30.0	315.3	226.8	43	2.96	30.17	317.1	46.2	54.8	-	High	-
522-360X	36.0	378.4	272.2	43	2.96	36.21	380.6	55.4	65.8	-	High	-
522-420X	42.0	441.4	317.5	43	2.96	42.24	444	64.6	76.7	-	High	-
522-500X	50.0	525.5	378	43	2.96	50.29	528.5	76.9	91.3	-	High	-
522-550X	55.0	578.1	415.8	43	2.96	55.32	581.4	84.6	100	-	Low	-
522-650X	65.0	683.2	491.4	43	2.96	65.38	687.1	100	118	-	Low	-
522-750X	75.0	788.3	567	43	2.96	75.43	792.8	115	137	-	Low	-
522-80	72.0	756.7	544.3	43	2.96	72.42	761.1	110	131	-	Low	-
522-850X	85.0	893.4	642.6	43	2.96	85.49	898.5	130	155	-	Low	-
522-950X	95.0	998.5	718.2	43	2.96	95.55	1004	146	173	-	Low	-

X in the Part Number = 1, 4, 6, or 8 and is equal to the number of injectors that are in the kit.

Honda - Acura

 COPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Impedance	Application
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%			
06164-PG7-A10	-	-	-	-	-	-	-	-	-	-	-	4-1.6l
06164-PK2-010	-	-	-	-	-	-	-	-	-	-	-	4-1.6l, 4-1.8l, 4-2.0l, 4-2.2l, 4-2.3l, 5-2.5l, 6-2.5l, 6-2.7l, 6-3.0l, 6-3.2l
06164-PM8-A00	-	-	-	-	-	-	-	-	-	-	-	4-1.5l, 4-1.8l
06164-P0A-000	-	-	-	-	-	-	-	-	-	-	-	4-2.2l, 6-2.5l, 6-2.7l, 6-3.0l, 6-3.2l

06164-P0F-000	-	-	-	-	-	-	-	-	-	-	-	-	4-2.2l
06164-P05-A02	-	-	-	-	-	-	-	-	-	-	-	-	4-1.5l, 4-1.6l
06164-P06-A0Z	-	-	-	-	-	-	-	-	-	-	-	-	4-1.5l, 4-1.6l
06164-P06-A02	-	-	-	-	-	-	-	-	-	-	-	-	4-1.7l, 4-1.8l

Lucas

COPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Drive Circuit	Type	Impedance	Application
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%					
D116XBA	47.57	500	359.6	43.5	3.0	47.57	500	73.2	86.9	Top	-	High	-	
D1540BA	26.65	280.1	201.5	43.5	3.0	26.65	280.1	41	48.7	Top	-	Low	-	
D1610BA	30.45	320	230.2	43.5	3.0	30.45	320	46.8	55.6	Top	-	Low	-	
D1650BA	20.03	210.5	151.4	43.5	3.0	20.03	210.5	30.8	36.6	Top	-	Low	-	
D1680BA	36.16	380	273.4	43.5	3.0	36.16	380	55.6	66.1	Top	-	Low	-	
D1720BA	29.75	312.7	224.9	43.5	3.0	29.75	312.7	45.8	54.4	EV1	-	High	-	
D3165BA	36.16	380	273.4	43.5	3.0	36.16	380	55.6	66.1	Top	-	High	-	
D3762FA	17.13	180	129.5	43.5	3.0	17.13	180	26.4	31.3	Top	-	High	-	
5107010	51.28	539	387.7	45	3.1	50.42	529.9	78.9	93.7	-	-	Low	-	
5201200	19.5	204.9	147.4	36.25	2.5	21.36	224.5	30	35.6	Top	Saturated	High	-	
5201201	19.5	204.9	147.4	43.5	3.0	19.5	204.9	30	35.6	Top	Saturated	High	-	
5202001	17.88	187.9	135.2	36.25	2.5	19.59	205.9	27.5	32.7	Top	Peak & Hold	Low	Porsche 914 1.8l	
5202003	17.9	188.1	135.3	36.25	2.5	19.61	206.1	27.5	32.7	Top	Saturated	High	-	
5202004	20.6	216.5	155.7	43.5	3.0	20.6	216.5	31.7	37.6	Top	Saturated	High	-	
5202005	15.7	165	118.7	43.5	3.0	15.7	165	24.2	28.7	Top	Saturated	High	-	
5203000	21.0	220.7	158.8	43.5	3.0	21	220.7	32.3	38.4	Top	Peak & Hold	Low	-	
5203002	37.27	391.7	281.8	43.5	3.0	37.27	391.7	57.3	68.1	-	-	High	-	
5204001	17.88	187.9	135.2	36.25	2.5	19.59	205.9	27.5	32.7	Top	Peak & Hold	Low	Fiat 2.0l	
5205000	26.5	278.5	200.3	43.5	3.0	26.5	278.5	40.8	48.4	Top	Peak & Hold	Low	-	
5205001	37.3	392	282	43.5	3.0	37.3	392	57.4	68.1	Top	Saturated	High	-	
5206001	20.0	210.2	151.2	36.25	2.5	21.91	230.3	30.8	36.5	Top	Ballasted	Low	-	
5206002	17.88	187.9	135.2	36.25	2.5	19.59	205.9	27.5	32.7	Top	Ballasted	Low	Toyota	
5206003	14.0	147.1	105.8	43.5	3.0	14	147.1	21.5	25.6	-	-	High	-	
5206004	24.73	259.9	187	36.25	2.5	27.09	284.7	38	45.2	Top	Ballasted	Low	300ZX	
5206005	19.5	204.9	147.4	36.25	2.5	21.36	224.5	30	35.6	Top	Peak & Hold	Low	-	
5207002	17.88	187.9	135.2	36.25	2.5	19.59	205.9	27.5	32.7	Top	Saturated	High	Chevy v8-5.0l	
5207002	23.9	251.2	180.7	43.5	3.0	23.9	251.2	36.8	43.7	-	-	High	-	
5207003	15.6	164	117.9	43.5	3.0	15.6	164	24	28.5	Top	Saturated	High	Buick v6-3.0l	
5207005	47.85	502.9	361.7	39.15	2.7	50.44	530.1	73.6	87.4	-	-	-	-	
5207006	30.73	323	232.3	39.15	2.7	32.39	340.4	47.3	56.1	Top	Peak & Hold	Low	Ford 2.3l Turbo	
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle			Drive Circuit			Stan Weiss 11
Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Type	Impedance	Application	
5207007	14.0	147.1	105.8	39.15	2.7	14.76	155.1	21.5	25.6	Top	Peak & Hold	Low	Ford 1.6l	
5207008	35.02	368.1	264.7	39.15	2.7	36.91	388	53.9	64	Top	Peak & Hold	Low	Ford 2.3l Turbo	
5207009	28.4	298.5	214.7	36.25	2.5	31.11	327	43.7	51.9	Top	Saturated	High	GM v6-3.8l	
5207010	40.2	422.5	303.9	39.15	2.7	42.37	445.4	61.8	73.4	Top	Peak & Hold	Low	-	
5207011	20.75	218.1	156.9	43.5	3.0	20.75	218.1	31.9	37.9	Top	Saturated	High	Chevrolet v8-5.7l	

5207013	19.12	201	144.5	39.15	2.7	20.15	211.8	29.4	34.9	Top	Saturated	High	Jeep 6-4.0l
5207600	36.05	378.9	272.5	39.15	2.7	38	399.4	55.5	65.9	Top	Peak & Hold	Low	-
5207601	47.85	502.9	361.7	39.15	2.7	50.44	530.1	73.6	87.4	Top	Peak & Hold	Low	-
5207602	51.38	540	388.4	39.15	2.7	54.16	569.2	79	93.9	Top	Peak & Hold	Low	-
5208001	17.88	187.9	135.2	36.25	2.5	19.59	205.9	27.5	32.7	Top	Peak & Hold	Low	Alfa 2.5l, 3.0l, Fiat 1.5l, Izuzu 2.0l, Nissan 200SX, 280ZX, 300ZX, Porsche 2.0l, Renault 1.6l, 1.7l, Rover 3.5l, Triumph 3.5l, VW 1.8l, 2.0l
5208003	17.88	187.9	135.2	36.25	2.5	19.59	205.9	27.5	32.7	Top	Peak & Hold	Low	Alfa, Triumph 2.0l
5208004	22.55	237	170.5	36.25	2.5	24.7	259.6	34.7	41.2	Top	Peak & Hold	Low	Ford 1.6l
5208005	22.55	237	170.5	36.25	2.5	24.7	259.6	34.7	41.2	Top	Peak & Hold	Low	Chrysler, BMW
5208006	15.6	164	117.9	36.25	2.5	17.09	179.6	24	28.5	Top	Saturated	High	Renault
5208007	17.88	187.9	135.2	36.25	2.5	19.59	205.9	27.5	32.7	Top	Ballasted	Low	BMW 325E
5208008	35.4	372.1	267.6	39.15	2.7	37.31	392.2	54.5	64.7	Top	Saturated	High	-
5208009	42.29	444.5	319.7	43.5	3.0	42.29	444.5	65.1	77.3	EV1	Saturated	High	-
5208010	51.4	540.2	388.6	43.5	3.0	51.4	540.2	79.1	93.9	Top	Peak & Hold	Low	-
5720A520	17.9	188.1	135.3	43.5	3.0	17.9	188.1	27.5	32.7	-	-	-	Chevy v8-5.0l
5720D570	17.9	188.1	135.3	43.5	3.0	17.9	188.1	27.5	32.7	-	-	-	Chevy v8-5.0l
5720D780	17.9	188.1	135.3	43.5	3.0	17.9	188.1	27.5	32.7	-	-	-	Chevy v8-5.0l
5720D810	17.9	188.1	135.3	43.5	3.0	17.9	188.1	27.5	32.7	-	-	-	Vette v8-5.7l
621002	19.8	208.1	149.7	43.5	3.0	19.8	208.1	30.5	36.2	-	-	High	-
621010	37.8	397.3	285.8	43.5	3.0	37.8	397.3	58.2	69.1	-	-	High	-
621015	17.85	187.6	134.9	36.25	2.5	19.55	205.5	27.5	32.6	-	Saturated	High	-
621016	15.6	164	117.9	43.5	3.0	15.6	164	24	28.5	-	-	-	-
621020	31.6	332.1	238.9	43.5	3.0	31.6	332.1	48.6	57.7	-	-	High	GM v6-3.8l
621022	23.9	251.2	180.7	43.5	3.0	23.9	251.2	36.8	43.7	-	-	High	-
621030	42.0	441.4	317.5	-	-	-	-	64.6	76.7	-	-	-	-
621031	42.3	444.6	319.8	43.5	3.0	42.3	444.6	65.1	77.3	-	EV1	High	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle			Drive Circuit		Stan Weiss 11
Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Type	Impedance	Application
621036	21.3	223.9	161	43.5	3.0	21.3	223.9	32.8	38.9	-	-	High	-
621037	37.25	391.5	281.6	43.5	3.0	37.25	391.5	57.3	68.1	-	-	High	-
621040	15.9	167.1	120.2	43.5	3.0	15.9	167.1	24.5	29	-	-	High	-
621046	20.0	210.2	151.2	43.5	3.0	20	210.2	30.8	36.5	-	-	High	-
621048	24.5	257.5	185.2	43.5	3.0	24.5	257.5	37.7	44.8	-	-	High	-
621050	25.75	270.6	194.7	43.5	3.0	25.75	270.6	39.6	47	-	-	High	-

MSD

COPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Drive Circuit		Impedance	Application
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%		Type			
2010	21.0	220.7	158.8	43.5	3.0	21	220.7	32.3	38.4	Top	12v Saturated	High	ZR-1 Corvette	
2011	26.0	273.3	196.6	43.5	3.0	26	273.3	40	47.5	Top	2/0.5A Peak & Hold	Low	GM Quad IV 2.3l DOHC	
2012	34.0	357.3	257	43.5	3.0	34	357.3	52.3	62.1	Top	2/0.5A Peak & Hold	Low	-	
2013	50.0	525.5	378	43.5	3.0	50	525.5	76.9	91.3	Top	12v Saturated	High	-	
2014	72.0	756.7	544.3	43.5	3.0	72	756.7	110	131	Top	4/1A Peak & Hold	Low	-	
2015	96.0	1009	725.7	43.5	3.0	96	1009	147	175	Top	4/1A Peak & Hold	Low	-	
2016	19.0	199.7	143.6	43.5	3.0	19	199.7	29.2	34.7	Top	12v Saturated	High	Ford 8-5.0l, GM 5.0l	
2017	22.0	231.2	166.3	43.5	3.0	22	231.2	33.8	40.2	Top	12v Saturated	High	Chevrolet	

2018	38.0	399.4	287.3	43.5	3.0	38	399.4	58.5	69.4	Top	12v Saturated	High	v8-5.7l
2019	24.0	252.2	181.4	43.5	3.0	24	252.2	36.9	43.8	Top	12v Saturated	High	Early LT-1
2030	60.0	630.6	453.6	43.5	3.0	60	630.6	92.3	109	Top	Saturated or Peak & Hold	-	-
2060	20.75	218.1	156.9	43.5	3.0	20.75	218.1	31.9	37.9	-	-	High	Honda
2061	25.7	270.1	194.3	43.5	3.0	25.7	270.1	39.5	47	-	-	Low	Honda
2062	33.7	354.2	254.8	43.5	3.0	33.7	354.2	51.8	61.6	-	-	Low	Honda
2063	49.5	520.2	374.2	43.5	3.0	49.5	520.2	76.2	90.4	-	-	High	Honda
2064	71.25	748.8	538.6	43.5	3.0	71.25	748.8	109	130	-	-	Low	Honda
2065	95.0	998.5	718.2	43.5	3.0	95	998.5	146	173	-	-	Low	Honda
2066	18.85	198.1	142.5	43.5	3.0	18.85	198.1	29	34.4	-	-	High	Honda
2067	21.7	228.1	164	43.5	3.0	21.7	228.1	33.4	39.6	-	-	High	Honda
2068	37.6	395.2	284.3	43.5	3.0	37.6	395.2	57.8	68.7	-	-	High	Honda
2069	23.8	250.1	179.9	43.5	3.0	23.8	250.1	36.6	43.5	-	-	High	Honda

Nippon Denso

 COPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Impedance	Application
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%			
195500-0474	18.08	190	136.7	43.5	3.0	18.08	190	27.8	33	Top	Low	-
195500-0610	62.8	660	474.8	43.5	3.0	62.8	660	96.6	114	Top	Low	-
195500-0730	13.5	141.9	102.1	43.5	3.0	13.5	141.9	20.8	24.7	Top	High	-
195500-0732	13.32	140	100.7	43.5	3.0	13.32	140	20.5	24.3	Top	High	-
195500-0830	65.65	690	496.3	43.5	3.0	65.65	690	101	119	Top	Low	-
195500-0900 Orange	64.7	680	489.1	-	-	-	-	99.5	118	Top	Low	84-85 RX-7
195500-1152	18.27	192	138.1	43.5	3.0	18.27	192	28.1	33.4	Top	High	-
195500-1280	21.88	230	165.4	43.5	3.0	21.88	230	33.7	40	Top	High	Ford 4-2.2l, Mercury 4-1.6l
195500-1300	28.35	298	214.3	43.5	3.0	28.35	298	43.6	51.8	Top	High	-
195500-1320	-	-	-	-	-	-	-	-	-	-	Low	-
195500-1330	17.88	187.9	135.2	43.5	3.0	17.88	187.9	27.5	32.7	Top	High	-
195500-1350 Red	43.77	460	330.9	-	-	-	-	67.3	80	-	Low	86-87 RX-7
195500-1350 Purple	43.77	460	330.9	-	-	-	-	67.3	80	-	High	88 RX-7 Turbo
195500-1370 Tan	52.33	550	395.6	-	-	-	-	80.5	95.6	-	Low	86-87 RX-7
195500-1370 Purple	52.33	550	395.6	-	-	-	-	80.5	95.6	-	-	88 RX-7 Turbo
195500-1650	28.55	300.1	215.8	37.0	2.55	30.96	325.4	43.9	52.2	-	-	Ford 4-2.2l Turbo
195500-1900	19.8	208.1	149.7	43.5	3.0	19.8	208.1	30.5	36.2	Top	High	-
195500-1960	21.5	226	162.5	43.5	3.0	21.5	226	33.1	39.3	Top	High	Ford 6-3.0l SHO
195500-1970 Navy Blue	19.5	204.9	147.4	37.0	2.55	21.14	222.2	30	35.6	Top	High	Ford 4-2.2l
195500-1980	20.35	213.9	153.8	43.5	3.0	20.35	213.9	31.3	37.2	Top	High	-
195500-2010 Red	43.77	460	330.9	-	-	-	-	67.3	80	Top	High	89-91 RX-7
195500-2020 Purple	52.33	550	395.6	44	3.03	52.03	546.9	80.5	95.6	Top	High	89-91 RX-7 Turbo
195500-2040	17.7	186	133.8	43.5	3.0	17.7	186	27.2	32.3	Top	High	-
195500-2110 Purple	11.4	119.8	86.23	37.0	2.55	12.36	129.9	17.5	20.8	Top	High	Ford 4-1.3l
195500-2120	-	-	-	43.5	-	-	-	-	-	-	High	-
195500-2130	34.25	360	258.9	43.5	3.0	34.25	360	52.7	62.6	Top	High	-
195500-2150	31.02	326	234.5	43.5	3.0	31.02	326	47.7	56.7	Top	High	Ford 4-2.2l Turbo
195500-2180	24.17	254	182.7	43.5	3.0	24.17	254	37.2	44.2	Top	High	-
195500-2190	19.98	210	151	43.5	3.0	19.98	210	30.7	36.5	Top	High	-
195500-2231	17.7	186	133.8	43.5	3.0	17.7	186	27.2	32.3	Top	High	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle				Stan Weiss 13
Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Impedance	Application
195500-2240	53.28	560	402.8	43.4	2.99	53.34	560.6	82	97.3	Side	High	-

195500-2310	-	-	-	43.5	-	-	-	-	-	-	High	-
195500-2460 Purple	56.14	590	424.4	43.4	2.99	56.2	590.7	86.4	102	Side	High	-
195500-2510	-	-	-	-	-	-	-	-	-	-	-	Colt/Eagle/Mitsubishi 4-2.4l
195500-2610	22.45	235.9	169.7	43.5	3.0	22.45	235.9	34.5	41	Top	Low	-
195500-2630	24.17	254	182.7	43.5	3.0	24.17	254	37.2	44.2	Top	High	-
195500-2660	-	-	-	-	-	-	-	-	-	-	-	Eagle/Mitsubishi 4- 2.4l
195500-3110	15.32	161	115.8	43.5	3.0	15.32	161	23.6	28	Top	High	-
195500-3310	24.35	255.9	184.1	43.5	3.0	24.35	255.9	37.5	44.5	Top	High	-
195500-3650	95.25	1001	720.1	43.5	3.0	95.25	1001	146	174	Top	Low	-
195500-4430	21.4	224.9	161.8	43.5	3.0	21.4	224.9	32.9	39.1	Top	High	-
195500-4450	40.43	424.9	305.6	43.5	3.0	40.43	424.9	62.2	73.9	Top	High	-
195500-5130	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-2.2l
195500-5160	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-2.0l, 4-2.2l
195500-5190	-	-	-	-	-	-	-	-	-	-	-	Toyota 6-3.0l, 6-4.0l Truck
195500-5220	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.6l, GEO 4-1.6l
195500-5250	-	-	-	-	-	-	-	-	-	-	-	Toyota 6-3.0l
195500-5410	-	-	-	-	-	-	-	-	-	-	-	Toyota 6-3.0l
195500-5440	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-2.4l
195500-5620	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.8l, GEO 4-1.8l
195500-5640	-	-	-	-	-	-	-	-	-	-	-	Toyota 6-3.0l
195500-5740	41.87	440.1	316.5	43.5	3.0	41.87	440.1	64.4	76.5	Top	High	-
195500-5800	41.87	440.1	316.5	43.5	3.0	41.87	440.1	64.4	76.5	Top	High	-
195500-7032	13.32	140	100.7	43.5	3.0	13.32	140	20.5	24.3	Top	High	-
195500-8900	68.5	719.9	517.9	43.5	3.0	68.5	719.9	105	125	Top	Low	-
195599-5351	-	-	-	-	-	-	-	-	-	-	-	Toyota 6-3.0l, 6-4.5l Truck
195599-5630	-	-	-	-	-	-	-	-	-	-	-	Toyota 6-3.0l
195599-5570	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.6l, GEO 4-1.6l
195599-5580	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-2.2l
195599-5590	-	-	-	-	-	-	-	-	-	-	-	Toyota 6-3.0l
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle				Stan Weiss 13
Part Number	lbs/hr	cc/min	grams /min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Imped ance	Application
195599-5630	-	-	-	-	-	-	-	-	-	-	-	Toyota 6-3.0l
23209-49015 Yellow	38.06	400	287.7	43.4	2.99	38.1	400.5	58.6	69.5	Side	High	Toyota
23209-49025 Ash	44.72	470	338.1	43.4	2.99	44.77	470.5	68.8	81.7	Side	High	Toyota
23209-49035 Orchid	50.43	530	381.2	43.4	2.99	50.49	530.6	77.6	92.1	Side	Low	Toyota
23209-79015 Black	43.29	455	327.3	43.4	2.99	43.34	455.5	66.6	79.1	Side	Low	Toyota
23209-79065 Red	52.33	550	395.6	43.4	2.99	52.39	550.6	80.5	95.6	Side	Low	Toyota
23250-46020 Yellow	38.06	400	287.7	43.4	2.99	38.1	400.5	58.6	69.5	Side	High	Toyota
23250-46040 Ash	44.72	470	338.1	43.4	2.99	44.77	470.5	68.8	81.7	Side	High	Toyota
23250-46060 Orchid	50.43	530	381.2	43.4	2.99	50.49	530.6	77.6	92.1	Side	Low	Toyota
23250-74090 Black	43.29	455	327.3	43.4	2.99	43.34	455.5	66.6	79.1	Side	Low	Toyota
23250-74150 Red	52.33	550	395.6	43.4	2.99	52.39	550.6	80.5	95.6	Side	Low	Toyota
35310-24000	-	-	-	-	-	-	-	-	-	-	-	Mitsubishi 4-1.5l
35310-24010	-	-	-	-	-	-	-	-	-	-	-	Mitsubishi 4-1.5l
Light Green	13.8	145	104.3	37.0	2.55	14.96	157.3	21.2	25.2	-	Low	Toyota
Green	13.8	145	104.3	37.0	2.55	14.96	157.3	21.2	25.2	-	Low	Toyota
Dark Blue	13.8	145	104.3	-	-	-	-	21.2	25.2	-	Low	Ford 4-1.6l
Gray	13.8	145	104.3	-	30.0	-	-	21.2	25.2	-	High	Ford 4-2.3l
Red / Dark Blue	14.75	155	111.5	42.0	2.9	15.01	157.8	22.7	26.9	-	High	Toyota
Violet	14.75	155	111.5	42.0	2.9	15.01	157.8	22.7	26.9	-	High	Toyota

Sky Blue	14.75	155	111.5	42.0	2.9	15.01	157.8	22.7	26.9	-	High	Toyota
Light Green	16.75	176	126.6	42.0	2.9	17.05	179.2	25.8	30.6	-	High	Toyota
Grey	16.75	176	126.6	42.0	2.9	17.05	179.2	25.8	30.6	-	High	Toyota
Dark Grey	17.3	181.8	130.8	37.0	2.55	18.76	197.1	26.6	31.6	-	Low	Toyota
Grey	17.3	181.8	130.8	37.0	2.55	18.76	197.1	26.6	31.6	-	Low	Toyota
Dark Grey	19.03	200	143.9	42.0	2.9	19.37	203.5	29.3	34.8	-	Low	Toyota
Beige	19.03	200	143.9	42.0	2.9	19.37	203.5	29.3	34.8	-	Low	Toyota
Orange	19.03	200	143.9	42.0	2.9	19.37	203.5	29.3	34.8	-	Low	Toyota
Brown	19.03	200	143.9	42.0	2.9	19.37	203.5	29.3	34.8	-	Low	Toyota
Pink	19.03	200	143.9	42.0	2.9	19.37	203.5	29.3	34.8	-	Low	Toyota
Dark Blue	19.03	200	143.9	42.0	2.9	19.37	203.5	29.3	34.8	-	High	Toyota
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle				Stan Weiss 13
Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Impedance	Application
Orange / Blue	19.03	200	143.9	42.0	2.9	19.37	203.5	29.3	34.8	-	High	Toyota
Brown	19.03	200	143.9	42.0	2.9	19.37	203.5	29.3	34.8	-	High	Toyota
Red	19.03	200	143.9	42.0	2.9	19.37	203.5	29.3	34.8	-	High	Toyota
Blue	20.0	210.2	151.2	37.0	2.55	21.69	227.9	30.8	36.5	-	Low	Toyota
Sky Blue	20.3	213.4	153.5	42.0	2.9	20.66	217.1	31.2	37.1	-	High	Toyota
Beige	20.25	212.8	153.1	42.0	2.9	20.61	216.6	31.2	37	-	High	Toyota
Yellow	20.25	212.8	153.1	42.0	2.9	20.61	216.6	31.2	37	-	High	Toyota
Yellow / Orange	23.8	250.1	179.9	42.0	2.9	24.22	254.6	36.6	43.5	-	Low	Toyota
Green	23.8	250.1	179.9	42.0	2.9	24.22	254.6	36.6	43.5	-	High	Toyota
Violet	23.8	250.1	179.9	42.0	2.9	24.22	254.6	36.6	43.5	-	High	Toyota
Brown	23.8	250.1	179.9	42.0	2.9	24.22	254.6	36.6	43.5	-	High	Toyota
Light Green	26.85	282.2	203	42.0	2.9	27.33	287.2	41.3	49.1	-	High	Toyota
Violet	26.85	282.2	203	42.0	2.9	27.33	287.2	41.3	49.1	-	High	Toyota
Yellow	28.05	294.8	212.1	37.0	2.55	30.41	319.7	43.2	51.2	-	Low	Toyota
Pink	28.05	294.8	212.1	37.0	2.55	30.41	319.7	43.2	51.2	-	Low	Toyota
Green	28.05	294.8	212.1	37.0	2.55	30.41	319.7	43.2	51.2	-	High	Toyota
Pink	30.0	315.3	226.8	42.0	2.9	30.53	320.9	46.2	54.8	-	High	Toyota
Light Green	30.0	315.3	226.8	42.0	2.9	30.53	320.9	46.2	54.8	-	High	Toyota
Red / Orange	34.75	365.2	262.7	37.0	2.55	37.68	396	53.5	63.5	-	Low	Toyota
Black	40.9	429.9	309.2	37.0	2.55	44.35	466.1	62.9	74.7	-	Low	Toyota

Nissan - Infiniti

COPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Impedance	Application
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%			
16021-03G15	-	-	-	-	-	-	-	-	-	Side	-	-
16021-12G00	-	-	-	-	-	-	-	-	-	Side	-	-
16021-41G00	-	-	-	-	-	-	-	-	-	Side	-	-
16021-69A05	-	-	-	-	-	-	-	-	-	Top	-	-
16021-78G00	-	-	-	-	-	-	-	-	-	Side	-	-
16021-84A00	-	-	-	-	-	-	-	-	-	Side	-	-
16021-84M05	-	-	-	-	-	-	-	-	-	Side	-	-
16021-89W00	-	-	-	-	-	-	-	-	-	Side	-	-
16600-AE060	-	-	-	-	-	-	-	-	-	Top	-	6-3.5l
16600-AX200	20.57	216.2	155.5	43.5	3.0	20.57	216.2	31.6	37.6	-	High	-
16600-F6610	-	-	-	-	-	-	-	-	-	Top	-	-
16600-RR543	52.8	554.9	399.2	-	-	-	-	81.2	96.5	Side	-	6-3.0l Twin Turbo
16600-RR544	70.4	739.9	532.2	-	-	-	-	108	128	Side	-	6-3.0l
16600-RR701	52.8	554.9	399.2	-	-	-	-	81.2	96.5	Side	-	6-3.0l Twin Turbo
16600-0Z800	-	-	-	-	-	-	-	-	-	Side	-	-
16600-01B00	-	-	-	-	-	-	-	-	-	Side	-	6-3.0l, 6-3.3l
16600-01B01	-	-	-	-	-	-	-	-	-	Side	-	6-3.0l, 6-3.3l
16600-01B10	-	-	-	-	-	-	-	-	-	Side	-	6-3.0l, 6-3.3l
16600-01P00	-	-	-	-	-	-	-	-	-	-	-	6-3.0l
16600-01Y00	-	-	-	-	-	-	-	-	-	-	-	4-1.8l
16600-01Y01	-	-	-	-	-	-	-	-	-	-	-	4-1.8l
16600-01Y03	-	-	-	-	-	-	-	-	-	-	-	4-1.8l
16600-01Y05	-	-	-	-	-	-	-	-	-	-	-	4-1.8l

16600-01Y10	-	-	-	-	-	-	-	-	-	-	-	-	4-1.8l
16600-01Y11	-	-	-	-	-	-	-	-	-	-	-	-	4-1.8l
16600-1S700	-	-	-	-	-	-	-	-	-	Side	-	-	-
16600-10Y00	-	-	-	-	-	-	-	-	-	-	-	-	4-2.0l, 6-3.0l
16600-10Y01	26.17	275	197.8	43.4	2.99	26.2	275.4	40.3	47.8	Side	High	-	-
16600-10Y05	-	-	-	-	-	-	-	-	-	Side	High	-	-
16600-16E00	-	-	-	-	-	-	-	-	-	Top	-	-	6-3.0l
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 14
Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Impedance	Application	
16600-16E05	-	-	-	-	-	-	-	-	-	-	-	-	6-3.0l
16600-16E10	-	-	-	-	-	-	-	-	-	-	-	-	6-3.0l
16600-16E12	-	-	-	-	-	-	-	-	-	-	-	-	6-3.0l
16600-16E15	-	-	-	-	-	-	-	-	-	Top	-	-	6-3.0l
16600-19P10	-	-	-	-	-	-	-	-	-	Top	-	-	-
16600-19P20	-	-	-	-	-	-	-	-	-	Top	-	-	6-3.0l
16600-19P22	-	-	-	-	-	-	-	-	-	Top	-	-	6-3.0l
16600-21P00	-	-	-	-	-	-	-	-	-	Top	-	-	6-3.0l Turbo
16600-21P10	-	-	-	-	-	-	-	-	-	Top	-	-	6-3.0l Turbo
16600-21P15	-	-	-	-	-	-	-	-	-	-	-	-	6-3.0l Turbo
16600-21U00	35.2	370	266.1	-	-	-	-	54.2	64.3	Side	-	-	6-3.0l 300ZX Twin Turbo
16600-21U01	31.9	335.3	241.2	-	-	-	-	49.1	58.3	Side	High	-	6-3.0l 300ZX Twin Turbo
16600-21U01	35.2	370	266.1	-	-	-	-	54.2	64.3	Side	High	-	6-3.0l 300ZX Twin Turbo
16600-21U01 Purple	39.0	409.9	294.8	42.67	2.94	39.38	413.9	60	71.3	Side	High	-	200SX SR20DET Turbo - Feedback SWR
16600-2Y905	-	-	-	-	-	-	-	-	-	-	-	-	6-3.5l
16600-2Y915	-	-	-	-	-	-	-	-	-	Top	-	-	-
16600-30P05	-	-	-	-	-	-	-	-	-	-	-	-	6-3.0l
16600-30P06	-	-	-	-	-	-	-	-	-	-	-	-	6-3.0l
16600-30P07	-	-	-	-	-	-	-	-	-	Top	-	-	6-3.0l
16600-30P08	-	-	-	-	-	-	-	-	-	Top	-	-	6-3.0l
16600-37M05	-	-	-	-	-	-	-	-	-	Top	-	-	-
16600-4Z800	-	-	-	-	-	-	-	-	-	Top	-	-	-
16600-40F10	-	-	-	-	-	-	-	-	-	-	-	-	4-2.4l
16600-40F15	-	-	-	-	-	-	-	-	-	-	-	-	4-2.4l
16600-40P05	-	-	-	-	-	-	-	-	-	-	-	-	6-3.0l 300ZX
16600-40P06	-	-	-	-	-	-	-	-	-	-	-	-	6-3.0l 300ZX
16600-40P07	31.9	335.3	241.2	-	-	-	-	49.1	58.3	Side	-	-	6-3.0l 300ZX Twin Turbo
16600-40P07	35.2	370	266.1	-	-	-	-	54.2	64.3	Side	-	-	6-3.0l 300ZX Twin Turbo
16600-40P08	31.9	335.3	241.2	-	-	-	-	49.1	58.3	Side	-	-	6-3.0l 300ZX Twin Turbo
16600-40P08	35.2	370	266.1	-	-	-	-	54.2	64.3	Side	-	-	6-3.0l 300ZX Twin Turbo
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 14
Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Impedance	Application	
16600-5E510	-	-	-	-	-	-	-	-	-	Side	-	-	4-2.4l
16600-5E511	-	-	-	-	-	-	-	-	-	Side	-	-	4-2.4l
16600-5L300	-	-	-	-	-	-	-	-	-	Top	-	-	-
16600-5M100	-	-	-	-	-	-	-	-	-	Top	-	-	-
16600-5S700	-	-	-	-	-	-	-	-	-	Side	-	-	-
16600-53F00	-	-	-	-	-	-	-	-	-	-	-	-	4-2.4l, 6-3.0l
16600-53F01	-	-	-	-	-	-	-	-	-	-	-	-	4-2.4l, 6-3.0l
16600-53J00	21.7	228.1	164	-	-	-	-	33.4	39.6	-	-	-	4-2.0l, 6-3.0l
16600-57Y00	-	-	-	-	-	-	-	-	-	-	-	-	4-1.6l
16600-57Y01	-	-	-	-	-	-	-	-	-	Top	-	-	-
16600-65E00	-	-	-	-	-	-	-	-	-	Top	-	-	-
16600-65E05	-	-	-	-	-	-	-	-	-	Top	-	-	-
16600-65E10	-	-	-	-	-	-	-	-	-	Top	-	-	-
16600-65E15	-	-	-	-	-	-	-	-	-	Top	-	-	-
16600-66U00	-	-	-	-	-	-	-	-	-	Top	-	-	-

16600-69U00	-	-	-	-	-	-	-	-	-	Side	-	-
16600-67U01	-	-	-	-	-	-	-	-	-	Side	-	-
16600-67U02	-	-	-	-	-	-	-	-	-	Side	-	-
16600-7E000	-	-	-	-	-	-	-	-	-	-	-	6-3.0l
16600-7E005	-	-	-	-	-	-	-	-	-	Top	-	6-3.0l
16600-7S000	27.23	286.2	205.9	43.5	3.0	27.23	286.2	41.9	49.7	Top	High	-
16600-7Y000	-	-	-	-	-	-	-	-	-	Top	-	6-3.5l
16600-72P00	-	-	-	-	-	-	-	-	-	Side	-	4-2.4l Truck
16600-72P10	-	-	-	-	-	-	-	-	-	Side	-	4-2.4l Truck
16600-8J010	-	-	-	-	-	-	-	-	-	Top	-	4-2.5l
16600-85E00	-	-	-	-	-	-	-	-	-	-	-	6-3.0l
16600-85E01	-	-	-	-	-	-	-	-	-	Top	-	6-3.0l
16600-85E05	-	-	-	-	-	-	-	-	-	-	-	6-3.0l
16600-85E06	-	-	-	-	-	-	-	-	-	Top	-	6-3.0l
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle				Stan Weiss 14
Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Impedance	Application
16600-86G00	-	-	-	-	-	-	-	-	-	Side	-	4-2.4l Truck
16600-86G10	-	-	-	-	-	-	-	-	-	-	-	4-2.4l Truck
16600-91F01 Brown	45.67	480	345.3	43.4	2.99	45.72	480.5	70.3	83.4	Side	High	-
16600-96E00	-	-	-	-	-	-	-	-	-	-	-	6-3.0l
16600-96E01	-	-	-	-	-	-	-	-	-	-	-	6-3.0l
16603-N4218	-	-	-	-	-	-	-	-	-	-	-	6-2.4l, 6-2.8l
16603-N4200	-	-	-	-	-	-	-	-	-	Top	Low	-
16603-N4201	-	-	-	-	-	-	-	-	-	Top	Low	-
16603-N4205	-	-	-	-	-	-	-	-	-	Top	Low	-
16603-N4218	-	-	-	-	-	-	-	-	-	Top	Low	-
16603-N4220	-	-	-	-	-	-	-	-	-	Top	Low	6-2.4l, 6-2.8l
16603-N4700	-	-	-	-	-	-	-	-	-	Top	-	6-2.8l
16603-N4710	-	-	-	-	-	-	-	-	-	Top	Low	6-2.8l
16603-N7600	-	-	-	-	-	-	-	-	-	Top	Low	6-2.4l, 6-2.8l
16603-N7610	-	-	-	-	-	-	-	-	-	Top	Low	4-2.2l, 6-2.4l, 6-2.8l
16603-N7611	-	-	-	-	-	-	-	-	-	Top	Low	4-2.0l, 6-2.4l, 6-2.8l
16603-N8801	-	-	-	-	-	-	-	-	-	Top	-	6-2.4l
16603-N8810	-	-	-	-	-	-	-	-	-	Top	-	6-2.4l
16603-N8812	-	-	-	-	-	-	-	-	-	Top	-	6-2.4l
16603-P8100	-	-	-	-	-	-	-	-	-	Top	-	4-2.0l, 6-2.4l
16603-P8110	-	-	-	-	-	-	-	-	-	Top	-	4-2.0l
16603-P8200	-	-	-	-	-	-	-	-	-	Top	-	4-2.0l, 6-2.4l
16603-P8210	-	-	-	-	-	-	-	-	-	Top	-	4-2.0l, 6-2.4l
16603-P9000	25.0	262.8	189	-	-	-	-	38.5	45.7	Top	-	6-2.8l 280ZX Turbo
16603-P9010	25.0	262.8	189	-	-	-	-	38.5	45.7	Top	-	6-2.8l 280ZX Turbo
16603-V0100	-	-	-	-	-	-	-	-	-	Top	-	6-2.8l
16603-V0101	-	-	-	-	-	-	-	-	-	Top	-	6-2.8l
16603-W5505	-	-	-	-	-	-	-	-	-	Top	-	6-2.4l, 6-2.8l
16603-W5515	-	-	-	-	-	-	-	-	-	Top	-	6-2.4l, 6-2.8l
16603-W5560	-	-	-	-	-	-	-	-	-	Top	-	6-2.8l
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle				Stan Weiss 14
Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Impedance	Application
16603-W5565	-	-	-	-	-	-	-	-	-	Top	-	6-2.8l
16603-Y8000	-	-	-	-	-	-	-	-	-	Top	-	6-2.8l
16603-Y8005	-	-	-	-	-	-	-	-	-	Top	-	6-2.4l
16603-Y8006	-	-	-	-	-	-	-	-	-	Top	-	6-2.8l
16603-Y8008	-	-	-	-	-	-	-	-	-	Top	-	6-2.8l
16603-Y8010	-	-	-	-	-	-	-	-	-	Top	-	6-2.8l
16603-Y8015	-	-	-	-	-	-	-	-	-	Top	-	6-2.4l, 6-2.8l
16603-Y8016	-	-	-	-	-	-	-	-	-	Top	-	6-2.8l
16603-Y8018	-	-	-	-	-	-	-	-	-	Top	-	6-2.8l
16603-01P00	-	-	-	-	-	-	-	-	-	Top	-	6-3.0l
16603-01P05	-	-	-	-	-	-	-	-	-	Top	-	6-3.0l
16603-01P10	-	-	-	-	-	-	-	-	-	Top	-	6-3.0l

16603-01P15	-	-	-	-	-	-	-	-	-	Top	-	6-3.0l
16603-02P00	25.0	262.8	189	-	-	-	-	38.5	45.7	Top	-	6-3.0l 300ZX Turbo
16603-02P10	25.0	262.8	189	-	-	-	-	38.5	45.7	Top	-	6-3.0l 300ZX Turbo
16603-04P10	-	-	-	-	-	-	-	-	-	Top	-	-
16603-17M00	-	-	-	-	-	-	-	-	-	Top	-	4-1.5l Turbo
16603-18F01	-	-	-	-	-	-	-	-	-	Top	-	4-1.8l 200SX Turbo
16603-18F02	-	-	-	-	-	-	-	-	-	-	-	4-1.8l 200SX Turbo
16603-18F11	-	-	-	-	-	-	-	-	-	-	-	4-1.8l 200SX Turbo
16603-18F12	-	-	-	-	-	-	-	-	-	-	-	4-1.8l 200SX Turbo
16611-AA100 Ash	46.62	490	352.4	43.4	2.99	46.67	490.5	71.7	85.2	Side	High	-
16611-AA230 Yellow	48.05	505	363.3	43.4	2.99	48.11	505.6	73.9	87.8	Side	High	-
16611-AA350	-	-	-	-	-	-	-	-	-	Top	-	-
16611-AA370 Yellow	54.71	575	413.6	43.4	2.99	54.77	575.7	84.2	100	Side	High	-
A6603-P8100	-	-	-	-	-	-	-	-	-	Top	-	4-2.0l, 4-2.2l, 6-2.4l, 6-2.8l
A6603-P8110	-	-	-	-	-	-	-	-	-	Top	-	4-2.0l, 4-2.2l
A6603-P8200	-	-	-	-	-	-	-	-	-	Top	-	4-2.0l, 4-2.2l, 6-2.4l, 6-2.8l
A6603-P8210	-	-	-	-	-	-	-	-	-	Top	-	4-2.0l, 4-2.2l

RC Engineering

COPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		52 BSFC - Est. HP Duty Cycle		Feed	Drive Circuit Type	Impedance	Application
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%				
PL2-0155	15	157.7	113.4	43.5	3.0	15	157.7	23.1	27.4	Top	4\1.5A Peak & Hold	Low	-
PL2-0195	19	199.7	143.6	43.5	3.0	19	199.7	29.2	34.7	Top	4\1.5A Peak & Hold	Low	-
PL2-0250	24	252.2	181.4	43.5	3.0	24	252.2	36.9	43.8	Top	4\1.5A Peak & Hold	Low	-
PL2-0270	26	273.3	196.6	43.5	3.0	26	273.3	40	47.5	Top	4\1.5A Peak & Hold	Low	-
PL2-0320	30	315.3	226.8	43.5	3.0	30	315.3	46.2	54.8	Top	4\1.5A Peak & Hold	Low	-
PL2-0370	35	367.9	264.6	43.5	3.0	35	367.9	53.8	63.9	Top	4\1.5A Peak & Hold	Low	-
PL4-0210	20	210.2	151.2	43.5	3.0	20	210.2	30.8	36.5	Top	4\1.5A Peak & Hold	Low	-
PL4-0750	71	746.2	536.8	43.5	3.0	71	746.2	109	129	Top	4\1.5A Peak & Hold	Low	-
PL4-0750D	71	746.2	536.8	43.5	3.0	71	746.2	109	129	Top	4\1.5A Peak & Hold	Low	-
PL4-0750H	71	746.2	536.8	43.5	3.0	71	746.2	109	129	Top	4\1.5A Peak & Hold	Low	-
PL4-1000	95	998.5	718.2	43.5	3.0	95	998.5	146	173	Top	4\1.5A Peak & Hold	Low	-
PL4-1000D	95	998.5	718.2	43.5	3.0	95	998.5	146	173	Top	4\1.5A Peak & Hold	Low	-
PL4-1000H	95	998.5	718.2	43.5	3.0	95	998.5	146	173	Top	4\1.5A Peak & Hold	Low	-
PL4-1200	114	1198	861.8	55	3.79	101.3	1065	175	208	Top	4\1.5A Peak & Hold	Low	-

PL4-1200D	114	1198	861.8	55	3.79	101.3	1065	175	208	Top	4\1.5A Peak & Hold	Low	-
PL4-1200H	114	1198	861.8	55	3.79	101.3	1065	175	208	Top	4\1.5A Peak & Hold	Low	-
PL6-0250	24	252.2	181.4	43.5	3.0	24	252.2	36.9	43.8	-	4\1.5A Peak & Hold	Low	-
PL8-0550	52	546.5	393.1	43.5	3.0	52	546.5	80	95	-	4\1.5A Peak & Hold	Low	-
PL9-0225	21	220.7	158.8	43.5	3.0	21	220.7	32.3	38.4	Top	4\1.5A Peak & Hold	Low	-
PL9-0550	52	546.5	393.1	43.5	3.0	52	546.5	80	95	Top	4\1.5A Peak & Hold	Low	-
PL9-0660	63	662.1	476.3	43.5	3.0	63	662.1	96.9	115	Top	4\1.5A Peak & Hold	Low	-
PL9-1200	104	1093	786.2	43.5	3.0	104	1093	160	190	Top	4\1.5A Peak & Hold	Low	-
PL9-1200	114	1198	861.8	55	3.79	101.3	1065	175	208	Top	4\1.5A Peak & Hold	Low	-
PB2-1600	152	1597	1149	43.5	3.0	152	1597	233	277	Top	2.5\1A Peak & Hold	Low	-
SL-310D	19	199.7	143.6	43.5	3.0	19	199.7	29.2	34.7	Top	Saturated	High	-
SL2-0195	19	199.7	143.6	43.5	3.0	19	199.7	29.2	34.7	-	Saturated	High	-
SL2-0240	23	241.7	173.9	43.5	3.0	23	241.7	35.4	42	-	Saturated	High	-
SL2-0240	30	315.3	226.8	43.5	3.0	30	315.3	46.2	54.8	-	Saturated	High	-
SL2-0310D	30	315.3	226.8	43.5	3.0	30	315.3	46.2	54.8	-	Saturated	High	-
SL2-0370	35	367.9	264.6	43.5	3.0	35	367.9	53.8	63.9	-	Saturated	High	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle			Drive Circuit		Stan Weiss 15
Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Type	Impedance	Application
SL4-0205	20	210.2	151.2	43.5	3.0	20	210.2	30.8	36.5	-	Saturated	High	-
SL4-0225	21	220.7	158.8	43.5	3.0	21	220.7	32.3	38.4	-	Saturated	High	-
SL4-0270	26	273.3	196.6	43.5	3.0	26	273.3	40	47.5	-	Saturated	High	-
SL4-0370	35	367.9	264.6	43.5	3.0	35	367.9	53.8	63.9	-	Saturated	High	-
SL4-0370H	35	367.9	264.6	43.5	3.0	35	367.9	53.8	63.9	-	Saturated	High	-
SL4-0440	42	441.4	317.5	43.5	3.0	42	441.4	64.6	76.7	-	Saturated	High	-
SL4-0550	52	546.5	393.1	43.5	3.0	52	546.5	80	95	-	Saturated	High	-
SL4-0550	52	546.5	393.1	43.5	3.0	52	546.5	80	95	-	Saturated	High	-
SL4-0750D	71	746.2	536.8	43.5	3.0	71	746.2	109	129	-	Saturated	High	-
SL4-0750H	71	746.2	536.8	43.5	3.0	71	746.2	109	129	-	Saturated	High	-
SL4-0750H	71	746.2	536.8	43.5	3.0	71	746.2	109	129	-	Saturated	High	-
SL9-0270	26	273.3	196.6	43.5	3.0	26	273.3	40	47.5	-	Saturated	High	-
SL9-0310	30	315.3	226.8	43.5	3.0	30	315.3	46.2	54.8	-	Saturated	High	-
SL9-0440	42	441.4	317.5	43.5	3.0	42	441.4	64.6	76.7	-	Saturated	High	Honda Civic/CRX, Acura Integra
SL9-0550	52	546.5	393.1	43.5	3.0	52	546.5	80	95	-	Saturated	High	-
SLG-0440	42	441.4	317.5	43.5	3.0	42	441.4	64.6	76.7	-	Saturated	High	-
SDM-0370	35	367.9	264.6	43.5	3.0	35	367.9	53.8	63.9	-	Saturated	High	-
SM2-0310	29.52	310.3	223.2	43.5	3.0	29.52	310.3	45.4	53.9	-	Saturated	High	-
SM2-0370	35.24	370.4	266.4	43.5	3.0	35.24	370.4	54.2	64.4	-	Saturated	High	-
SM2-0450	42.86	450.5	324	43.5	3.0	42.86	450.5	65.9	78.3	-	Saturated	High	-

Rochester / GMCOPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Flow		Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle							
Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Impedance	Application	
1606771	38	399.4	287.3	-	-	-	-	58.5	69.4	-	-	Cadillac v8-8.2l - Feedback Gary Kosier	

1607247	38	399.4	287.3	-	-	-	-	58.5	69.4	-	-	Low	Cadillac v8-5.7l, v8-7.0l
5233785	-	-	-	-	-	-	-	-	-	-	-	-	Chevy Truck 2.0l, 2.5l
5234395	-	-	-	-	-	-	-	-	-	-	-	-	Chevy 2.0l, 2.5l
5235008	-	-	-	-	-	-	-	-	-	-	-	-	Buick v6-3.3l
5235027	18.65	196	141	43.5	3.0	18.65	196	28.7	34.1	-	High	-	-
5235036	-	-	-	43.5	-	-	-	-	-	-	High	-	-
5235041	27.8	292.2	210.2	43.5	3.0	27.8	292.2	42.8	50.8	-	Low	-	-
5235047	19.3	202.8	145.9	43.5	3.0	19.3	202.8	29.7	35.3	-	High	-	Chevy v8-5.0l
5235130	-	-	-	-	-	-	-	-	-	-	Low	-	Chevy Truck v6-3.1l
5235136	15.22	160	115.1	46	3.17	14.8	155.6	23.4	27.8	EV1	-	-	Chevy v6-2.8l, v6-3.1l, Buick v6-2.8l, v6-3.3l
5235203	-	-	-	-	-	-	-	-	-	-	Low	-	Chevy Truck v6-4.3l
5235206	-	-	-	-	-	-	-	-	-	-	Low	-	Chevy Truck v8-5.7l
5235210	14.65	154	110.8	43.5	3.0	14.65	154	22.5	26.8	-	High	-	Cadillac/Chevy v6-2.8l
5235211	21.6	227	163.3	43.5	3.0	21.6	227	33.2	39.5	-	High	-	Vette v8-5.7l
5235236	32.25	338.9	243.8	-	-	-	-	49.6	58.9	-	Low	-	Olds 2.3l
5235261	-	-	-	-	-	-	-	-	-	-	-	-	Cadillac v8-4.1l
5235267	-	-	-	-	-	-	-	-	-	-	-	-	Chevy 2.0l, 2.5l
5235274	-	-	-	-	-	-	-	-	-	-	-	-	Cadillac v8-4.5l, GEO
5235279	-	-	-	-	-	-	-	-	-	-	Low	-	Chevy Truck v8-5.0l
5235284	-	-	-	-	-	-	-	-	-	-	Low	-	Chevy 2.5l
5235301	20.45	214.9	154.6	-	-	-	-	31.5	37.4	EV1	High	-	GM v8-5.0l
5235302	20.45	214.9	154.6	-	-	-	-	31.5	37.4	-	High	-	v8-5.7l Truck
5235302	21.6	227	163.3	43.5	3.0	21.6	227	33.2	39.5	-	High	-	Vette v8-5.7l
5235348	-	-	-	-	-	-	-	-	-	-	-	-	Buick v6-3.0l
5235357	21.7	228.1	164	43.5	3.0	21.7	228.1	33.4	39.6	-	High	-	Vette v8-5.7l LT5
5235366	21.7	228.1	164	43.5	3.0	21.7	228.1	33.4	39.6	-	High	-	Vette v8-5.7l LT5
5235367	-	-	-	-	-	-	-	-	-	-	-	-	Buick v6-3.3l
5235401	-	-	-	-	-	-	-	-	-	-	Low	-	Chevy Truck v8-6.0l, v8-7.0l
5235434	20.45	214.9	154.6	-	-	-	-	31.5	37.4	EV1	High	-	Chevy v8-5.0l
		Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle				Stan Weiss 16
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance		Application
5235435	20.45	214.9	154.6	-	-	-	-	31.5	37.4	EV1	High	-	Chevy v8-5.0l
5235436	20.45	214.9	154.6	43.5	3.0	20.45	214.9	31.5	37.4	Top	High	-	Chevy Truck v8-5.7l
5235437	20.45	214.9	154.6	-	-	-	-	31.5	37.4	Top	High	-	Chevy Truck v8-5.7l
5235451	21.7	228.1	164	43.5	3.0	21.7	228.1	33.4	39.6	-	High	-	Cadillac v8-4.5l
5235484	-	-	-	-	-	-	-	-	-	-	Low	-	Chevy 2.5l
5287350	-	-	-	-	-	-	-	-	-	-	-	-	Cadillac v8-5.7l, 8-7.0l, 8-8.2l
10026723	-	-	-	-	-	-	-	-	-	EV1	-	-	Buick/Pontiac 4-1.8l Turbo
10031208	-	-	-	-	-	-	-	-	-	EV1	-	-	Buick 4-1.8l Turbo
10040430	-	-	-	-	-	-	-	-	-	EV1	-	-	Buick/Pontiac 4-2.0l Turbo
10108480	-	-	-	-	-	-	-	-	-	EV1	-	-	Chevy /Pontiac v8-5.0l
10108481	-	-	-	-	-	-	-	-	-	EV1	-	-	Chevy /vette/Pontiac v8-5.7l
12456154	26.2	275.4	198.1	58	4.0	22.69	238.5	40.3	47.9	-	-	-	LS1
12482704	28.6	300.6	216.2	58	4.0	24.77	260.3	44	52.3	-	-	-	LS6
12533952	28.6	300.6	216.2	58	4.0	24.77	260.3	44	52.3	-	-	-	LSx
12555894	26	273.3	196.6	43.5	3.0	26	273.3	40	47.5	EV1	High	-	LS1
12561462	28.6	300.6	216.2	58	4.0	24.77	260.3	44	52.3	-	-	-	LSx
12586551	19.61	206.1	148.2	43.5	3.0	19.61	206.1	30.2	35.8	-	High	-	Chevy v6-3.8l
12598646	51.72	543.6	391	58	4.0	44.79	470.8	79.6	94.5	-	-	-	LS9
12599504	26.09	274.2	197.2	43.5	3.0	26.09	274.2	40.1	47.7	-	High	-	2.9l, 3.7l, 4.2l
15637677	32.0	336.3	241.9	45	3.1	31.46	330.7	49.2	58.5	-	High	-	GMC Typhoon v6-4.3l Turbo
17059401	-	-	-	-	-	-	-	-	-	EV1	-	-	Buick/Olds /Pontiac Quad 4-2.3l
17059402	-	-	-	-	-	-	-	-	-	EV1	-	-	Chevy v6-2.8l, v6-3.1l, Buick v6-2.8l, v6-3.3l
17068993 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Buick /Chevy /GMC /Olds 4-2.5l, Pontiac 4-2.0l, 4-2.5l
17069647	21.7	228.1	164	43.5	3.0	21.7	228.1	33.4	39.6	EV1	High	-	Vette v8-5.7l LT5
17069648	21.7	228.1	164	43.5	3.0	21.7	228.1	33.4	39.6	EV1	High	-	Vette v8-5.7l LT5
17069769	-	-	-	-	-	-	-	-	-	EV1	-	-	Buick/Olds /Pontiac 6-3.3l
17078258 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Cadillac v8-4.1l
17078273 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Buick /Olds /Pontiac 4-1.8l
17079012	-	-	-	-	-	-	-	-	-	-	-	-	Cadillac v8-6.0l

TBI 17079664 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Buick 4-2.0l
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 16
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Imped ance		Application
17079694 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Cadillac /Olds 4-2.0l
17083509	-	-	-	-	-	-	-	-	-	-	-	-	Chevy 6-3.4l
17084614	-	-	-	-	-	-	-	-	-	-	-	-	Buick/Olds /Pontiac Quad 4-2.3l, Chevy 2.3l
17084888	15.4	161.9	116.4	43.5	3.0	15.4	161.9	23.7	28.1	EV1	High	-	-
17086284	-	-	-	-	-	-	-	-	-	EV1	-	-	Buick/Chevy /Olds /Pontiac 6-3.1l, Olds 6-2.8l
17086517	17.6	185	133.1	43.5	3.0	17.6	185	27.1	32.2	-	Low	-	-
17086542	19.6	206	148.2	43.5	3.0	19.6	206	30.2	35.8	EV1	High	-	-
17086544	22.45	235.9	169.7	43.5	3.0	22.45	235.9	34.5	41	EV1	High	-	-
17086594	-	-	-	-	-	-	-	-	-	EV1	-	-	Pontiac v8-5.7l
17086651	-	-	-	-	-	-	-	-	-	EV1	-	-	Pontiac 6-3.1l
17086729	-	-	-	-	-	-	-	-	-	EV1	-	-	Cadillac 8-4.5l
17087325	19.88	208.9	150.3	50	3.45	18.54	194.9	30.6	36.3	-	High	-	Vette v8-5.7l
17087515	-	-	-	-	-	-	-	-	-	EV1	-	-	Buick/Olds /Pontiac Quad 4-2.3l
17087930	-	-	-	-	-	-	-	-	-	-	-	-	Chevy /Olds /Pontiac 6-3.4l
17087959	19	199.7	143.6	-	-	-	-	29.2	34.7	EV1	High	-	Cadillac v8-4.9l
17087960	-	-	-	-	-	-	-	-	-	EV1	-	-	Cadillac v8-4.9l
17089116	30.8	323.7	232.8	43.5	3.0	30.8	323.7	47.4	56.3	-	Low	-	-
17089276	-	-	-	43.5	-	-	-	-	-	-	High	-	-
17089569	15.4	161.9	116.4	43.5	3.0	15.4	161.9	23.7	28.1	-	High	-	-
17090571	-	-	-	-	-	-	-	-	-	EV1	-	-	Buick/Chevy /Olds /Pontiac v6-3.8l, Cadillac 8-4.9l
17090844	29.7	312.1	224.5	-	-	-	-	45.7	54.3	-	-	-	v6-3.4l DOHC
17090849	-	-	-	-	-	-	-	-	-	-	-	-	Chevy /Olds /Pontiac 6-3.4l
17091189	23.8	250.1	179.9	43.5	3.0	23.8	250.1	36.6	43.5	-	Low	-	-
17091299	-	-	-	-	-	-	-	-	-	-	-	-	Buick/Olds /Pontiac 4-2.3l
17091300	-	-	-	-	-	-	-	-	-	-	-	-	Chevy /Olds /Pontiac 4-2.3l
17091432	-	-	-	-	-	-	-	-	-	-	-	-	Chevy /GMC Truck v6-4.3l, v8-5.0l, v8-5.7l, Olds 8-4.3l
17091474	-	-	-	-	-	-	-	-	-	-	-	-	Cadillac 8-4.6l, Olds 8-4.0l
17091728	19.2	201.8	145.1	43.5	3.0	19.2	201.8	29.5	35.1	-	High	-	-
17095004	24.75	260.1	187.1	43.5	3.0	24.75	260.1	38.1	45.2	-	High	-	-
17100262	16.65	175	125.9	43.5	3.0	16.65	175	25.6	30.4	-	High	-	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 16
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Imped ance		Application
17101649	-	-	-	43.5	-	-	-	-	-	-	High	-	-
17102119	19	199.7	143.6	-	-	-	-	29.2	34.7	EV1	High	-	-
17102726	-	-	-	-	-	-	-	-	-	-	-	-	GEO 4-1.6l
17102727	27.8	292.2	210.2	43.5	3.0	27.8	292.2	42.8	50.8	-	Low	-	-
17102747	-	-	-	-	-	-	-	-	-	EV1	-	-	Buick/Chevy 6-3.1l, 6-3.3l, Olds 6- 3.3l
17103001	19.6	206	148.2	43.5	3.0	19.6	206	30.2	35.8	-	Low	-	-
17103007	17.7	186	133.8	43.5	3.0	17.7	186	27.2	32.3	-	High	-	-
17103020	-	-	-	43.5	-	-	-	-	-	-	High	-	-
17103146	21.2	222.8	160.3	43.5	3.0	21.2	222.8	32.6	38.7	-	-	-	V6 3800
17103146	19.4	203.9	146.7	43.5	3.0	19.4	203.9	29.8	35.4	-	High	-	-
17103509	-	-	-	-	-	-	-	-	-	-	-	-	Olds /Pontiac 6-3.4l
17103668	19	199.7	143.6	-	-	-	-	29.2	34.7	EV1	High	-	Cadillac v8-4.9l
17104256	-	-	-	-	-	-	-	-	-	-	-	-	Chevy /Pontiac 6-3.4l
17104487	50.0	525.5	378	43.5	3.0	50	525.5	76.9	91.3	-	High	-	-
17104959	95.0	998.5	718.2	43.5	3.0	95	998.5	146	173	-	Low	-	-
17104988	72.0	756.7	544.3	43.5	3.0	72	756.7	110	131	-	Low	-	-
17105004	-	-	-	-	-	-	-	-	-	-	-	-	Buick/Olds /Pontiac 4-2.3l
17105006	-	-	-	-	-	-	-	-	-	-	-	-	Pontiac 4-2.0l
17105094	-	-	-	-	-	-	-	-	-	EV1	-	-	Chevy /vette/Pontiac v8-5.7l
17105286	-	-	-	-	-	-	-	-	-	-	-	-	GEO 4-1.6l
17105384	-	-	-	-	-	-	-	-	-	EV1	-	-	GEO 4-1.6l. 4-1.8l

17105386	-	-	-	-	-	-	-	-	-	-	-	-	GEO 4-1.6l
17105516	-	-	-	-	-	-	-	-	-	-	-	-	Buick/Olds /Pontiac 4-2.3l
17105517	-	-	-	-	-	-	-	-	-	-	-	-	Chevy /Olds /Pontiac 4-2.3l
17106121	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	
17106488	18.1	190.2	136.8	43.5	3.0	18.1	190.2	27.8	33.1	-	Low	-	
17107262	-	-	-	-	-	-	-	-	-	-	-	-	Buick 6-3.1l
17107267	-	-	-	-	-	-	-	-	-	EV1	-	-	Buick/Chevy /Olds /Pontiac 6-3.1l
17108604	-	-	-	-	-	-	-	-	-	-	-	-	Buick/Chevy /Olds /Pontiac 4-2.3l
17108715	-	-	-	-	-	-	-	-	-	EV1	-	-	Chevy 6-3.1l
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 16
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance		Application
17109488	16.95	178.1	128.1	43.5	3.0	16.95	178.1	26.1	31	-	High	-	-
17109596	19.4	203.9	146.7	43.5	3.0	19.4	203.9	29.8	35.4	-	High	-	-
17109826	18.15	190.8	137.2	43.5	3.0	18.15	190.8	27.9	33.2	-	High	-	-
17109952	21.7	228.1	164	43.5	3.0	21.7	228.1	33.4	39.6	EV1	High	-	Vette v8-5.7l LT5
17109953	21.7	228.1	164	43.5	3.0	21.7	228.1	33.4	39.6	EV1	High	-	Vette v8-5.7l LT5
17110855	-	-	-	-	-	-	-	-	-	EV1	-	-	Chevy v6-2.8l, Buick v6-2.8l
17110870	-	-	-	-	-	-	-	-	-	EV1	-	-	Chevy /vette v8-5.7l
17110872	-	-	-	-	-	-	-	-	-	EV1	-	-	Chevy /Pontiac v8-5.0l
17111159 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Chevy v6-4.3l
17111276 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Cadillac v8-4.1l
17111277 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Cadillac v8-4.1l
17111297	-	-	-	-	-	-	-	-	-	EV1	-	-	Cadillac/Chevy /Olds /Pontiac /Buick v6-2.8l, Pontiac 6-3.1l
17111418	-	-	-	-	-	-	-	-	-	EV1	-	-	Chevy /vette/Pontiac v8-5.7l
17111456 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Chevy /GMC 6-2.8l
17111466 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Cadillac v8-4.5l
17111468 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Chevy /GMC /Pontiac v6-4.3l
17111545 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Chevy / Pontiac v8-5.0l
17111546 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Pontiac v8-5.0l
17111549 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Buick 4-1.8l
17111661	-	-	-	-	-	-	-	-	-	EV1	-	-	Buick /Olds /Pontiac v6-2.8l
17111704	-	-	-	-	-	-	-	-	-	EV1	-	-	Cadillac 8-4.1l
17111771 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Cadillac / Chevy /GMC v8-5.7l, Chevy /GMC /Pontiac v8-5.0l
17111774 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Chevy /GMC v8-5.7l
17111784 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Chevy /GMC v8-7.4l
17111789	-	-	-	-	-	-	-	-	-	EV1	-	-	Buick v6-2.8l
17111799	-	-	-	-	-	-	-	-	-	EV1	-	-	Buick/Olds /Pontiac 6-3.1l, Buick /Olds /Pontiac v6-2.8l
17111821 TBI	-	-	-	-	-	-	-	-	-	-	-	-	-
17111928 TBI	-	-	-	-	-	-	-	-	-	-	-	-	GMC v6-4.3l
17111929 TBI	-	-	-	-	-	-	-	-	-	-	-	-	GMC v6-4.3l
17111960	-	-	-	-	-	-	-	-	-	EV1	-	-	Pontiac v8-5.0l, v8-5.7l
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 16
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance		Application
17111961	-	-	-	-	-	-	-	-	-	EV1	-	-	Pontiac v8-5.7l
17111965	-	-	-	-	-	-	-	-	-	EV1	-	-	Buick/Olds /Pontiac Quad 4-2.3l
17111983 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Pontiac 4-1.6l
17111986 TBI	-	-	-	-	-	-	-	-	-	-	-	-	Buick /Chevy /Olds 4-2.0l, 4-2.5l, Chevy 4-2.2l, GMC /Pontiac 4-2.5l
17111991	-	-	-	-	-	-	-	-	-	-	-	-	-

TBI	-	-	-	-	-	-	-	-	-	-	-	Buick /Olds /Pontiac 4-2.0l
17112022 TBI	-	-	-	-	-	-	-	-	-	-	-	-
17112093	-	-	-	-	-	-	-	-	-	EV1	-	Pontiac v8-5.0l
17112094	-	-	-	-	-	-	-	-	-	EV1	-	Chevy /vette v8-5.7l
17112102	-	-	-	-	-	-	-	-	-	-	-	Cadillac 8-4.5l
17112123 TBI	-	-	-	-	-	-	-	-	-	-	-	Buick /Chevy /GMC /Olds /Pontiac 4-2.5l
17112249 TBI	-	-	-	-	-	-	-	-	-	-	-	Chevy /GMC v8-7.4l
17112283	-	-	-	-	-	-	-	-	-	EV1	-	Pontiac v8-5.0l
17112284	-	-	-	-	-	-	-	-	-	EV1	-	Pontiac v8-5.0l
17112285	-	-	-	-	-	-	-	-	-	EV1	-	Pontiac v8-5.7l
17112286	-	-	-	-	-	-	-	-	-	EV1	-	Pontiac v8-5.7l
17112290	-	-	-	-	-	-	-	-	-	EV1	-	Chevy 6-3.1l
17112400 TBI	-	-	-	-	-	-	-	-	-	-	-	Chevy /GMC v6-4.3l, Buick /Cadillac /Chevy /GMC /Olds v8-5.0l
17112401 TBI	-	-	-	-	-	-	-	-	-	-	-	-
17112493 TBI	-	-	-	-	-	-	-	-	-	-	-	Buick /Cadillac / Chevy /GMC /Olds v8-5.7l
17112503 TBI	-	-	-	-	-	-	-	-	-	-	-	Chevy 6-2.8l, 6-3.1l, GMC 6-2.8l, Olds /Pontiac 6-3.1l
17112521 TBI	-	-	-	-	-	-	-	-	-	-	-	Cadillac v8-4.5l, Chevy / GMC /Olds v6-4.3l
17112560 TBI	-	-	-	-	-	-	-	-	-	-	-	Chevy /GMC v8-7.4l
17112584 TBI	-	-	-	-	-	-	-	-	-	-	-	Buick v8-5.7l
17112693	-	-	-	-	-	-	-	-	-	-	-	Buick/Chevy /Olds 4-2.2l
17112742 TBI	-	-	-	-	-	-	-	-	-	-	-	Chevy /GMC v8-5.7l
17112979	-	-	-	-	-	-	-	-	-	-	-	Chevy /Pontiac 6-3.4l
17112982	19	199.7	143.6	-	-	-	-	29.2	34.7	EV1	High	Cadillac 8-4.9l
17113080 TBI	-	-	-	-	-	-	-	-	-	-	-	Chevy /GMC v8-7.4l
17113124	-	-	-	-	-	-	-	-	-	-	-	Buick/Chevy /GMC Truck/Olds /Pontiac 4-2.2l
17113140	-	-	-	-	-	-	-	-	-	-	-	Cadillac 8-4.6l
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle				Stan Weiss 16
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Impedance	Application
17113151	-	-	-	-	-	-	-	-	-	-	-	Chevy /GMC Truck/Olds v6-4.3l
17113175	-	-	-	-	-	-	-	-	-	-	-	Chevy /Pontiac v6-3.4l
17113197	-	-	-	-	-	-	-	-	-	-	-	Buick/Chevy /GMC Truck/Olds /Pontiac 4-2.2l
17113221	-	-	-	-	-	-	-	-	-	-	-	Chevy /GMC Truck 8-7.4l
17113317	-	-	-	-	-	-	-	-	-	-	-	Chevy /Olds /Pontiac 6-3.4l
17113384	-	-	-	-	-	-	-	-	-	-	-	Chevy /GMC Truck/Olds v6-4.3l
17113573	-	-	-	-	-	-	-	-	-	-	-	Chevy /Olds /Pontiac 6-3.4l
17113674	24.0	252.2	181.4	43.5	3.0	24	252.2	36.9	43.8	-	High	GMC / Chevy 2.2l
17113738	50.0	525.5	378	43.5	3.0	50	525.5	76.9	91.3	-	High	-
17113739	40.0	420.4	302.4	43.5	3.0	40	420.4	61.5	73.1	-	High	LS1
17113739	43.77	460	330.9	58.0	4.0	37.91	398.4	67.3	80	-	High	LS1
17113741	55.0	578.1	415.8	43.5	3.0	55	578.1	84.6	100	-	Low	-
17113742	75.0	788.3	567	43.5	3.0	75	788.3	115	137	-	Low	-
17113743	85.0	893.4	642.6	43.5	3.0	85	893.4	130	155	-	Low	-
17113744	96.0	1009	725.7	43.5	3.0	96	1009	147	175	-	Low	-
17113812	30.0	315.3	226.8	43.5	3.0	30	315.3	46.2	54.8	-	High	-
17113813	42.0	441.4	317.5	43.5	3.0	42	441.4	64.6	76.7	-	High	-
17113814	65.0	683.2	491.4	43.5	3.0	65	683.2	100	118	-	Low	-
17113841	55.0	578.1	415.8	43.5	3.0	55	578.1	84.6	100	-	Low	-
17120254	20.85	219.1	157.6	50	3.45	19.45	204.4	32.1	38.1	EV1	High	Vette v8-5.7l
17120262	-	-	-	-	-	-	-	-	-	EV1	-	Chevy 6-2.8l, Olds /Pontiac 6-3.1l
17120601	-	-	-	-	-	-	-	-	-	-	-	Buick/Chevy /Olds /Pontiac v6-3.8l
17120683	18.0	189.2	136.1	43.5	3.0	18	189.2	27.7	32.9	-	High	-
17121068	20.85	219.1	157.6	50	3.45	19.45	204.4	32.1	38.1	-	High	Vette v8-5.7l

17121068	24.4	256.4	184.5	50	3.45	22.76	239.2	37.5	44.6	-	High	Jereome Nicodemus on asnu
17121296	-	-	-	-	-	-	-	-	-	EV1	-	flowbench Buick/Chevy /Olds /Pontiac v6-3.8l, Cadillac 8-4.9l
17121552	-	-	-	-	-	-	-	-	-	-	-	Cadillac 8-4.6l, Olds 8-4.0l
17121705	-	-	-	-	-	-	-	-	-	-	-	Chevy /Olds /Pontiac 6-3.4l
17121882	29.7	312.1	224.5	-	-	-	-	45.7	54.3	-	-	v6-3.4l DOHC
17121909	26.65	280.1	201.5	50	3.45	24.86	261.3	41	48.7	-	High	Vette v8-5.7l LT4
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle				Stan Weiss 16
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Imped ance	Application
17121947	19.88	208.9	150.3	50	3.45	18.54	194.9	30.6	36.3	EV1	High	Buick/Cadillac/Chevy /vette/Pontiac v8-5.7l
17121948	20.0	210.2	151.2	50	3.45	18.65	196.1	30.8	36.5	-	High	Cadillac v8-5.7l
17121966	-	-	-	-	-	-	-	-	-	-	-	Chevy /Olds /Pontiac 6-3.4l
17122509	-	-	-	-	-	-	-	-	-	-	-	Chevy /Pontiac 6-3.1l
17122264	-	-	-	-	-	-	-	-	-	-	-	Buick/Chevy /Olds /Pontiac 4-2.4l
17122683	24.0	252.2	181.4	43.5	3.0	24	252.2	36.9	43.8	-	High	-
17123907	-	-	-	-	-	-	-	-	-	-	-	GM Truck v6-4.3l
17123919	-	-	-	43.5	-	-	-	-	-	-	Low	-
17124068	25.1	263.8	189.8	43.5	3.0	25.1	263.8	38.6	45.9	-	High	-
17124187	-	-	-	43.5	-	-	-	-	-	-	High	-
17124248	23.9	251.2	180.7	43.5	3.0	23.9	251.2	36.8	43.7	EV1	High	Buick/Chevy /vette/Pontiac v8-5.7l LT1
17124251	26.65	280.1	201.5	43.5	3.0	26.65	280.1	41	48.7	-	High	Vette v8-5.7l LT4
17124289	26.65	280.1	201.5	50	3.45	24.86	261.3	41	48.7	-	High	Vette v8-5.7l LT4
17124782	-	-	-	43.5	-	-	-	-	-	-	Low	-
17125053	-	-	-	43.5	-	-	-	-	-	-	High	-
17191728	19.5	204.9	147.4	43.5	3.0	19.5	204.9	30	35.6	-	High	-
23424745	78.0	819.8	589.7	43.5	3.0	78	819.8	120	142	-	Low	-
24500225	-	-	-	-	-	-	-	-	-	EV1	-	Buick/Chevy /Olds /Pontiac v6-3.8l
24500369	-	-	-	-	-	-	-	-	-	EV1	-	Buick/Olds /Pontiac v6-3.8l
24501509	-	-	-	-	-	-	-	-	-	EV1	-	Buick/Chevy /Olds /Pontiac v6-3.8l
24503226	-	-	-	-	-	-	-	-	-	EV1	-	Buick/Chevy /Olds /Pontiac v6-3.8l
24503406	-	-	-	-	-	-	-	-	-	-	-	Buick/Olds /Pontiac v6-3.8l
24507459	-	-	-	-	-	-	-	-	-	-	-	Buick/Olds /Pontiac v6-3.8l
24508208	-	-	-	-	-	-	-	-	-	-	-	Buick/Olds /Pontiac v6-3.8l
25176913	13.8	145	104.3	43.5	3.0	13.8	145	21.2	25.2	-	High	-
25180245	23.8	250.1	179.9	43.5	3.0	23.8	250.1	36.6	43.5	-	High	-
25317628	22.1	232.3	167.1	43.5	3.0	22.1	232.3	34	40.4	-	High	v8-6.0l
25320687	24.0	252.2	181.4	43.5	3.0	24	252.2	36.9	43.8	-	High	GMC / Chevy 2.2l
25323972	19.61	206.1	148.2	43.5	3.0	19.61	206.1	30.2	35.8	-	High	Chevy v6-3.8l
25324367	65.0	683.2	491.4	43.5	3.0	65	683.2	100	118	-	Low	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle				Stan Weiss 16
Part Number	lbs/hr	cc /min	grams /min	PSI	BARS	lbs/hr	cc /min	80%	95%	Feed	Imped ance	Application
25324343	42.0	441.4	317.5	43.5	3.0	42	441.4	64.6	76.7	-	High	-
25324344	55.0	578.1	415.8	43.5	3.0	55	578.1	84.6	100	-	Low	-
25324366	30.0	315.3	226.8	43.5	3.0	30	315.3	46.2	54.8	-	High	-
25324743	42.0	441.4	317.5	43.5	3.0	42	441.4	64.6	76.7	-	High	-
25324744	55.0	578.1	415.8	43.5	3.0	55	578.1	84.6	100	-	Low	Feedback - Dave Doddek
25324746	85.0	893.4	642.6	43.5	3.0	85	893.4	130	155	-	Low	-
25519365	-	-	-	-	-	-	-	-	-	EV1	-	Buick/Pontiac v6-3.8l Turbo
25519366	-	-	-	-	-	-	-	-	-	EV1	-	Buick/Olds v6-3.8l
25523721	-	-	-	-	-	-	-	-	-	EV1	-	Buick/Olds /Pontiac 6-3.0l
25527181	-	-	-	-	-	-	-	-	-	EV1	-	Buick/Olds /Pontiac 6-3.0l
25530916	-	-	-	-	-	-	-	-	-	EV1	-	Olds v6-3.8l
25531465	-	-	-	-	-	-	-	-	-	EV1	-	Buick/Olds /Pontiac v6-3.8l inc Turbo
25531467	-	-	-	-	-	-	-	-	-	EV1	-	Buick/Olds /Pontiac v6-3.8l inc Turbo
25531468	-	-	-	-	-	-	-	-	-	EV1	-	Buick/Olds /Pontiac v6-3.0l
96060117 TBI	-	-	-	-	-	-	-	-	-	-	-	Metro 3-1.3l
96093614 TBI	-	-	-	-	-	-	-	-	-	-	-	Metro 3-1.0l, 3-1.3l

-	55.0	578.1	415.8	43.5	3.0	55	578.1	84.6	100	-	High	-
-	65.0	683.2	491.4	43.5	3.0	65	683.2	100	118	-	Low	-
-	83.0	872.3	627.5	43.5	3.0	83	872.3	127	151	-	Low	-
-	96.0	1009	725.7	43.5	3.0	96	1009	147	175	-	Low	-

Siemens Deka

 COPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Impedance	Application
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%			
-	30.0	315.3	226.8	43.5	3.0	30	315.3	46.2	54.8	-	High	-
-	36.0	378.4	272.2	43.5	3.0	36	378.4	55.4	65.8	-	High	-
-	50.0	525.5	378	43.5	3.0	50	525.5	76.9	91.3	-	High	-
-	55.0	578.1	415.8	43.5	3.0	55	578.1	84.6	100	-	High	-
-	55.0	578.1	415.8	43.5	3.0	55	578.1	84.6	100	-	Low	-
FI114961	60.5	635.9	457.4	43.5	3.0	60.5	635.9	93.1	110	EV1	High	LS1
-	65.0	683.2	491.4	43.5	3.0	65	683.2	100	118	-	Low	-
-	72.0	756.7	544.3	43.5	3.0	72	756.7	110	131	EV1	Low	-
-	83.0	872.3	627.5	43.5	3.0	83	872.3	127	151	EV1	High	-
-	83.0	872.3	627.5	43.5	3.0	83	872.3	127	151	EV1	Low	-
-	220.0	2312	1663	43.5	3.0	220	2312	338	401	Top	Low	-
100977	68.5	719.9	517.9	43.5	3.0	68.5	719.9	105	125	-	High	-
107961	59.5	625.3	449.8	43.5	3.0	59.5	625.3	91.5	108	EV1	High	-
107962	61.85	650	467.6	43.5	3.0	61.85	650	95.2	113	EV1	High	-
108191	59.5	625.3	449.8	43.5	3.0	59.5	625.3	91.5	108	EV6	High	-
109958	52.33	550	395.6	43.5	3.0	52.33	550	80.5	95.6	EV6	High	-
109991	80.87	849.9	611.4	43.5	3.0	80.87	849.9	124	147	EV6	High	-
110324	80.87	849.9	611.4	43.5	3.0	80.87	849.9	124	147	EV1	High	-
FI11351	46.5	488.7	351.5	43.5	3.0	46.5	488.7	71.5	85	USCAR EV6	High	-
LU107	60.0	630.6	453.6	43.5	3.0	60	630.6	92.3	109	USCAR EV1	High	LS2
SD-63LBUSCAR	62.7	659	474	43.5	3.0	62.7	659	96.5	114	EV6 USCAR	High	-
SEM143L	143.0	1502	1081	43.5	3.0	143	1502	220	261	-	Low	-
SEM184L	184.0	1933	1391	43.5	3.0	184	1933	283	336	-	Low	-
S3102	57.0	599.1	430.9	43.5	3.0	57	599.1	87.7	104	EV1	Low	-
S3105	82.3	865	622.2	43.5	3.0	82.3	865	126	150	-	Low	-
S3145	71.35	749.9	539.4	43.5	3.0	71.35	749.9	109	130	-	Low	-
S3172	52.33	550	395.6	43.5	3.0	52.33	550	80.5	95.6	EV1	High	-
S107	60.0	630.6	453.6	43.5	3.0	60	630.6	92.3	109	-	High	-
SL107	65.0	683.2	491.4	43.5	3.0	65	683.2	100	118	-	High	-

Subaru

 COPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Impedance	Application
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%			
16600-AA000	-	-	-	-	-	-	-	-	-	-	-	4-1.8l, 4-1.8l turbo
16600-KA050	-	-	-	-	-	-	-	-	-	-	-	3-1.2l
16600-KA051	-	-	-	-	-	-	-	-	-	-	-	3-1.2l
16600-KA110	-	-	-	-	-	-	-	-	-	-	-	3-1.2l
16611-AA090	-	-	-	-	-	-	-	-	-	-	-	4-2.2l
16611-AA120	-	-	-	-	-	-	-	-	-	-	-	4-2.2l
16611-AA140	-	-	-	-	-	-	-	-	-	-	-	4-2.2l, 6-3.3l
16611-AA141	-	-	-	-	-	-	-	-	-	-	-	4-2.2l, 6-3.3l
16611-AA150	-	-	-	-	-	-	-	-	-	-	-	4-2.2l turbo
16611-AA180	-	-	-	-	-	-	-	-	-	-	-	4-2.2l
16611-AA181	-	-	-	-	-	-	-	-	-	-	-	4-2.2l

16611-AA210	-	-	-	-	-	-	-	-	-	-	-	-	4-2.2l, 4-2.5l, 6-3.3l
16611-AA260	-	-	-	-	-	-	-	-	-	-	-	-	4-2.2l
16611-AA270	-	-	-	-	-	-	-	-	-	-	-	-	4-1.8l
16611-AA300	-	-	-	-	-	-	-	-	-	-	-	-	4-1.8l, 4-2.2l
16611-AA310	-	-	-	-	-	-	-	-	-	-	-	-	4-2.5l
16637-AA000 TBI	-	-	-	-	-	-	-	-	-	-	-	-	4-1.8l
16637-AA010 TBI	-	-	-	-	-	-	-	-	-	-	-	-	4-1.8l

Toyota - Lexus

COPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Impedance	Application
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%			
22210-62020	-	-	-	-	-	-	-	-	-	-	-	Lexus 4-2.5l
22210-62030	-	-	-	-	-	-	-	-	-	-	-	Lexus 4-2.5l
23203-11010	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.5l
23209-11040	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.5l
23209-11090	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.5l
23209-11100	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.5l
23209-16070	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.6l
23209-16080	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.6l
23209-16100	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.6l, GEO 4-1.6l
23209-16120	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.6l, GEO 4-1.6l
23209-16130	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.6l
23209-16150	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.6l, GEO 4-1.6l
23209-16160	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.8l, GEO 4-1.8l
23209-20010	-	-	-	-	-	-	-	-	-	-	-	Toyota 6-3.0l
23209-34010	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.6l
23209-42010	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-2.0l, 6-3.0l
23209-45011	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.6l, 4-2.0l, 6-2.6l, 6-2.8l
23209-46030	-	-	-	-	-	-	-	-	-	-	-	Lexus 6-3.0l, Toyota 6-3.0l
23209-46031	-	-	-	-	-	-	-	-	-	-	-	Toyota 6-3.0l
23209-46050	-	-	-	-	-	-	-	-	-	-	-	Toyota 6-3.0l
23209-49035	-	-	-	-	-	-	-	-	-	-	-	Toyota 6-3.0l
23209-50010	-	-	-	-	-	-	-	-	-	-	-	Lexus 8-4.0l
23209-50020	-	-	-	-	-	-	-	-	-	-	-	Lexus 8-4.0l
23209-62020	-	-	-	-	-	-	-	-	-	-	-	Lexus 4-2.5l, 6-2.5l
23209-62030	-	-	-	-	-	-	-	-	-	-	-	Lexus 6-3.0l, Toyota 6-3.0l
23209-70040	-	-	-	-	-	-	-	-	-	-	-	Toyota 6-3.0l
23209-70080	-	-	-	-	-	-	-	-	-	-	-	Toyota 6-3.0l

23209-73010	-	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-2.2l
23209-74040	-	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-2.2l
23209-74050	-	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-2.0l
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 19
Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Impedance		Application
23209-74060	-	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-2.0l
23209-74100	-	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-2.2l
23209-76010	-	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-2.4l
23209-79015	-	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-2.0l
23209-79045	-	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-2.4l
23250-11040	14.75	155	111.5	41.2	2.84	15.16	159.3	22.7	26.9	-	High	-	Toyota 4-1.5l
23250-11090	-	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.5l
23250-11100	-	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.5l
23250-13010	14.9	156.6	112.6	-	-	-	-	22.9	27.2	-	Low	-	-
23250-16061	34.7	364.7	262.3	36.25	2.5	38.01	399.5	53.4	63.4	-	Low	-	-
23250-16080	20.5	215.5	155	41.2	2.84	21.06	221.4	31.5	37.5	-	High	-	-
23250-16100	-	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.6l, GEO 4-1.6l
23250-16120	16.75	176	126.6	41.2	2.84	17.21	180.9	25.8	30.6	-	High	-	Toyota 4-1.6l, GEO 4-1.6l
23250-16150	-	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.6l, GEO 4-1.6l
23250-16160	-	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-1.8l, GEO 4-1.8l
23250-20010	-	-	-	-	-	-	-	-	-	-	-	-	Toyota 6-3.0l
23250-22040	-	-	-	43.5	-	-	-	-	-	-	High	-	Toyota 1.8l
23250-35010	23.75	249.6	179.5	36.25	2.5	26.02	273.4	36.5	43.4	-	Low	-	-
23250-35020	27.0	283.8	204.1	36.25	2.5	29.58	310.9	41.5	49.3	-	Low	-	-
23250-35040	19.0	199.7	143.6	41.2	2.84	19.52	205.2	29.2	34.7	-	High	-	-
23250-41011	-	-	-	-	-	-	-	-	-	-	-	-	Toyota 6-2.6l
23250-42010	40.85	429.3	308.8	36.25	2.5	44.75	470.3	62.8	74.6	-	Low	-	-
23250-45011	16.9	177.6	127.8	36.25	2.5	18.51	194.6	26	30.9	-	Low	-	Toyota 4-2.0l, 6-2.8l
23250-46030	-	-	-	-	-	-	-	-	-	-	-	-	Lexus 6-3.0l, Toyota 6-3.0l
23250-46050	-	-	-	-	-	-	-	-	-	-	-	-	Toyota 6-3.0l
23250-49035	50.4	529.7	381	36.25	2.5	55.21	580.3	77.5	92.1	-	High	-	Toyota 6-3.0l
23250-50010	-	-	-	-	-	-	-	-	-	-	-	-	Lexus 8-4.0l
23250-61010	20.5	215.5	155	41.2	2.84	21.06	221.4	31.5	37.5	-	High	-	-
23250-62010	20.5	215.5	155	41.2	2.84	21.06	221.4	31.5	37.5	-	High	-	-
23250-62020	19.0	199.7	143.6	41.2	2.84	19.52	205.2	29.2	34.7	-	High	-	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle					Stan Weiss 19
Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Impedance		Application
23250-62030	19.0	199.7	143.6	41.2	2.84	19.52	205.2	29.2	34.7	-	High	-	Lexus 6-3.0l, Toyota 6-3.0l

23250-70080	29.95	314.8	226.4	41.2	2.84	30.77	323.4	46.1	54.7	-	High	-
23250-70040	-	-	-	-	-	-	-	-	-	-	-	Toyota 6-3.0l
23250-73010	19.0	199.7	143.6	41.2	2.84	19.52	205.2	29.2	34.7	-	Low	Toyota 4-2.2l
23250-74030	19.0	199.7	143.6	41.2	2.84	19.52	205.2	29.2	34.7	-	Low	-
23250-74040	27.55	289.6	208.3	36.25	2.5	30.18	317.2	42.4	50.3	-	Low	Toyota 4-2.2l
23250-74050	23.75	249.6	179.5	36.25	2.5	26.02	273.4	36.5	43.4	-	High	Toyota 4-2.0l
23250-74060	19.0	199.7	143.6	41.2	2.84	19.52	205.2	29.2	34.7	-	High	-
23250-74090	41.85	439.8	316.4	36.25	2.5	45.84	481.8	64.4	76.5	-	Low	-
23250-74100	-	-	-	43.5	-	-	-	-	-	-	High	Toyota 2.0l, 4-2.2l
23250-76010	-	-	-	-	-	-	-	-	-	-	-	Toyota 4-2.4l
23250-79015	40.85	429.3	308.8	36.25	2.5	44.75	470.3	62.8	74.6	-	Low	Toyota 4-2.0l
23250-79045	27	283.8	204.1	41.2	2.84	27.74	291.6	41.5	49.3	-	High	-

Trick Flow

COPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Drive Circuit Type	Impedance	Application
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%				
TFS-89024	24	252.2	181.4	43.5	3.0	24	252.2	36.9	43.8	EV1	12v Saturated	High	-
TFS-89030	30	315.3	226.8	43.5	3.0	30	315.3	46.2	54.8	EV1	12v Saturated	High	-
TFS-89036	36	378.4	272.2	43.5	3.0	36	378.4	55.4	65.8	EV1	12v Saturated	High	-
TFS-89044	44	462.4	332.6	43.5	3.0	44	462.4	67.7	80.4	EV1	12v Saturated	High	-
TFS-89048	48	504.5	362.9	43.5	3.0	48	504.5	73.8	87.7	EV1	12v Saturated	High	-
TFS-89055	55	578.1	415.8	43.5	3.0	55	578.1	84.6	100	EV1	4\1A Peak and Hold	Low	-
TFS-89072	72	756.7	544.3	43.5	3.0	72	756.7	110	131	EV1	4\1A Peak and Hold	Low	-
TFS-89083	83	872.3	627.5	43.5	3.0	83	872.3	127	151	EV1	4\1A Peak and Hold	Low	-
TFS-89095	95	998.5	718.2	43.5	3.0	95	998.5	146	173	EV1	4\1A Peak and Hold	Low	-
TFS-89120	120	1261	907.2	43.5	3.0	120	1261	184	219	EV1	4\1A Peak and Hold	Low	-

Thanks to:

Giuseppe For many of these numbers.

Weber

COPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Part Number	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle		Feed	Drive Circuit Type	Impedance	Application	n-H
	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%					
IW 025 Yellow	25.82	271.4	195.2	43.5	3.0	25.82	271.4	39.7	47.2	-	-	Low	-	-
IW 030 Blue	18.02	189.4	136.2	43.5	3.0	18.02	189.4	27.7	32.9	-	-	High	-	-
IW 031 Green	25.7	270.1	194.3	43.5	3.0	25.7	270.1	39.5	47	-	-	High	-	-
IW 042 Red	19.03	200	143.9	43.5	3.0	19.03	200	29.3	34.8	-	-	High	-	-
IW 044	25.21	265	190.6	43.5	3.0	25.21	265	38.8	46.1	-	-	Low	-	-

IW 050	18.08	190	136.7	43.5	3.0	18.08	190	27.8	33	-	-	High	Ford	-
IW 051	16.18	170.1	122.3	43.5	3.0	16.18	170.1	24.9	29.6	-	-	High	-	-
IW 052 Brown	13.32	140	100.7	43.5	3.0	13.32	140	20.5	24.3	-	-	High	-	-
IW 054	18.08	190	136.7	43.5	3.0	18.08	190	27.8	33	-	-	High	Citroen, Fiat, Lancia, Peugeot	-
IW 057	13.32	140	100.7	43.5	3.0	13.32	140	20.5	24.3	-	-	High	Fiat	-
IW 058 Biege	36.53	383.9	276.2	43.5	3.0	36.53	383.9	56.2	66.7	-	-	High	-	-
IW 061	47.57	500	359.6	43.5	3.0	47.57	500	73.2	86.9	-	-	High	-	-
IW 155	10.94	115	82.75	43.5	3.0	10.94	115	16.8	20	-	-	High	Citroen, Ford, Peugeot	-
IW 158	36.15	379.9	273.3	43.5	3.0	36.15	379.9	55.6	66	-	-	High	-	-
IW 204	25.2	264.9	190.5	43.5	3.0	25.2	264.9	38.8	46	-	-	High	-	-
IW 720	17.13	180	129.5	43.5	3.0	17.13	180	26.4	31.3	-	-	High	Citroen, Fiat, Peugeot	-
IW 724	27.12	285	205	32.63	2.25	31.31	329.1	41.7	49.5	EV1	-	High	-	-
IAW 058	35.54	373.5	268.7	43.5	3.0	35.54	373.5	54.7	64.9	EV1	-	High	Alfa, Lancia	-
IAW 158	35.54	373.5	268.7	43.5	3.0	35.54	373.5	54.7	64.9	EV1	-	High	-	-
INP 069	41.87	440.1	316.5	43.5	3.0	41.87	440.1	64.4	76.5	EV1	-	High	-	-
IPM 001	9.51	100	71.94	43.5	3.0	9.515	100	14.6	17.4	-	-	High	Citroen, Peugeot	-
IWP 001	18.08	190	136.7	43.5	3.0	18.08	190	27.8	33	-	-	High	-	-
IWP 003	20.46	215	154.7	43.5	3.0	20.46	215	31.5	37.4	-	-	High	-	-
IWP 006	21.5	226	162.5	43.5	3.0	21.5	226	33.1	39.3	-	-	High	Fiat, Lancia	y
IWP 022	20.46	215	154.7	43.5	3.0	20.46	215	31.5	37.4	-	-	High	-	-
IWP 023	15.03	158	113.6	43.5	3.0	15.03	158	23.1	27.5	-	-	High	-	y
IWP 024	21.5	226	162.5	43.5	3.0	21.5	226	33.1	39.3	-	-	High	-	-
IWP 025	18.08	190	136.7	43.5	3.0	18.08	190	27.8	33	-	-	High	-	-
IWP 026	17.51	184	132.4	43.5	3.0	17.51	184	26.9	32	-	-	High	-	-
IWP 041	13.89	146	105	43.5	3.0	13.89	146	21.4	25.4	-	-	High	-	-
	Flow			Rating @		Flow @ 43.5 PSI / 3 Bars		.52 BSFC - Est. HP Duty Cycle			Drive Circuit			Stan Weiss 21
Part Number	lbs/hr	cc/min	grams/min	PSI	BARS	lbs/hr	cc/min	80%	95%	Feed	Type	Imped ance	Application	n-H
IWP 042	21.88	230	165.4	43.5	3.0	21.88	230	33.7	40	-	-	High	-	-
IWP 043	31.3	329	236.6	43.5	3.0	31.3	329	48.2	57.2	-	-	High	-	y
IWP 044	18.36	193	138.8	43.5	3.0	18.36	193	28.2	33.5	-	-	High	-	-
IWP 045	19.03	200	143.9	43.5	3.0	19.03	200	29.3	34.8	-	-	High	-	y
IWP 048	20.46	215	154.7	43.5	3.0	20.46	215	31.5	37.4	-	-	High	-	y
IWP 049	17.51	184	132.4	43.5	3.0	17.51	184	26.9	32	-	-	High	-	y
IWP 058	12.56	132	95.00	43.5	3.0	12.56	132	19.3	22.9	-	-	High	-	-
IWP 063	39.96	420	302.1	43.5	3.0	39.96	420	61.5	73	EV1	-	High	-	-
IWP 064	17.7	186	133.8	43.5	3.0	17.7	186	27.2	32.3	-	-	High	-	y
IWP 065	15.03	158	113.6	43.5	3.0	15.03	158	23.1	27.5	-	-	High	-	y
IWP 067	21.5	226	162.5	43.5	3.0	21.5	226	33.1	39.3	-	-	High	-	-
IWP 069	46.72	491	353.2	43.5	3.0	46.72	491	71.9	85.4	EV1	-	High	-	y
IWP 076	20.46	215	154.7	43.5	3.0	20.46	215	31.5	37.4	-	-	High	-	-
IWP 116	14.75	155	111.5	43.5	3.0	14.75	155	22.7	26.9	-	-	High	-	-
IWP 145	48.52	509.9	366.8	43.5	3.0	48.52	509.9	74.6	88.6	-	-	High	-	-
IWP 162	35.87	377	271.2	43.5	3.0	35.87	377	55.2	65.5	-	-	High	-	y
IWP 189	46.62	490	352.4	43.5	3.0	46.62	490	71.7	85.2	-	-	High	-	y



This WebSite Designed and Maintained By World Wide Enterprises

This page best viewed at 1024 x 768 or greater.

Peak Horse Power per Injector																
Flow Rate in lbs/hr - cc/min	BSFC - 80% Duty Cycle (Street)								BSFC - 95% Duty Cycle (Race)							
	.32	.37	.42	.47	.52	.57	.62	.67	.32	.37	.42	.47	.52	.57	.62	.67
2 / 21.07	5.05	4.37	3.85	3.45	3.12	2.85	2.63	2.43	5.98	5.18	4.57	4.09	3.70	3.38	3.11	2.88
3 / 31.58	7.55	6.53	5.76	5.15	4.66	4.26	3.92	3.63	8.95	7.75	6.83	6.11	5.53	5.05	4.64	4.30
4 / 42.09	10	8.69	7.66	6.85	6.20	5.66	5.21	4.82	11.9	10.3	9.09	8.13	7.35	6.71	6.17	5.72

5 / 52.60	12.5	10.8	9.57	8.56	7.74	7.06	6.50	6.02	14.8	12.8	11.3	10.1	9.18	8.38	7.71	7.13	
6 / 63.11	15	13	11.4	10.2	9.28	8.47	7.79	7.21	17.8	15.4	13.6	12.1	11	10	9.24	8.55	
7 / 73.62	17.5	15.1	13.3	11.9	10.8	9.87	9.08	8.40	20.8	18	15.8	14.1	12.8	11.7	10.7	9.97	
8 / 84.13	20	17.3	15.2	13.6	12.3	11.2	10.3	9.60	23.8	20.5	18.1	16.2	14.6	13.3	12.3	11.3	
9 / 94.64	22.5	19.5	17.1	15.3	13.8	12.6	11.6	10.7	26.7	23.1	20.4	18.2	16.4	15	13.8	12.8	
10 / 105.1	25	21.6	19	17	15.4	14	12.9	11.9	29.7	25.7	22.6	20.2	18.3	16.7	15.3	14.2	
11 / 115.6	27.5	23.8	21	18.7	16.9	15.4	14.2	13.1	32.7	28.2	24.9	22.2	20.1	18.3	16.9	15.6	
12 / 126.1	30	25.9	22.9	20.4	18.5	16.8	15.5	14.3	35.6	30.8	27.1	24.3	21.9	20	18.4	17	
13 / 136.6	32.5	28.1	24.8	22.1	20	18.2	16.8	15.5	38.6	33.4	29.4	26.3	23.8	21.7	19.9	18.4	
14 / 147.1	35	30.3	26.7	23.8	21.5	19.6	18.1	16.7	41.6	35.9	31.7	28.3	25.6	23.3	21.5	19.9	
15 / 157.7	37.5	32.4	28.6	25.5	23.1	21.1	19.4	17.9	44.5	38.5	33.9	30.3	27.4	25	23	21.3	
16 / 168.2	40	34.6	30.5	27.2	24.6	22.5	20.6	19.1	47.5	41.1	36.2	32.3	29.2	26.7	24.5	22.7	
17 / 178.7	42.5	36.8	32.4	28.9	26.2	23.9	21.9	20.3	50.5	43.6	38.5	34.4	31.1	28.3	26	24.1	
18 / 189.2	45	38.9	34.3	30.6	27.7	25.3	23.2	21.5	53.4	46.2	40.7	36.4	32.9	30	27.6	25.5	
19 / 199.7	47.5	41.1	36.2	32.3	29.2	26.7	24.5	22.7	56.4	48.8	43	38.4	34.7	31.7	29.1	26.9	
20 / 210.2	50	43.2	38.1	34	30.8	28.1	25.8	23.9	59.4	51.4	45.2	40.4	36.5	33.3	30.6	28.4	
21 / 220.7	52.5	45.4	40	35.7	32.3	29.5	27.1	25.1	62.3	53.9	47.5	42.4	38.4	35	32.2	29.8	
22 / 231.2	55	47.6	41.9	37.4	33.8	30.9	28.4	26.3	65.3	56.5	49.8	44.5	40.2	36.7	33.7	31.2	
23 / 241.7	57.5	49.7	43.8	39.1	35.4	32.3	29.7	27.5	68.3	59.1	52	46.5	42	38.3	35.2	32.6	
24 / 252.2	60	51.9	45.7	40.9	36.9	33.7	31	28.7	71.3	61.6	54.3	48.5	43.8	40	36.8	34	
25 / 262.8	62.5	54.1	47.6	42.6	38.5	35.1	32.3	29.9	74.2	64.2	56.5	50.5	45.7	41.7	38.3	35.4	
Flow Rate in lbs/hr - cc/min	BSFC - 80% Duty Cycle (Street)									BSFC - 95% Duty Cycle (Race)							
	.32	.37	.42	.47	.52	.57	.62	.67		.32	.37	.42	.47	.52	.57	.62	.67
26 / 273.3	65	56.2	49.5	44.3	40	36.5	33.5	31	77.2	66.8	58.8	52.6	47.5	43.3	39.8	36.9	
27 / 283.8	67.5	58.4	51.4	46	41.5	37.9	34.8	32.2	80.2	69.3	61.1	54.6	49.3	45	41.4	38.3	
28 / 294.3	70	60.5	53.3	47.7	43.1	39.3	36.1	33.4	83.1	71.9	63.3	56.6	51.2	46.7	42.9	39.7	
29 / 304.8	72.5	62.7	55.2	49.4	44.6	40.7	37.4	34.6	86.1	74.5	65.6	58.6	53	48.3	44.4	41.1	
30 / 315.3	75	64.9	57.1	51.1	46.2	42.1	38.7	35.8	89.1	77	67.9	60.6	54.8	50	46	42.5	
31 / 325.8	77.5	67	59	52.8	47.7	43.5	40	37	92	79.6	70.1	62.7	56.6	51.7	47.5	44	
32 / 336.3	80	69.2	61	54.5	49.2	44.9	41.3	38.2	95	82.2	72.4	64.7	58.5	53.3	49	45.4	
33 / 346.8	82.5	71.4	62.9	56.2	50.8	46.3	42.6	39.4	98	84.7	74.6	66.7	60.3	55	50.6	46.8	
34 / 357.3	85	73.5	64.8	57.9	52.3	47.7	43.9	40.6	101	87.3	76.9	68.7	62.1	56.7	52.1	48.2	
35 / 367.9	87.5	75.7	66.7	59.6	53.8	49.1	45.2	41.8	104	89.9	79.2	70.7	63.9	58.3	53.6	49.6	
36 / 378.4	90	77.8	68.6	61.3	55.4	50.5	46.5	43	107	92.4	81.4	72.8	65.8	60	55.2	51	
37 / 388.9	92.5	80	70.5	63	56.9	51.9	47.7	44.2	110	95	83.7	74.8	67.6	61.7	56.7	52.5	
38 / 399.4	95	82.2	72.4	64.7	58.5	53.3	49	45.4	113	97.6	86	76.8	69.4	63.3	58.2	53.9	
39 / 409.9	97.5	84.3	74.3	66.4	60	54.7	50.3	46.6	116	100	88.2	78.8	71.3	65	59.8	55.3	
40 / 420.4	100	86.5	76.2	68.1	61.5	56.1	51.6	47.8	119	103	90.5	80.9	73.1	66.7	61.3	56.7	
41 / 430.9	103	88.6	78.1	69.8	63.1	57.5	52.9	49	122	105	92.7	82.9	74.9	68.3	62.8	58.1	
42 / 441.4	105	90.8	80	71.5	64.6	58.9	54.2	50.1	125	108	95	84.9	76.7	70	64.4	59.6	
43 / 451.9	108	93	81.9	73.2	66.2	60.4	55.5	51.3	128	110	97.3	86.9	78.6	71.7	65.9	61	
44 / 462.4	110	95.1	83.8	74.9	67.7	61.8	56.8	52.5	131	113	100	88.9	80.4	73.3	67.4	62.4	
45 / 473.0	113	97.3	85.7	76.6	69.2	63.2	58.1	53.7	134	116	102	91	82.2	75	69	63.8	
46 / 483.5	115	99.5	87.6	78.3	70.8	64.6	59.4	54.9	137	118	104	93	84	76.7	70.5	65.2	
47 / 494.0	118	102	89.5	80	72.3	66	60.6	56.1	140	121	106	95	85.9	78.3	72	66.6	
48 / 504.5	120	104	91.4	81.7	73.8	67.4	61.9	57.3	143	123	109	97	87.7	80	73.5	68.1	
49 / 515.0	123	106	93.3	83.4	75.4	68.8	63.2	58.5	145	126	111	99	89.5	81.7	75.1	69.5	
50 / 525.5	125	108	95.2	85.1	76.9	70.2	64.5	59.7	148	128	113	101	91.3	83.3	76.6	70.9	
Flow Rate in lbs/hr - cc/min	BSFC - 80% Duty Cycle (Street)									BSFC - 95% Duty Cycle (Race)							
	.32	.37	.42	.47	.52	.57	.62	.67		.32	.37	.42	.47	.52	.57	.62	.67
51 / 536.0	128	110	97.1	86.8	78.5	71.6	65.8	60.9	151	131	115	103	93.2	85	78.1	72.3	
52 / 546.5	130	112	99	88.5	80	73	67.1	62.1	154	134	118	105	95	86.7	79.7	73.7	
53 / 557.0	133	115	101	90.2	81.5	74.4	68.4	63.3	157	136	120	107	96.8	88.3	81.2	75.1	
54 / 567.5	135	117	103	91.9	83.1	75.8	69.7	64.5	160	139	122	109	98.7	90	82.7	76.6	
55 / 578.1	138	119	105	93.6	84.6	77.2	71	65.7	163	141	124	111	100	91.7	84.3	78	
56 / 588.6	140	121	107	95.3	86.2	78.6	72.3	66.9	166	144	127	113	102	93.3	85.8	79.4	
57 / 599.1	143	123	109	97	87.7	80	73.5	68.1	169	146	129	115	104	95	87.3	80.8	
58 / 609.6	145	125	110	98.7	89.2	81.4	74.8	69.3	172	149	131	117	106	96.7	88.9	82.2	
59 / 620.1	148	128	112	100	90.8	82.8	76.1	70.4	175	151	133	119	108	98.3	90.4	83.7	
60 / 630.6	150	130	114	102	92.3	84.2	77.4	71.6	178	154	136	121	110	100	91.9	85.1	
61 / 641.1	153	132	116	104	93.8	85.6	78.7	72.8	181	157	138	123	111	102	93.5	86.5	
62 / 651.6	155	134	118	106	95.4	87	80	74	184	159	140	125	113	103	95	87.9	
63 / 662.1	158	136	120	107	96.9	88.4	81.3	75.2	187	162	143	127	115	105	96.5	89.3	
64 / 672.6	160	138	122	109	98.5	89.8	82.6	76.4	190	164	145	129	117	107	98.1	90.7	
65 / 683.2	163	141	124	111	100	91.2	83.9	77.6	193	167	147	131	119	108	100	92.2	
66 / 693.7	165	143	126	112	102	92.6	85.2	78.8	196	169	149	133	121	110	101	93.6	
67 / 704.2	168	145	128	114	103	94	86.5	80	199	172	152	135	122	112	103	95	
68 / 714.7	170	147	130	116	105	95.4	87.7	81.2	202	175	154	137	124	113	104	96.4	
69 / 725.2	173	149	131	117	106	96.8	89	82.4	205	177	156	139	126	115	106	97.8	
70 / 735.7	175	151	133	119	108	98.2	90.3	83.6	208	180	158	141	128	117	107	99.3	
71 / 746.2	178	154	135	121	109	100	91.6	84.8	211	182	161	144	130	118	109	101	

72 / 756.7	180	156	137	123	111	101	92.9	86	214	185	163	146	132	120	110	102
73 / 767.2	183	158	139	124	112	102	94.2	87.2	217	187	165	148	133	122	112	104
74 / 777.7	185	160	141	126	114	104	95.5	88.4	220	190	167	150	135	123	113	105
75 / 788.3	188	162	143	128	115	105	96.8	89.6	223	193	170	152	137	125	115	106
Flow Rate in lbs/hr - cc/min	BSFC - 80% Duty Cycle (Street)								BSFC - 95% Duty Cycle (Race)							
	.32	.37	.42	.47	.52	.57	.62	.67	.32	.37	.42	.47	.52	.57	.62	.67
76 / 798.8	190	164	145	129	117	107	98.1	90.7	226	195	172	154	139	127	116	108
77 / 809.3	193	166	147	131	118	108	99.4	91.9	229	198	174	156	141	128	118	109
78 / 819.8	195	169	149	133	120	109	101	93.1	232	200	176	158	143	130	120	111
79 / 830.3	198	171	150	134	122	111	102	94.3	235	203	179	160	144	132	121	112
80 / 840.8	200	173	152	136	123	112	103	95.5	238	205	181	162	146	133	123	113
81 / 851.3	203	175	154	138	125	114	105	96.7	240	208	183	164	148	135	124	115
82 / 861.8	205	177	156	140	126	115	106	97.9	243	211	185	166	150	137	126	116
83 / 872.3	208	179	158	141	128	116	107	99.1	246	213	188	168	152	138	127	118
84 / 882.8	210	182	160	143	129	118	108	100	249	216	190	170	153	140	129	119
85 / 893.4	213	184	162	145	131	119	110	101	252	218	192	172	155	142	130	121
86 / 903.9	215	186	164	146	132	121	111	103	255	221	195	174	157	143	132	122
87 / 914.4	218	188	166	148	134	122	112	104	258	223	197	176	159	145	133	123
88 / 924.9	220	190	168	150	135	124	114	105	261	226	199	178	161	147	135	125
89 / 935.4	223	192	170	151	137	125	115	106	264	229	201	180	163	148	136	126
90 / 945.9	225	195	171	153	138	126	116	107	267	231	204	182	164	150	138	128
91 / 956.4	228	197	173	155	140	128	117	109	270	234	206	184	166	152	139	129
92 / 966.9	230	199	175	157	142	129	119	110	273	236	208	186	168	153	141	130
93 / 977.4	233	201	177	158	143	131	120	111	276	239	210	188	170	155	143	132
94 / 987.9	235	203	179	160	145	132	121	112	279	241	213	190	172	157	144	133
95 / 998.5	238	205	181	162	146	133	123	113	282	244	215	192	174	158	146	135
96 / 1009	240	208	183	163	148	135	124	115	285	246	217	194	175	160	147	136
97 / 1019	243	210	185	165	149	136	125	116	288	249	219	196	177	162	149	138
98 / 1030	245	212	187	167	151	138	126	117	291	252	222	198	179	163	150	139
99 / 1040	248	214	189	169	152	139	128	118	294	254	224	200	181	165	152	140
100 / 1051	250	216	190	170	154	140	129	119	297	257	226	202	183	167	153	142
Flow Rate in lbs/hr - cc/min	BSFC - 80% Duty Cycle (Street)								BSFC - 95% Duty Cycle (Race)							
	.32	.37	.42	.47	.52	.57	.62	.67	.32	.37	.42	.47	.52	.57	.62	.67
101 / 1061	253	218	192	172	155	142	130	121	300	259	228	204	185	168	155	143
102 / 1072	255	221	194	174	157	143	132	122	303	262	231	206	186	170	156	145
103 / 1082	258	223	196	175	158	145	133	123	306	264	233	208	188	172	158	146
104 / 1093	260	225	198	177	160	146	134	124	309	267	235	210	190	173	159	147
105 / 1103	263	227	200	179	162	147	135	125	312	270	238	212	192	175	161	149
106 / 1114	265	229	202	180	163	149	137	127	315	272	240	214	194	177	162	150
107 / 1124	268	231	204	182	165	150	138	128	318	275	242	216	195	178	164	152
108 / 1135	270	234	206	184	166	152	139	129	321	277	244	218	197	180	165	153
109 / 1145	273	236	208	186	168	153	141	130	324	280	247	220	199	182	167	155
110 / 1156	275	238	210	187	169	154	142	131	327	282	249	222	201	183	169	156
111 / 1166	278	240	211	189	171	156	143	133	330	285	251	224	203	185	170	157
112 / 1177	280	242	213	191	172	157	145	134	333	288	253	226	205	187	172	159
113 / 1187	283	244	215	192	174	159	146	135	335	290	256	228	206	188	173	160
114 / 1198	285	246	217	194	175	160	147	136	338	293	258	230	208	190	175	162
115 / 1208	288	249	219	196	177	161	148	137	341	295	260	232	210	192	176	163
116 / 1219	290	251	221	197	178	163	150	139	344	298	262	234	212	193	178	164
117 / 1229	293	253	223	199	180	164	151	140	347	300	265	236	214	195	179	166
118 / 1240	295	255	225	201	182	166	152	141	350	303	267	239	216	197	181	167
119 / 1250	298	257	227	203	183	167	154	142	353	306	269	241	217	198	182	169
120 / 1261	300	259	229	204	185	168	155	143	356	308	271	243	219	200	184	170

COPYRIGHT © 2002-2011 [Stan Weiss](#) — World Wide Enterprises

Close This Window



[[Back to Home Page](#)]